



**pump
house**

^a **DIVERSiTECH** 
company

WHY PUMP HOUSE?



Products

We strive to deliver to you, our customers, the best products on the market, constantly innovating and improving. Our products are designed to save you time. We are the only company which covers the ancillary range for the HVACR market. **Your one stop shop!**



Wow factor

We are the solution provider for your logistic requirements. We listen to your requirements and provide the fastest response time within the industry. 95% of our Flexi Support Enquires are responded to within four working hours. **Try our service now!**



Experienced staff

We understand that each customer need is unique. Our team at Pump House respect and consider it in every decision we make. Face to face, over the phone or electronically - we are here to serve. Our sales and technical teams set the highest standards.



Technical Experts

We believe that delivering exceptional technical support is crucial to the success of our customers. All our staff are technically trained; we have a team of people ready to help you.



International

Globally connected operations within 30 countries across 5 continents. Customising our products and services to suit the individual needs of our international customer base.



Charitable Giving

We continue to support local charities such as Maytree Respite Centre whose voluntary work is inspiring and unconditional.

PUMP HOUSE PROVIDE THE



- 1. We answer all calls into the business within THREE rings**
- 2. We acknowledge all orders with a 'THANK YOU' phone call and an order confirmation email**
- 3. All after visit requests from our Area Sales Managers are actioned within 60 minutes**
- 4. We respond to 95% of all our Flexi Support Systems enquiries within 4 working hours**
- 5. Any customer requesting a quotation will receive a follow up call after the quotation has been sent**
- 6. We send catalogues and new literature with all orders to ensure our customers are kept up to date at all times**

TRY AND SEE!



Refrigeration



Refrigeration

Dairy Cabinet Supermarket Pumps

The Pump House dairy cabinet supermarket pumps can fit under low display cabinets due to being just 76mm in height. The multiple inlets offer a variety of installation options for the contractor.



| Code | Brand | Description | Tank Capacity | Max Flow | Dimensions mm (HxWxD) | Discharge Size (inches) |
|---------|------------|-------------------------------|---------------|----------|-----------------------|-------------------------|
| DCP-30A | Pump House | Dairy Cabinet Pump (Standard) | 5.5 litre | 700LPH | 76x200x610 | 1/2 |
| DCP-30E | Pump House | Dairy Cabinet Pump (No Lid) | 5.5 litre | 700LPH | 76x200x610 | 1/2 |
| DCP-30V | Pump House | Dairy Cabinet Pump (Vertical) | 4.5 litre | 700LPH | 200x580x76 | 1/2 |

Evaporator Tray

A thermostatically-controlled cast aluminium tray designed to collect and evaporate condensate water. Ideal for refrigeration display cabinets.



| Code | Brand | Description | Tank Capacity | Evaporation Rate | Dimensions mm (HxWxD) | Weight |
|--------|------------|-----------------|---------------|------------------|-----------------------|--------|
| ET-150 | Pump House | Evaporator Tray | 1.5 litres | 150ml per hour | 90x320x120 | 1.1kg |

Vibration Absorber

Designed for the installation of the suction and discharge lines of air conditioning and refrigeration systems. Used to dampen compressor-induced vibrations and reduce the damage to the system's pipe work.



| Part Code | Description | Tube OD (Inches) | Tube OD (mm) | Max. Working Pressure (psiG) | Burst Pressure (psiG) |
|------------|----------------------------------|------------------|--------------|------------------------------|-----------------------|
| VIBA-1/4 | Vibration Absorber 1/4 (6mm) | 1/4 | 6mm | 650 (44.8 bar) | 3250 (224 bar) |
| VIBA-3/8 | Vibration Absorber 3/8 (10mm) | 3/8 | 10mm | 650 (44.8 bar) | 3250 (224 bar) |
| VIBA-1/2 | Vibration Absorber 1/2 (12mm) | 1/2 | 12mm | 650 (44.8 bar) | 3250 (224 bar) |
| VIBA-5/8 | Vibration Absorber 5/8 (16mm) | 5/8 | 16mm | 650 (44.8 bar) | 3250 (224 bar) |
| VIBA-3/4 | Vibration Absorber 3/4 (18mm) | 3/4 | 18mm | 650 (44.8 bar) | 3250 (224 bar) |
| VIBA-7/8 | Vibration Absorber 7/8 (22mm) | 7/8 | 22mm | 650 (44.8 bar) | 3250 (224 bar) |
| VIBA-1-1/8 | Vibration Absorber 1-1/8 (28mm) | 1-1/8 | 28mm | 600 (41.3 bar) | 3000 (206.8 bar) |
| VIBA-1-3/8 | Vibration Absorber 1-3/8 (35mm) | 1-3/8 | 35mm | 550 (37.9 bar) | 2750 (189.6 bar) |
| VIBA-1-5/8 | Vibration Absorber 1-5/8 (42mm) | 1-5/8 | 42mm | 510 (35.1 bar) | 2550 (175.8 bar) |
| VIBA-2-1/8 | Vibration Absorber 2-1/8 (54mm) | 2-1/8 | 54mm | 400 (27.5 bar) | 2000 (137.8 bar) |
| VIBA-2-5/8 | Vibration Absorber 2-5/8 (64mm) | 2-5/8 | 64mm | 350 (24.1 bar) | 1750 (120.6 bar) |
| VIBA-3-1/8 | Vibration Absorber 3-1/8 (76mm) | 3-1/8 | 76mm | 320 (22.0 bar) | 1600 (110.3 bar) |
| VIBA-3-5/8 | Vibration Absorber 3-5/8 (89mm) | 3-5/8 | 89mm | 190 (13.1 bar) | 570 (39.3 bar) |
| VIBA-4-1/8 | Vibration Absorber 4-1/8 (108mm) | 4-1/8 | 108mm | 190 (13.1 bar) | 570 (39.3 bar) |

Klo-Shure® Clamps - Series 7

Klo-Shure® eliminates having to double-wrap, glue and tape the insulation on strut-mounted clamps. Klo-Shure insulation coupling reduces the time required to insulate copper tubing used for refrigerant lines. The patented clamp allows sections of closed-cell insulation to be secured at fixing points.



| | Size in inches | | Insulation Wall Thickness | | | |
|----------------|----------------|--------|---------------------------|--------|--------|--------|
| | | | 3/8" | 1/2" | 3/4" | 1" |
| Copper Pipe ID | 1/4" | 723025 | | 724025 | 726025 | 728025 |
| | 3/8" | 723037 | | 724037 | 726037 | 728037 |
| | 1/2" | 723050 | | 724050 | 726050 | 728050 |
| | 5/8" | 723062 | | 724062 | 726062 | 728062 |
| | 3/4" | 723075 | | 724075 | 726075 | 728075 |
| | 7/8" | 723087 | | 724087 | 726087 | 728087 |
| | 1" | 723100 | | 724100 | - | - |
| | 1-1/8" | 723112 | | 724112 | 726112 | 728112 |
| | 1-3/8" | 723137 | | 724137 | 726137 | 728137 |
| | 1-5/8" | 723162 | | 724162 | 726162 | 728162 |
| | 2-1/8" | 723212 | | 724212 | 726212 | 728212 |
| | 2-5/8" | - | | 724262 | 726262 | 728262 |
| | 3-1/8" | - | | 724312 | 726312 | 728312 |
| | 3-5/8" | - | | 724362 | 726362 | 728362 |
| | 4-1/8" | - | | 724412 | 726412 | 728412 |



Easy-Fit



Flange



Flare



Install



Partners



PH Family



PH Motors



Portable



Service



Squeeze



Refrigeration

Universal Multi-Fit Fan Motors

Universal, multi-fit fan motors are individually boxed and come complete with fixings. The 1 metre power cord offers flexibility during installation. CE certified / ROHS-2 compliant.



| Code | Description | Watts | Voltage | Frequency | Revs | Cable Length |
|--------|-------------------------------------|-------|---------|-----------|---------------|--------------|
| FM-5W | Universal Multi-Fit Fan Motor - 5W | 5W | 240V | 50/60Hz | 1300/1500 rpm | 1m |
| FM-7W | Universal Multi-Fit Fan Motor - 7W | 7W | 240V | 50/60Hz | 1300/1500 rpm | 1m |
| FM-10W | Universal Multi-Fit Fan Motor - 10W | 10W | 240V | 50/60Hz | 1300/1500 rpm | 1m |
| FM-16W | Universal Multi-Fit Fan Motor - 16W | 16W | 240V | 50/60Hz | 1300/1500 rpm | 1m |
| FM-18W | Universal Multi-Fit Fan Motor - 18W | 18W | 240V | 50/60Hz | 1300/1500 rpm | 1m |
| FM-25W | Universal Multi-Fit Fan Motor - 25W | 25W | 240V | 50/60Hz | 1300/1500 rpm | 1m |
| FM-34W | Universal Multi-Fit Fan Motor - 34W | 34W | 240V | 50/60Hz | 1300/1500 rpm | 1m |

Tangential Fan Motors

Tangential single-impeller fan motor assemblies with aluminium blades. Individually boxed complete with fixings. CE certified / ROHS-2 compliant.



| Code | Description | Watts | Blade Length | Rotate Speed | Air Flow |
|--------------|---|-------|--------------|--------------|----------|
| FMTS-15W-120 | Tangential Fan Motor 15W with 120mm Blade | 15W | 120mm | 2200rpm | 80m³/h |
| FMTS-20W-120 | Tangential Fan Motor 20W with 180mm Blade | 20W | 180mm | 2000rpm | 120m³/h |
| FMTS-30W-240 | Tangential Fan Motor 30W with 240mm Blade | 30W | 240mm | 2100rpm | 170m³/h |
| FMTS-30W-300 | Tangential Fan Motor 30W with 300mm Blade | 30W | 300mm | 1900rpm | 190m³/h |

Axial Fan Motors

Axial shaded fan motors have a compact structure and small volume. Lightweight, low noise and used on refrigeration equipment. Individually boxed, CE certified / ROHS-2 compliant, these motors have an ambient operating temperature -20°C to +60°C



| Code | Description | Watts | Voltage | Frequency | Revs | Cable Length | Air Flow | Db(A) Rating |
|--------------|---------------------------------------|-------|---------|-----------|---------|--------------|----------|--------------|
| FM-A-8038-L | Axial Fan Motor - 15W (with lead) | 15W | 240V | 50Hz | 2200rpm | 30mm | 40m³/h | 23.4 |
| FM-A-12025-L | Axial Fan Motor - 13W (with lead) | 13W | 240V | 50Hz | 1800rpm | 30mm | 71m³/h | 35.6 |
| FM-A-12038-L | Axial Fan Motor - 20W (with lead) | 20W | 240V | 50Hz | 2500rpm | 30mm | 132m³/h | 37.3 |
| FM-A-12038-T | Axial Fan Motor - 20W (with terminal) | 20W | 240V | 50Hz | 2500rpm | - | 132m³/h | 37.3 |

| Code | Description | Watts | Height | Dimensions in (mm) | Depth |
|--------------|---------------------------------------|-------|--------|--------------------|-------|
| FM-A-8038-L | Axial Fan Motor - 15W (with lead) | 15W | 80mm | Width | 38mm |
| FM-A-12025-L | Axial Fan Motor - 13W (with lead) | 13W | 120mm | 120mm | 26mm |
| FM-A-12038-L | Axial Fan Motor - 20W (with lead) | 20W | 120mm | 120mm | 38mm |
| FM-A-12038-T | Axial Fan Motor - 20W (with terminal) | 20W | 120mm | 120mm | 38mm |

Fan Motor Assemblies

A complete range of pressed aluminium blades, fan rings, guards and brackets to suit our range of multi-fit fan motors. Available in a variety of diameters and pitches to suit most refrigeration applications. All accessories can be sold as individual items or as a complete assembly combined to create your own fan requirements.



| Code | Description | Diameter | Pitch |
|------------|--------------------|----------|-------|
| FBS-154-25 | Fan Blade - Sucker | 154mm | 25° |
| FBS-154-31 | Fan Blade - Sucker | 154mm | 31° |
| FBS-172-25 | Fan Blade - Sucker | 172mm | 25° |
| FBS-172-31 | Fan Blade - Sucker | 172mm | 31° |
| FBS-200-25 | Fan Blade - Sucker | 200mm | 25° |
| FBS-200-31 | Fan Blade - Sucker | 200mm | 31° |
| FBS-230-25 | Fan Blade - Sucker | 230mm | 25° |
| FBS-230-31 | Fan Blade - Sucker | 230mm | 31° |
| FBS-254-25 | Fan Blade - Sucker | 254mm | 25° |
| FBS-254-31 | Fan Blade - Sucker | 254mm | 31° |
| FBS-300-25 | Fan Blade - Sucker | 300mm | 25° |
| FBS-300-31 | Fan Blade - Sucker | 300mm | 31° |

| Code | Description | Diameter | Pitch |
|------------|--------------------|----------|-------|
| FBB-154-25 | Fan Blade - Blower | 154mm | 25° |
| FBB-154-31 | Fan Blade - Blower | 154mm | 31° |
| FBB-172-25 | Fan Blade - Blower | 172mm | 25° |
| FBB-172-31 | Fan Blade - Blower | 172mm | 31° |
| FBB-200-25 | Fan Blade - Blower | 200mm | 25° |
| FBB-200-31 | Fan Blade - Blower | 200mm | 31° |
| FBB-230-25 | Fan Blade - Blower | 230mm | 25° |
| FBB-230-31 | Fan Blade - Blower | 230mm | 31° |
| FBB-254-25 | Fan Blade - Blower | 254mm | 25° |
| FBB-254-31 | Fan Blade - Blower | 254mm | 31° |
| FBB-300-25 | Fan Blade - Blower | 300mm | 25° |
| FBB-300-31 | Fan Blade - Blower | 300mm | 31° |

| Code | Description | Diameter |
|---------|-------------|----------|
| FRS-154 | Fan Ring | 154mm |
| FRS-172 | Fan Ring | 172mm |
| FRS-200 | Fan Ring | 200mm |
| FRS-230 | Fan Ring | 230mm |
| FRS-254 | Fan Ring | 254mm |
| FRS-300 | Fan Ring | 300mm |

| Code | Description | Diameter |
|--------|-------------|----------|
| FG-154 | Fan Guard | 154mm |
| FG-172 | Fan Guard | 172mm |
| FG-200 | Fan Guard | 200mm |
| FG-230 | Fan Guard | 230mm |
| FG-254 | Fan Guard | 254mm |
| FG-300 | Fan Guard | 300mm |

| Code | Height | Width | Depth |
|-----------|--------|-------|-------|
| FBR-109-1 | 109mm | 81mm | 24mm |
| FBR-109-2 | 109mm | 78mm | 39mm |
| FBR-109-3 | 109mm | 78mm | 49mm |
| FBR-39 | 39mm | - | - |
| FBR-55 | 55mm | - | - |
| FBR-72 | 72mm | - | - |
| FBR-84 | 84mm | - | - |



Easy-Fit



Fixings



Flare



Install



Partners



Pet Family



Pet Motors



Portable



Service



Squeeze

Refrigeration

Rotary Enclosed Isolators

Our insulated 3 and 4 pole rotary enclosed isolators are CE marked and suitable for disconnecting the power supply to outdoor air conditioning units.

The isolators are weatherproof to IP65, easy to install and conform to IEC 60947-3. They have a lockable off position and interlocking cover which can be removed only in the off position. Earth and neutral terminals included and M20/25 knockouts up to 63A.



| Code | No. of poles | Amps AC21 | AC23A 240VA | AC23A 400VA | Cable Capacity Solid | Cable Capacity Stranded | Height | Width | Depth |
|-------------|--------------|-----------|-------------|-------------|----------------------|-------------------------|--------|-------|-------|
| IS-3P-20A | 3 | 20 Amp | 5.5 kW | 3.7 kW | 1-16mm ² | 0.75-10mm ² | 175mm | 114mm | 135mm |
| IS-3P-32A | 3 | 32 Amp | 11 kW | 7.5 kW | 1-16mm ² | 0.75-10mm ² | 175mm | 114mm | 135mm |
| IS-3P-40A | 3 | 40 Amp | 15 kW | 11 kW | 1-16mm ² | 0.75-10mm ² | 175mm | 114mm | 135mm |
| IS-3P-63A | 3 | 63 Amp | 22 kW | 18.5 kW | 1-16mm ² | 0.75-10mm ² | 175mm | 114mm | 135mm |
| IS-4P-20A-S | 4 | 20 Amp | 5.5 kW | 3.7 kW | 1-16mm ² | 0.75-10mm ² | 125mm | 100mm | 120mm |
| IS-4P-20A | 4 | 20 Amp | 5.5 kW | 3.7 kW | 1-16mm ² | 0.75-10mm ² | 175mm | 114mm | 135mm |
| IS-4P-32A-S | 4 | 32 Amp | 11 kW | 7.5 kW | 1-16mm ² | 0.75-10mm ² | 125mm | 100mm | 120mm |
| IS-4P-32A | 4 | 32 Amp | 11 kW | 7.5 kW | 1-16mm ² | 0.75-10mm ² | 175mm | 114mm | 135mm |
| IS-4P-40A | 4 | 40 Amp | 15 kW | 11 kW | 1-16mm ² | 0.75-10mm ² | 175mm | 114mm | 135mm |
| IS-4P-63A | 4 | 63 Amp | 22 kW | 18.5 kW | 1-16mm ² | 0.75-10mm ² | 175mm | 114mm | 135mm |

Easy~Fit Protective Housings

Easy~Fit housings are manufactured in two sizes and are ideal for all brands of outdoor refrigeration condensing equipment.


The steel goes through an 8-phase epoxy polyester powder coating process and is finished with a scratch resistant textured finish in RAL 7032.



| Code | Size | External Dimensions mm (HxWxD) | | | Internal Dimensions mm (HxWxD) | | | Weight |
|------|-------|-----------------------------------|-----|-----|-----------------------------------|-----|-----|--------|
| CH-S | Small | 500 | 710 | 600 | 410 | 640 | 530 | 23kg |
| CH-L | Large | 550 | 810 | 720 | 460 | 740 | 640 | 30kg |

Refrigerant ID Labels

A range of self adhesive vinyl labels. Each label indicates the type of refrigerant and come in a handy pack of 10. We also supply pipe labels. Avoid costly mistakes by properly identifying the type of refrigerant contained in recovery cylinders and air conditioning and refrigeration equipment. Contact us for more information.



Air Conditioning





Dairy Cabinet Pump with IP54 splash-proof enclosure



- Industry leading IP54 dairy cabinet pump
- 1/2" barbed hose tail – for easy connection
- Multiple inlet options (top, end or side)
- Power and alarm cables pre-fitted
- High discharge head and flow rate suitable for most applications
- Splash-proof enclosure
- One year warranty



Scan the QR for the video!



Tank Pumps

Pump House stock a range of various branded condensate removal tank pumps.



PH-1L / PH-1LSS



PH-1-SILENCE



VCC-20S



VCMX-20S



VCMA-20S



PH-2-SILENCE



PH-2L / PH-2LSS



VCL-24S



VCL-45S

| Code | Brand | Description | Max Head | Max Flow | dB(A) | Dimensions mm (HxWxD) | Discharge Size (inch) |
|------------------|--------------|---------------------|----------|----------|-------|-----------------------|-----------------------|
| PH-1L / PH-1L-SS | Pump House | 1 Litre Tank Pump | 6m | 270LPH | 43 | 122x220x134 | 3/8 |
| PH-1-SILENCE | Pump House | 0.6 Litre Tank Pump | 6m | 14LPH | 12 | 127x170x81 | 1/4 |
| VCC-20S | Little Giant | 1 Litre Tank Pump | 4.3m | 294LPH | 58-62 | 125x300x125 | 1/4 & 3/8 |
| VCMX-20S | Little Giant | 1.4 Litre Tank Pump | 4.8m | 284LPH | 58 | 165x260x122 | 1/4 & 3/8 |
| VCMA-20S | Little Giant | 1.9 Litre Tank Pump | 4.3m | 294LPH | 58-62 | 178x288x127 | 1/4 & 3/8 |
| PH-2L / PH-2L-SS | Pump House | 2 Litre Tank Pump | 4.8m | 300LPH | 60 | 180x290x130 | 1/4 & 3/8 |
| PH-2-SILENCE | Pump House | 2.2 Litre Tank Pump | 6m | 14LPH | 12 | 165x250x135 | 1/4 |
| VCL-24S | Little Giant | 3.8 Litre Tank Pump | 5.9m | 900LPH | 58-62 | 263x305x150 | 1/4 & 3/8 |
| VCL-45S | Little Giant | 3.8 Litre Tank Pump | 10.5m | 1560LPH | 58-62 | 267x305x150 | 3/8 |



Easy-Fit



Fixings



Flexi



Install +



Partners



PH Family



PH Motors



Portable



Service +



Squeezy

Condensate Pumps & Accessories

Mini Pumps

Pump House stock a range of mini condensate pumps ideal for split air conditioning systems, small enough to be placed in the unit or within trunking. We also provide mini pump options that come with an elbow and length of trunking.



EC-400 Pump Only



EC-1 Pump Only



EC-1 KIT with elbow and trunking



DE-05-FD Flowwatch Design®
with elbow and trunking

| Code | Brand | Description | Max Head | Max Flow | dB(A) | Dimensions mm (HxWxD) | Discharge Size |
|----------|--------------|-------------------------|----------|----------|-------|--------------------------|----------------|
| EC-400 | Little Giant | Mini Pump | 12m | 14LPH | 58 | 45x110x35 | 1/4 inch |
| EC-1 | Little Giant | Mini Pump | 10m | 10LPH | 21 | 104x46x58 | 1/4 inch |
| EC-1 KIT | Little Giant | Mini Pump with Trunking | 10m | 10LPH | 21 | 104X46X58 | 1/4 inch |
| DE-05-FD | Siccor | Mini Pump with Trunking | 10m | 12LPH | <21 | 800X150x80 | 1/4 inch |

Peristaltic Pumps

Pump House stock three versions of the Little Giant Peristaltic Pump.



TPT with Temperature Sensor



TPS with Sensor



TPR with Reservoir & Alarm



TPRC-10



EXTCABLE



599325

| Code | Brand | Description | Max Head | Max Flow | Dimensions mm (HxWxD) | Discharge Size |
|----------|--------------|--|----------|----------|-----------------------|----------------|
| TPS | Little Giant | Peristaltic Pump with Sensor | 14m | 9.5LPH | 115x96x98 | 1/4 inch |
| TPT | Little Giant | Peristaltic Pump with Temperature Sensor | 14m | 9.5LPH | 115x96x98 | 1/4 inch |
| TPR | Little Giant | Peristaltic Pump with Reservoir | 14m | 9.5LPH | 115x96x98 | 1/4 inch |
| TPRC-10 | Little Giant | Peristaltic Replacement Tube | | | | |
| EXTCABLE | Little Giant | Peristaltic Sensor Extension Cable – 4 metres | | | | |
| 599325 | Little Giant | Peristaltic Service Kit – 2 replacement tubes and rotation wheel | | | | |



Easy-Fit



Fixings



Flexi



Install +



Partners



PH Family



PH Motors



Portable



Service +



Squeezy

Condensate Pumps & Accessories

Pressure Relief & Boiler Condensate Pump - PRV*Sure*

This pump is manufactured from high temperature plastic, and comes complete with 10m of higher specification hose.

It meets EN Standards and can handle temperatures up to 110 degrees. Supplied with 10 metres of 'no sag' high grade braided hose. The unique design also cools the PRV discharge so it is safe for use with solvent weld pipework. For installers who are audited or working to EN Standards.



PH-3.8L-HW

| Code | Brand | Description | Max Head | Max Flow | Temperature | Dimensions mm (HxWxD) | Discharge Size |
|------------|------------|--|----------|----------|-------------|-----------------------|------------------|
| PH-3.8L-HW | Pump House | Pressure Relief & Boiler Condensate Pump | 8m | 312LPH | 110°C | 249x325x160 | 3/8 inch (9.5mm) |

High Temperature Pressure Relief Pump - PH-5L-HW

Designed for unvented cylinder T&P discharge and steam humidifiers. Having one of the largest discharge rates of 32 litres per minute this pump can handle both high temperature up to 100 degrees and high flow rates.

Manufactured in the UK this heavy duty, high temperature tank pump incorporates thermal overload protection and a high level alarm switch.



PH-5L-HW

| Code | Brand | Description | Max Head * | Max Flow | Temperature | Dimensions mm (HxWxD) | Discharge Size |
|----------|------------|---|------------|------------------|-------------|-----------------------|----------------|
| PH-5L-HW | Pump House | High Temperature & Pressure Relief Pump | 8m / 20m | 1920LPH / 32 LPM | 100°C | 350x190x260 | (15mm) |

* Max Heads - 8 metre for flow rates up to 25 Litres per minute / 20 metre for flow rates of 5 Litres per minute

Adaptors

Pump House stock a range of adaptors to connect the unit and pump.



| Code | Description | Pump Type Application | Pack Qty |
|-------------|---|---------------------------------|----------|
| ADAP-CAC-S | Cassette Adaptor - Small (Green) 3/4" x 1" | Tank Pump | 3 Pack |
| ADAP-CAC-M | Cassette Adaptor - Medium (Blue) 3/4" x 1-1/4" | Tank Pump | 3 Pack |
| ADAP-CAC-L | Cassette Adaptor - Large (Black) 3/4" x 1-1/2" | Tank Pump | 3 Pack |
| ADAP-CAC-X | Cassette Adaptor - Multipack | Tank Pump | 3 Pack |
| ADAP-1 | Condensate Drain Adaptor - 22mm to 3/8" | Tank Pump - 9.5mm (3/8") outlet | Single |
| ECOP-ADAP | Condensate Drain Adaptor - 16,18,22,35mm to 1/4" Hose | All Pumps | Single |
| CV-38-3 | Non-return check valve - 3/8" (9.5mm) | Tank Pump - 9.5mm (3/8") outlet | 3 Pack |
| CV-14-3 | Non-return check valve - 1/4" | Tank Pump - (1/4") outlet | 3 Pack |
| PH-PUMP-NRV | Non-return check valve - 3/8" (9.5mm) | Tank Pump - 9.5mm (3/8") outlet | Single |
| 154724 | Non-return check valve - 3/8" (9.5mm) | VCMX-20s pump | Single |

Self-Sealing Pipe Adaptor

The self-sealing adaptor is used to form a connection between condensate hose and a soil & vent pipe. Drill a 13mm hole (for SVA-3) or a 10mm hole (for SVA-6). Insert and twist in to seal the connection.



SV-ADAPTOR



SV-ADAPTOR-6

| Code | Description | Pack Qty |
|--------------|--|----------|
| SVA-3 | Self-sealing pipe adaptor - 6mm & 9.5mm (1/4 & 3/8) hose to soil & vent pipe | 3 Pack |
| SV-ADAPTOR | Self-sealing pipe adaptor - 6mm & 9.5mm (1/4 & 3/8) hose to soil & vent pipe | Single |
| SVA-6-3 | Self-sealing pipe adaptor - 6mm (1/4) hose to soil & vent pipe | 3 pack |
| SV-ADAPTOR-6 | Self-sealing pipe adaptor - 6mm (1/4) hose to soil & vent pipe | Single |

Audible Alarm

This audible alarm can be wired into all pumps with a high level alarm switch.



| Code | Brand | Description | Pack Qty |
|---------------|--------------|--|----------|
| AUDIBLE ALARM | Little Giant | Audible Alarm for all pumps with a high level alarm switch | Single |



Easy-Fit



Fixings



Flexi



Install +



Partners



PH Family



PH Motors



Portable



Service +



Squeazy

Condensate Pumps & Accessories

Condensate Braided Hose

Our reinforced PVC braided hose is suitable for condensate drains and comes packaged in clear shrink wrap for protection and easy storage. The black hose has no light penetration, which prevents build up of mould growth.

Available in clear and black, in 5m & 30m coils.



| Code | Colour | Description | ID | OD | Pressure in Bar | | Min Bend Radius | Min Temp* | Max Temp |
|-----------|--------|------------------|------|------|-----------------|-------|-----------------|-----------|----------|
| | | | | | Working | Burst | | | |
| RVT-1/2-6 | Clear | 1/2" x 6 metres | 12mm | 16mm | 6 | 18 | 30° | -15°C | +60°C |
| RVT-3/4-6 | Clear | 3/4" x 6 metres | 19mm | 23mm | 6 | 18 | 30° | -15°C | +60°C |
| RVT-1/4 | Clear | 1/4" x 30 metres | 6mm | 10mm | 7 | 21 | 30° | -15°C | +60°C |
| RVT-3/8 | Clear | 3/8" x 30 metres | 10mm | 14mm | 8 | 24 | 30° | -15°C | +60°C |
| RVT-1/2 | Clear | 1/2" x 30 metres | 12mm | 16mm | 6 | 18 | 30° | -15°C | +60°C |
| RVT-5/8 | Clear | 5/8" x 30 metres | 16mm | 20mm | 6 | 18 | 30° | -15°C | +60°C |
| RVT-1/4-B | Black | 1/4" x 30 metres | 6mm | 10mm | 7 | 21 | 30° | -15°C | +60°C |
| RVT-3/8-B | Black | 3/8" x 30 metres | 10mm | 14mm | 8 | 24 | 30° | -15°C | +60°C |
| RVT-1/2-B | Black | 1/2" x 30 metres | 12mm | 16mm | 6 | 18 | 30° | -15°C | +60°C |

* Hose stored in conditions above +5°C will be easier to handle/install.

Clear Vinyl Hose

Applications include air conditioning and refrigeration condensate drains, condensate pump discharge lines and humidifier overflows. Available in 15m and 30m coils, the clear vinyl hose comes packed in a box making it easier to use and store.



| Code | Colour | Description | ID | OD | Quantity |
|--------|--------|------------------|------|------|-----------|
| VT-1/4 | Clear | 1/4" x 30 metres | 6mm | 10mm | 30 metres |
| VT-3/8 | Clear | 3/8" x 30 metres | 10mm | 14mm | 30 metres |

Hose Connectors & Clamps

A range of Nylon hose connectors & clamps, to connect hose and secure fitting to prevent leaks.



701-038

701-030



B-6H

| Code | Description | Pack Qty |
|---------|------------------------------|----------|
| 701-030 | Hose Connector – Nylon 1/4 | Single |
| 701-032 | Hose Connector – Nylon 3/8 | Single |
| 701-038 | Hose T Connector – Nylon 3/8 | Single |
| B-4H | Hose Clamp – 3/16 – 5/16 | Single |
| B-6H | Hose Clamp – 1/4 – 3/8 | Single |

Condensate Cop™

Condensate Cop™ is a unique clamp-on float switch intended for HVAC drain pan installation. The Condensate Cop™ features a large over-clamping area that fits easily over the edge of all types of drain pans; including formed plastic and galvanized sheet metal. A separate float/probe assembly swivels to accommodate drain pans having sloped sides. The swivel action allows the installer to position the float switch for best operation and then clamp it into place. The probe features an inlet grill which prevents the float from being blocked or damaged by insulation or other debris. Sealed inside the probe is a magnetically actuated normally closed switch. The switch opens when rising water presents a potential flooding condition.



| Code | Description | UOM | Master Qty |
|------|----------------------------------|------|------------|
| CC-1 | Condensate Cop™ Drain Pan Switch | Each | 12 |

CS1200 AC Shutoff Switch

The CS1200 is an easy to install, reliable, condensate overflow detection switch. Featuring a unique universal pan mount design to assure accurate detection in metal or plastic secondary drain pans.



| Code | Description | UOM | Master Qty |
|--------|-------------------|------|------------|
| CS1200 | AC Shutoff Switch | Each | 12 |

Drain Dawg™

The Drain Dawg™ is a complete condensate drain cleaning kit, including the CT-475M deluxe nitrogen / CO₂ 0-475 psi regulator, the TG-10 & BS-25 ten foot hose and blowgun assembly, and the CW-15 fifteen inch whip hose. Also included is the AP-DD Drain Dawg™ Accessory Fitting Kit which contains the DF-75 Drain Dawg™ inflatable tip, the CK-141 3/4"-1" cone fitting, the FA-02 CO₂ to nitrogen adaptor, the QN-S3 needle tip, and the TC-25 tyre chuck.



| Code | Description | UOM | Master Qty |
|------|-----------------|------|------------|
| CB-2 | Drain Dawg™ Kit | Each | 3 |

Drain Kat™

The Drain Kat™ is an over the shoulder, refillable, nitrogen or CO₂ mini drain cleaning kit. Featuring a small cylinder that holds 9 cubic feet of nitrogen or 2-1/2 pounds of CO₂. The cylinder includes an integral mounted regulator for a quick and easy adjustment of discharge pressure.

| Code | Description | UOM | Master Qty |
|-------|----------------|------|------------|
| MBK-6 | Drain Kat™ Kit | Each | 2 |



Easy-Fit



Fixinga



Flexi



Install +



Partners



PH Family



PH Motors



Portable



Service +



Squeeze

Other Pumps

Magnetic Drive Pumps - MD-SC / MD-HC Series

Little Giant magnet driven pumps feature a leak proof design that allows the pumps to be used in a variety of applications where continuous and reliable operation is desired and when pumping corrosive liquid is necessary.

The MD-SC Series is designed to pump mild to strong acids found in electroplating applications with temperatures up to 66°C. The MD-HC series can pump strong acids and alkaline solutions, including sulphuric nitric and hydrochloric acid with temperatures up to 93°C. In addition, the HC series offers "Run Dry" protection.



TE-3-MD-SC



TE-3-MD-HC



TE-4-MD-SC



TE-4-MD-HC



TE-5-MD-SC



TE-5-MD-HC



TE-5.5-MD-SC



TE-5.5-MD-HC



TE-6-MD-SC



TE-6-MD-HC



TE-7-MD-SC



TE-7-MD-HC

| Code | Brand | Description | Max Head | Max Flow | Liquid Temp. in °C | Inlet Size (inch) | Discharge Size (inch) |
|-------------|--------------|----------------------------------|----------|----------|--------------------|-------------------|-----------------------|
| TE3-MD-SC | Little Giant | Magnetic Drive TE3 Series Pump | 3.5m | 1980LPH | 66°C | 1" FNPT | 1/2" MNPT |
| TE3-MD-HC | Little Giant | Magnetic Drive TE3 Series Pump | 3.5m | 2100LPH | 93.3°C | 1" FNPT | 1/2" MNPT |
| TE4-MD-SC | Little Giant | Magnetic Drive TE4 Series Pump | 4.9m | 2940LPH | 66°C | 1" FNPT | 1/2" MNPT |
| TE4-MD-HC | Little Giant | Magnetic Drive TE4 Series Pump | 4.9m | 2940LPH | 93.3°C | 1" FNPT | 1/2" MNPT |
| TE5-MD-SC | Little Giant | Magnetic Drive TE5 Series Pump | 6.2m | 3660LPH | 66°C | 1" FNPT | 1/2" MNPT |
| TE5-MD-HC | Little Giant | Magnetic Drive TE5 Series Pump | 6.2m | 3660LPH | 93.3°C | 1" FNPT | 1/2" MNPT |
| TE5.5-MD-SC | Little Giant | Magnetic Drive TE5.5 Series Pump | 8.8m | 6120LPH | 66°C | 1" FNPT | 3/4" MNPT |
| TE5.5-MD-HC | Little Giant | Magnetic Drive TE5.5 Series Pump | 8.8m | 6120LPH | 82.2°C | 1" FNPT | 3/4" MNPT |
| TE6-MD-SC | Little Giant | Magnetic Drive TE6 Series Pump | 10.7m | 7500LPH | 66°C | 1" FNPT | 3/4" MNPT |
| TE6-MD-HC | Little Giant | Magnetic Drive TE6 Series Pump | 10.7m | 7500LPH | 82.2°C | 1" FNPT | 3/4" MNPT |
| TE7-MD-SC | Little Giant | Magnetic Drive TE7 Series Pump | 12.3m | 9540LPH | 66°C | 1-1/2" FNPT | 1" MNPT |
| TE7-MD-HC | Little Giant | Magnetic Drive TE7 Series Pump | 12.3m | 9540LPH | 93.3°C | 1-1/2" FNPT | 1" MNPT |

Pool Cover Pump - APCP-1700 (577309)

Little Giant Pool Cover Pumps help safeguard and protect the pool cover from prolonged accumulation of rain or melting snow. This automatic version is certified for use on pool covers, all of which can attach to a standard garden hose for easy water removal. It removes standing water from pool covers and is ideal for household water transfer applications.



APCP-1700

| Code | Brand | Description | Max Head | Max Flow | Dimensions mm (HxWxD) | Discharge Size (inch) | Weight |
|-----------|--------------|---------------------------|----------|----------|-----------------------|-----------------------|--------|
| APCP-1700 | Little Giant | Automatic Pool Cover Pump | 6.6m | 6814LPH | 210x305x305 | 1" FNPT | 5.4kg |

Parts Washer Pump 1Y-PW (501027) PE2-YSA (14940101)

Submersible, unpainted, aluminium housing pumps with Viton® seals, 1/4" MNPT discharge, master builders conduit fitting. The PE pumps have an epoxy encapsulated motor.



1Y-PW



PE2-YSA

| Code | Brand | Description | Max Head | Max Flow | Dimensions mm (WxD) | Discharge Size (inch) | Weight |
|-------|--------------|---------------------------|----------|----------|---------------------|-----------------------|--------|
| 1Y-PW | Little Giant | Automatic Pool Cover Pump | 6.6m | 6814LPH | 117x109 | 1/4" MNPT | 5.4kg |

| Code | Brand | Description | Max Head | Max Flow | Dimensions mm (HxWxD) | Discharge Size (inch) | Weight |
|---------|--------------|------------------------|----------|----------|-----------------------|-----------------------|--------|
| PE2-YSA | Little Giant | Small Submersible Pump | 3.8m | 1135LPH | 142x137x73 | 1/4" MNPT | 2kg |

Other Little Giant Pumps are available - if you have a specific requirement and would like to find a pump please contact us via e-mail sales@pumpph.co.uk or visit our website www.pumpph.co.uk for more information and technical details.



Easy-Fit



Fixings



Flexi



Install +



Partners



PH Family



PH Motors



Portable



Service +



Squeazy

Condensing Unit Guards

Easy~Fit Condensing Guards

Pump House manufacture a range of weather-resistant, steel mesh guards, offering a safe solution to vandalism and accidental damage of your expensive AC unit or ASHP. The range is ideal for all manufacturers of air conditioning and air source heat pump units. The unique sliding panel system allows for easy installation, which are secured into place when the front panel is fitted. Back panels are also available to make the guard free standing. For wall mounted units, we can offer a base panel for full security.



| Code | Size | External Dimensions mm (HxWxD) | | | Internal Dimensions mm (HxWxD) | | | Weight |
|--------------|-------|-----------------------------------|------|------|-----------------------------------|------|------|--------|
| CG-S | S | 750 | 1050 | 450 | 720 | 1020 | 450 | 18kg |
| CG-M | M | 1150 | 1150 | 650 | 1120 | 1120 | 640 | 27kg |
| CG-L | L | 1450 | 1150 | 650 | 1420 | 1120 | 640 | 30kg |
| CG-XL | XL | 1800 | 1150 | 650 | 1770 | 1120 | 640 | 40kg |
| CG-500-S | S | 620 | 1050 | 500 | 590 | 990 | 470 | 13kg |
| CG-500-M | M | 1020 | 1050 | 500 | 990 | 990 | 470 | 18kg |
| CG-500-L | L | 1420 | 1050 | 500 | 1390 | 990 | 470 | 23kg |
| CG-750-S | S | 950 | 1150 | 750 | 920 | 1120 | 740 | 25kg |
| CG-750-M | M | 1150 | 1150 | 750 | 1120 | 1120 | 740 | 32kg |
| CG-750-L | L | 1450 | 1150 | 750 | 1420 | 1120 | 740 | 33kg |
| CG-750-INV | INV | 1150 | 1450 | 750 | 1120 | 1420 | 740 | 33kg |
| CG-900L-INV | L-INV | 1150 | 1450 | 900 | 1120 | 1420 | 890 | 34kg |
| CG-900L-SQ | L-SQ | 1450 | 1450 | 900 | 1420 | 1370 | 890 | 51kg |
| CG-900-XXL | XXL | 1800 | 1450 | 900 | 1770 | 1370 | 890 | 60kg |
| CG-VRF-BP | BP-S | 2000 | 1160 | 1200 | 1970 | 1130 | 1200 | 64kg |
| CG-VRF-EP-6 | EP-S | 2000 | 580 | 1200 | 1970 | | 1200 | 24kg |
| CG-VRF-EP-12 | EP-M | 2000 | 1160 | 1200 | 1970 | | 1200 | 41kg |

Easy~Fit Wooden Guards

Made from tanalised, pressure-treated timber. All panels are louvered to optimise air flow. Sized to protect both ASHP and AC units, these guards offer a solution for listed buildings and sites where aesthetics are a consideration. All components are flat packed, easy to install, assemble and transport.



| Code | Size | External Dimensions mm (HxWxD) | | | Internal Dimensions mm (HxWxD) | | | Weight |
|-----------------|--------|-----------------------------------|------|-----|-----------------------------------|------|-----|--------|
| CG-750S-WOOD | S | 905/960 | 1275 | 865 | 850/890 | 1055 | 753 | 35kg |
| CG-750M-WOOD | M | 1135/1135 | 1275 | 865 | 1075/1115 | 1055 | 753 | 40kg |
| CG-750M+WOOD | M+ | 255/1310 | 1275 | 865 | 1200/1240 | 1055 | 753 | 44kg |
| CG-750L-WOOD | L | 1530/1585 | 1275 | 865 | 1475/1515 | 1055 | 753 | 51kg |
| CG-750LINV-WOOD | L-INV | 1130/1185 | 1630 | 865 | 1075/1115 | 1405 | 753 | 47kg |
| CG-750L+WOOD | L+ | 1600/1655 | 1275 | 865 | 1545/1585 | 1055 | 753 | 57kg |
| CG-750L+INVWOOD | L+ INV | 1655/1690 | 1630 | 865 | 1580/1620 | 1405 | 753 | 59kg |

Easy~Fit Brackets



Pump House offer a range of flat packed brackets, the Type 1 bracket has uprights and mounts directly onto the wall. Type 2 comes with a crossbar so that the uprights can be spaced exactly as required. The integral spirit level makes installation easier. Type 3 brackets have a unique interlocking mechanism enabling the arms to be joined in a matter of seconds.

For improved corrosion resistance all metal receives a 100% zinc plating, followed by a hard ED coating, before being finished with an external grade polyester textured powder coating in RAL 7032.



For lighter condensing units we offer an economy version. This incorporates the traditional crossbar style for easy spacing of the support arms. We also offer a range of stainless steel brackets, which are recommended for coastal locations exposed to sea salt or in corrosive environments.

| Code | Size | Description | Crossbar mm | Upright mm | Support Arm mm | Safe Working Load* | Max Load | Weight |
|------------|------|--------------------------------|----------------|---------------|----------------------|--------------------------|-------------|--------|
| CBR1-S | S | Type 1 Bracket | | 450 | 480 | 60kg | 120kg | 3.6kg |
| CBR1-M | M | Type 1 Bracket | | 500 | 530 | 90kg | 180kg | 4.6kg |
| CBR1-L | L | Type 1 Bracket | | 550 | 580 | 140kg | 280kg | 4.7kg |
| CBR1-XL | XL | Type 1 Bracket | | 550 | 660 | 250kg | 500kg | 8.8kg |
| CBR1-XXL | XXL | Type 1 Bracket | | 550 | 1000 | 250kg | 500kg | 11kg |
| CBR2-S | S | Type 2 Bracket | 720 | 400 | 400 | 60kg | 120kg | 3.8kg |
| CBR2-M | M | Type 2 Bracket | 900 | 500 | 500 | 90kg | 180kg | 4.6kg |
| CBR2-L | L | Type 2 Bracket | 1100 | 550 | 540 | 140kg | 280kg | 6.6kg |
| CBR2-XL | XL | Type 2 Bracket | 1040 | 550 | 660 | 250kg | 500kg | 16.2kg |
| CBR2-M-SS | M | Type 2 Stainless Steel Bracket | 900 | 500 | 500 | 90kg | 180kg | 4.6kg |
| CBR2-L-SS | L | Type 2 Stainless Steel Bracket | 1040 | 550 | 540 | 140kg | 280kg | 6.7kg |
| CBR2-XL-SS | XL | Type 2 Stainless Steel Bracket | 1040 | 550 | 660 | 160kg | 280kg | 16.3kg |
| CBR2-EL | S | Type 2 Economy Bracket | 780 | 365 | 550 | 60kg | 120kg | 3.7kg |
| CBR3-M | M | Type 3 Bracket | 900 | 500 | 500 | 90kg | 180kg | 6.8kg |
| CBR3-L | L | Type 3 Bracket | 1040 | 550 | 540 | 140kg | 280kg | 8.3kg |

* All brackets are tested to twice the safe working loads at an independent UK facility.

Condensing Brackets & Trays

Cantilever Arms / Cantilever Arm Kits

These ready-made, hot-dipped galvanised steel cantilever arms with 14mm diameter holes, offer a quick and easy method of supporting condensing units on external walls. Available in straight or webbed versions, in a variety of lengths. This is a low cost option to mounting AC units or ASHP's. The cantilever arm kits come with all of the fixings needed for a quick and easy installation.



Cantilever
Webbed Arm



Cantilever
Single Arm



Cantilever
Kit

| Code | Size | Description | Upright mm | Support Arm mm | Safe Working Load* | Weight |
|------------|--------|-----------------------------|---------------|-------------------|--------------------------|--------|
| CA-450-S | Single | Cantilever Arm 450mm | - | 450 | 250kg | 1.4kg |
| CA-600-S | Single | Cantilever Arm 600mm | - | 600 | 190kg | 2kg |
| CA-750-S | Single | Cantilever Arm 750mm | - | 750 | 150kg | 2.4kg |
| CA-600-W | Webbed | Cantilever Arm 600mm Webbed | - | 600 | 190kg | 2.6kg |
| CA-750-W | Webbed | Cantilever Arm 750mm Webbed | - | 750 | 150kg | 3kg |
| CA-450-KIT | Single | Cantilever Arm Kit - 450mm | 750 | 450 | 250kg* | 8kg |
| CA-600-KIT | Single | Cantilever Arm Kit - 600mm | 750 | 600 | 190kg* | 9kg |

Easy~Fit Condensate Trays

The metal option has a concave profile to ensure effective drainage. Supplied with fixing arms to mount to the bracket. For improved corrosion resistance all metal receives a 100% zinc plating, followed by a hard ED coating, before being finished with an external grade polyester textured powder coating in RAL 7032. The plastic tray is rust free and comes complete with clips to secure to a bracket.



Plastic
Tray



Metal
Tray

| Code | Size | Description | Dimensions mm (LxW) | Drain Connection | Weight |
|-----------|------|----------------------|---------------------|---------------------|--------|
| CCTM-800 | S | Metal Tray Small | 800x400 | 1/2 BSP Male Thread | 5.3kg |
| CCTM-1100 | M | Metal Tray Medium | 1100x400 | 1/2 BSP Male Thread | 7kg |
| CCTM-1400 | L | Metal Tray Large | 1400x400 | 1/2 BSP Male Thread | 8.3kg |
| CCT-790 | S | Plastic Tray - Small | 790x390 | 5/8 or 3/4 | 1.3kg |
| CCT-940 | L | Plastic Tray - Large | 940x420 | 5/8 or 3/4 | 1.7kg |

INABA DENKO

A range of internal and external trunking to protect air conditioning pipes and provide a professional finish. Available in ivory, white and black. This range can be painted to suit many indoor and outdoor applications and is UV resistant and fire proof.



Straight Duct



90° Elbow Bend



45° Elbow Bend



Reducer Joint



Duct End



Flexible Joint



Connection Piece



90° Flat Bend



45° Flat Bend



Wall Rossette



T-Joint



Wall Cover



Flat Rossette

| Ivory | White | Black | Description |
|-----------------|-----------------|-----------------|---|
| ID-NSD-100-I | ID-NSD-100-W | ID-SD-100-K | Slimduct - 100mm - 2000mm (order 10) |
| ID-NSD-75-I | ID-NSD-75-W | ID-SD-75-K | Slimduct - 75mm - 2000mm (order 10) |
| ID-SC-100-I | ID-SC-100-W | ID-SC-100-K | Slimduct - 100mm Elbow Bend |
| ID-SC-75-I | ID-SC-75-W | ID-SC-75-K | Slimduct - 75mm Elbow Bend |
| ID-SCF-100-I | ID-SCF-100-W | ID-SCF-100-K | Slimduct - 100mm 45 Degree Elbow Bend |
| ID-SCF-75-I | ID-SCF-75-W | ID-SCF-75-K | Slimduct - 75mm 45 Degree Elbow Bend |
| ID-SDR-100-75-I | ID-SDR-100-75-W | ID-SDR-100-75-K | Slimduct - 100-75mm Reducer Joint |
| ID-SEN-100-I | ID-SEN-100-W | ID-SEN-100-K | Slimduct - 100mm Duct End |
| ID-SE-75-I | ID-SE-75-W | ID-SE-75-K | Slimduct - 75mm Duct End |
| ID-SF-100-800-I | ID-SF-100-800-W | ID-SF-100-800-K | Slimduct - 100mm - 800mm Flexible Joint |
| ID-SF-75-500-I | ID-SF-75-500-W | ID-SF-75-500-K | Slimduct - 75mm - 500mm Flexible Joint |
| ID-SJ-100-I | ID-SJ-100-W | ID-SJ-100-K | Slimduct - 100mm Connection Piece |
| ID-SJ-75-I | ID-SJ-75-W | ID-SJ-75-K | Slimduct - 75mm Connection Piece |
| ID-SK-100-I | ID-SK-100-W | ID-SK-100-K | Slimduct - 100mm 90 Degree Flat Bend |
| ID-SK-75-I | ID-SK-75-W | ID-SK-75-K | Slimduct - 75mm 90 Degree Flat Bend |
| ID-SKF-100-I | ID-SKF-100-W | ID-SKF-100-K | Slimduct - 100mm 45 Degree Flat Bend |
| ID-SKF-75-I | ID-SKF-75-W | ID-SKF-75-K | Slimduct - 75mm 45 Degree Flat Bend |
| ID-SP-100-I | ID-SP-100-W | ID-SP-100-K | Slimduct - 100mm Flat Rossette |
| ID-SP-75-I | ID-SP-75-W | ID-SP-75-K | Slimduct - 75mm Flat Rossette |
| ID-ST-100-I | ID-ST-100-W | ID-ST-100-K | Slimduct - 100mm T Joint |
| ID-ST-75-I | ID-ST-75-W | ID-ST-75-K | Slimduct - 75mm T Joint |
| ID-SW-100-I | ID-SW-100-W | ID-SW-100-K | Slimduct - 100mm Wall Cover |
| ID-SW-75-I | ID-SW-75-W | ID-SW-75-K | Slimduct - 75mm Wall Cover |
| ID-SWC-100-I | ID-SWC-100-W | ID-SWC-100-K | Slimduct - 100mm Wall Rossette |
| ID-SWC-75-I | ID-SWC-75-W | ID-SWC-75-K | Slimduct - 75mm Wall Rossette |



Easy-Fit



Fixings



Flexi



Install +



Partners



PH Family



PH Motors



Portable



Service +



Squeazy



Mounting

Flexi Lite Slab & Foot Kit

A low cost, lightweight floor mounting solution for air conditioning equipment and air source heat pumps.

Easy to transport, locate and construct.

The kit comes complete with two anti-vibration feet, a lightweight slab and all the fixings.




| Code | Description | Dimensions mm (HxWxD) | Weight | Safe Working Load* |
|-----------------|---|-----------------------|--------|--------------------|
| FF-UC3-S | Flexi Slab & Foot Kit (41mm Strut) 2 x 400mm Feet | 150x400x900 | 16kg | 400kg |
| FF-UC3 | Flexi Slab & Foot Kit (41mm Strut) 2 x 600mm Feet | 175x600x1200 | 25.5kg | 600kg |
| FF-UC3-3 | Flexi Slab & Foot Kit (41mm Strut) 3 x 600mm Feet | 175x600x1200 | 31kg | 600kg |
| FF-UC3-XL | Flexi Slab & Foot Kit (41mm Strut) 2 x 600mm Feet | 175x865x1200 | 31kg | 600kg |
| FF-UC3-ASN | Flexi Slab & Foot Kit (M10 strut) 2 x 600mm Narrow feet | 175x600x1200 | 47kg | 600kg |
| FF-UC-PLATE-KIT | Fixing Plate Kit - 4 Plates and Fixings | | | |



Ultralite® Slab

Don't be fooled - Ultralite® Slabs look and perform like a concrete slab, starting at only 7kg, they are lightweight and very easy to handle and transport. So give your aching back a rest and use Ultralite® slabs to mount AC units and air source heat pumps.



| Code | Description | Dimensions mm (HxWxD) | Weight | Safe Working Load* |
|----------|-------------------------|-----------------------|--------|--------------------|
| UC1636-2 | Ultralite Equipment Pad | 50x400x900 | 7kg | 300kg |
| UC2424-2 | Ultralite Equipment Pad | 50x600x600 | 7kg | 300kg |
| UC2436-3 | Ultralite Equipment Pad | 75x600x900 | 12kg | 485kg |
| UC2442-3 | Ultralite Equipment Pad | 75x600x1050 | 16kg | 595kg |
| UC2448-3 | Ultralite Equipment Pad | 75x600x1200 | 16kg | 700kg |

Mounting Blocks

These mounting blocks are lightweight, 100% rust-free, UV stabilised and manufactured from reinforced PVC. Suitable for mounting air conditioning units and domestic air source heat pumps.

The blocks reduce vibration and are supplied with anti-slip strips on the base along with fixings for a simple rapid installation. End caps are available to provide a professional finish. CMB-350 & CMB-450 are sold in boxes of 12. CMB-1000 are sold in pairs.



| Code (Black) | Code (White) | Description | Dimensions mm (HxWxL) | Weight | Safe Working Load* |
|--------------|--------------|--------------------------|-----------------------|--------|--------------------|
| CMB-350 | | Mounting Blocks – 350mm | 100x100x350 | 0.6kg | 240kg |
| CMB-450 | CMB-450-W | Mounting Blocks – 450mm | 100x100x450 | 0.7kg | 240kg |
| CMB-1000 | CMB-1000-W | Mounting Blocks – 1000mm | 100x100x1000 | 1.6kg | 240kg |

Rubber & Cork Mounting Strips & Pads

Anti-vibration mounting strips / pads are a low cost option for mounting air conditioning units, air source heat pumps and other equipment, providing vibration reduction and sound dampening.



Anti Vibration Mounting Strips

Available in recycled rubber and cork-rubber in various sizes. Rubber AVM Pad comes in three sizes (steel plates are in the larger sizes).

| Code | Description | Dimensions mm (WxL) | Thickness mm | Weight |
|-----------|---|---------------------|--------------|--------|
| AVMS-1 | Anti-vibration Mounting Strip – Rubber | 50x500 | 15 | 0.4kg |
| AVMS-2 | Anti-vibration Mounting Strip – Rubber | 75x1000 | 15 | 1kg |
| AVMS-3 | Anti-vibration Mounting Strip – Rubber | 75x1200 | 15 | 1.7kg |
| AVMS-4 | Anti-vibration Mounting Strip – Rubber | 100x1000 | 15 | 1.4kg |
| AVMS-CR-3 | Anti-vibration Mounting Strip – Cork/Rubber | 75x1200 | 12.5 | 0.6kg |
| AVMS-CR-4 | Anti-vibration Mounting Strip – Cork/Rubber | 100x1200 | 12.5 | 0.9kg |

| Code | Description | Dimensions mm (HxWxL) | Weight | Safe Working Load* |
|-----------|---|-----------------------|--------|--------------------|
| AVM-PAD-1 | Rubber AVM Pad – 330mm | 45x300x300 | 3.2kg | 200kg |
| AVM-PAD-2 | Rubber AVM Pad – 600mm with steel plates | 30x105x 600 | 2.8kg | 150kg |
| AVM-PAD-3 | Rubber AVM Pad – 1000mm with steel plates | 30x500x1000 | 22kg | 300kg |



Easy-Fit



Fixings



Flexi



Install +



Partners



PH Family



PH Motors



Portable



Service +




Squeazy

Mounting

EVA™ Pads / Cork Rubber Anti-Vibration Pads

EVA™ anti-vibration pads are designed to effectively eliminate vibrations and reduce noise levels from equipment such as compressors, condensing units and air source heat pumps. Out performing cork and rubber by 3:1, the EVA pad has a special composite foam centre and is resistant to most oils & chemicals.

The cork is laminated between two corrugated pads to reduce vibration and noise. Designed to withstand 3.5kg per cm². Ideal for air conditioners, compressors, cooling towers or anywhere where vibration control is needed.



| Code EVA | Code Cork / Rubber | Description | Dimensions mm (HxWxL) | Weight | Safe Working Load* |
|----------|--------------------|-------------|-----------------------|--------|---------------------------|
| MP-2E | MP-2C | Pad – 50mm | 20x50x50 | 0.04kg | 3.5kg per cm ² |
| MP-3E | MP-3C | Pad – 80mm | 20x80x80 | 0.08kg | 3.5kg per cm ² |
| MP-4E | MP-4C | Pad – 100mm | 20x100x100 | 0.1kg | 3.5kg per cm ² |
| MP-6E | MP-6C | Pad – 150mm | 20x150x150 | 0.3kg | 3.5kg per cm ² |
| MP-12E | MP-12C | Pad – 305mm | 20x305x305 | 1.4kg | 3.5kg per cm ² |
| MP-18E | MP-18C | Pad – 460mm | 20x460x460 | 3kg | 3.5kg per cm ² |

Rubber Anti-Vibration Pad

Highest quality oil resistant pads, designed to withstand 3.5kg per cm². The rubber pads are corrugated on both sides. Ideal for air conditioners, compressors or anywhere where vibration control is needed.



| Code | Description | Dimensions mm (HxWxL) | Weight | Safe Working Load* |
|-------|-----------------------------------|-----------------------|--------|---------------------------|
| MP-2 | Rubber Anti-vibration Pad – 50mm | 20x50x50 | 0.04kg | 3.5kg per cm ² |
| MP-3 | Rubber Anti-vibration Pad – 80mm | 20x80x80 | 0.05kg | 3.5kg per cm ² |
| MP-4 | Rubber Anti-vibration Pad – 100mm | 20x100x100 | 0.1kg | 3.5kg per cm ² |
| MP-6 | Rubber Anti-vibration Pad – 150mm | 20x150x150 | 0.2kg | 3.5kg per cm ² |
| MP-18 | Rubber Anti-vibration Pad – 460mm | 20x460x460 | 1.8kg | 3.5kg per cm ² |

ISO-Cube Anti-Vibration Pads

Natural rubber pads, designed to reduce vibration and noise emanating from refrigeration and air conditioning equipment. The circular design in each pad offers a suction cup effect, which eliminates the need to bolt the pads down. A standard 18" (46cm) pad is divided into eighty-one 2" (5cm) segments, each of which may be cut or torn to provide smaller pads.



| Code | Description | Dimensions mm (HxWxL) | Weight | Safe Working Load* |
|--------|--------------------------------------|-----------------------|--------|----------------------------|
| ISO-2 | ISO Cube Natural Rubber Pads – 50mm | 20x50x50 | 0.6kg | 12.6kg per cm ² |
| ISO-4 | ISO Cube Natural Rubber Pads – 100mm | 20x100x100 | 0.18kg | 12.6kg per cm ² |
| ISO-18 | ISO Cube Natural Rubber Pads – 460mm | 20x460x460 | 3.8kg | 12.6kg per cm ² |

Quick Sling®

Quick Sling stands offer light and easy-assembly support for outdoor a/c condensing units and heat pumps. Ideal for raising the condensing unit height in surface installations. The elevated height allows for ease of installation, maintenance and service. Available in three height options.

- Flat-packed for easy handling, transport and storage
- Quick and easy to assemble
- Adjustable to suit outdoor units with fixing feet centres up to 700mm (L) and 430mm (W)
- Each 150mm square foot is height adjustable (up to 30mm) to accommodate uneven surfaces
- Includes anti-vibration mounting bolts
- Epoxy powder coated finish



| Code | Description | Length mm | Width mm | Height mm | Safe Working Load | Weight |
|----------|----------------------------|--------------|-------------|--------------|-------------------------|--------|
| QSMS1201 | Quick Sling Stand - Low | 1056 | 941 | 305 | 180kg | 10kg |
| QSMS1801 | Quick Sling Stand - Medium | 1056 | 941 | 450 | 180kg | 13kg |
| QSMS2401 | Quick Sling Stand - High | 1056 | 941 | 600 | 180kg | 16kg |



Easy-Fit



Fixings



Flexi



Install +



Partners



PH Family



PH Motors



Portable



Service +



Squeazy

Portables

Portables - Cool Only & Heat / Cool Pump

The portable air conditioners are suitable for offices, computer rooms and light commercial use. The cooling only model is ideal for cooling flats, conservatories or loft conversions during hot summer months. The heat and cool model can be used as an energy efficient form of heating along with cooling. The units come with a hose, tray, remote control and wall kit. Spare parts are available upon request - please enquire for more details.

A energy efficient



PAC-C-12S



PAC-C-12

| Code | Description | Cool Capacity Btu / kW | Heat Capacity Btu / kW | Watts | Amps | Air Flow Volume | EER | COP | Sound Power Level dBA |
|-----------|----------------------|---------------------------|---------------------------|-------|------|--------------------|-----|-----|-----------------------------|
| PAC-C-12 | Portable (Cooling) | 12,000 / 3.5 | N/A | 1350 | 5.9 | 370m³/h | 2.6 | N/A | 65 |
| PAC-C-12S | Portable (Cooling) | 12,000 / 3.5 | N/A | 1350 | 5.9 | 420m³/h | 2.6 | N/A | 56 |
| PAC-H-12 | Portable (Heat Pump) | 12,000 / 3.5 | 10,000 / 2.9 | 1350 | 5.9 | 370m³/h | 2.6 | 2.6 | 65 |
| PAC-H-12S | Portable (Heat Pump) | 12,000 / 3.5 | 12,000 / 3.5 | 1380 | 6 | 420m³/h | 2.6 | 2.7 | 56 |

| Code | Description | Height mm | Width mm | Depth mm | Weight | Hose Length | Refrigerant | Cooling Area |
|-----------|----------------------|--------------|-------------|-------------|--------|----------------|-------------|-----------------|
| PAC-C-12 | Portable (Cooling) | 765mm | 467mm | 397mm | 34kg | 1.5m | R410A | 18-26m² |
| PAC-C-12S | Portable (Cooling) | 730mm | 485mm | 360mm | 28kg | 1.5m | R410A | 25-30m² |
| PAC-H-12 | Portable (Heat Pump) | 765mm | 467mm | 397mm | 37.5kg | 1.5m | R410A | 18-26m² |
| PAC-H-12S | Portable (Heat Pump) | 730mm | 485mm | 360mm | 28.5kg | 1.5m | R410A | 25-30m² |

Through-The-Wall Air Conditioner

Wall air conditioners, also known as through-the-wall or in-wall air conditioners, are designed to be a long-lasting fixture. These 12,000 btu air conditioners are mounted into a hole in the wall as a permanent installation. Meets EN14511 standard and EU commission regulation 206/2012. R32 Refrigerant. Supplied with remote controller, this proven, well tested design is suitable for areas up to 23m².



| Code | Description | Cool Capacity Btu / kW | Watts | Amps | Air Flow Volume |
|--------------|---------------------|------------------------|-------|------|-----------------|
| WAC-C-12-INV | Through-the-wall AC | 12,000 / 3.5 | 1100 | 5.1 | 400m³/h |

| Code | Description | Height | Width | Depth | Weight | Refrigerant | Cooling Area |
|--------------|---------------------|--------|-------|-------|--------|-------------|--------------|
| WAC-C-12-INV | Through-the-wall AC | 400mm | 560mm | 670mm | 42kg | R32 | 16-23m² |

Universal Remote Controller

This universal air-conditioning remote controller is compatible with units from all major air conditioning manufacturers. This easy to use, time saving tool is perfect for maintaining and servicing any air conditioning unit.



| Code | Max Range | Batteries | Length | Width | Height | Weight |
|---------|-----------|-----------|--------|-------|--------|--------|
| KT-1000 | 3m | AAA x 2 | 130mm | 45mm | 16mm | 50g |

Cushion Clamps

Cushion Clamps are the industry established method of supporting copper refrigerant tube, especially for multiple pipe runs. The zinc dichromate plating provides excellent corrosion resistance and the polymer insert ensures a positive grip, absorbs shock and vibration and prevents galvanic corrosion.

| Code | Pipe Diameter | Diameter |
|--------|---------------|----------|
| CC-004 | 1/4 | 10 |
| CC-006 | 3/8 | 10 |
| CC-008 | 1/2 | 10 |
| CC-010 | 5/8 | 10 |
| CC-012 | 3/4 | 10 |
| CC-014 | 7/8 | 10 |
| CC-018 | 1-1/8 | 10 |

| Code | Pipe Diameter | Diameter |
|--------|---------------|----------|
| CC-022 | 1-3/8 | 10 |
| CC-026 | 1-5/8 | 10 |
| CC-034 | 2-1/8 | 5 |
| CC-042 | 2-5/8 | 5 |
| CC-050 | 3-1/8 | 5 |
| CC-058 | 3-5/8 | 5 |
| CC-066 | 4-1/8 | 5 |



Threaded Rod Hangers

These clamps support a pair of flow and return insulated copper air conditioning pipes on either M8 or M10 threaded rod. By simply squeezing the tips together, the spring steel rod hanger can be fitted or adjusted in seconds, even after the refrigerant pipes have been installed. Black zinc coating matches the insulation colour and offers corrosion resistance.



| Code | Description | Liquid Pipe Diameter (inches) | Gas Pipe Diameter (inches) | Threaded Rod Diameter (inches) | Pack Quantity |
|-------|------------------------------|-------------------------------|----------------------------|--------------------------------|---------------|
| TRH-1 | Threaded Rod Hanger - Size 1 | 1/4 | 1/2 | M8/M10 | 10 |
| TRH-2 | Threaded Rod Hanger - Size 2 | 3/8 | 5/8 | M8/M10 | 10 |
| TRH-3 | Threaded Rod Hanger - Size 3 | 1/2 | 7/8 | M8/M10 | 10 |
| TRH-4 | Threaded Rod Hanger - Size 4 | 5/8 | 1-1/8 | M8/M10 | 10 |

Grip Fit Clamps

The asymmetric design provides a perfect fit for any one of four pairs of flow and return insulated refrigerant pipes. An 8mm hole allows the clamps to be fixed directly to any flat surface, such as a wall or ceiling. The hinged design allows the product to be installed quickly.



| Code | Description | Liquid Pipe Diameter (inches) | Gas Pipe Diameter (inches) | Pack Quantity |
|-------|-------------------------|-------------------------------|----------------------------|---------------|
| GFC-1 | Grip Fit Clamp - Size 1 | 1/4 | 1/2 | 10 |
| GFC-2 | Grip Fit Clamp - Size 2 | 3/8 | 5/8 | 10 |
| GFC-3 | Grip Fit Clamp - Size 3 | 1/2 | 7/8 | 10 |
| GFC-4 | Grip Fit Clamp - Size 4 | 5/8 | 1-1/8 | 10 |



Easy-Fit



Fixings



Flexi



Install +



Partners



PH Family



PH Motors



Portable



Service +



Squeazy

Clamps and Clips

RPC channel clips

The RPC channel clip fits around the pipe and insulation. Ideal for multiple pipe runs, the one piece composite (nylon) alloy clamp absorbs shock and vibration. Quick and easy to install and suitable for temperatures -40°C to +140°C.



| Code | Description | Tube OD (inches) | Pack Quantity |
|----------|------------------|------------------|---------------|
| RPC-0014 | RPC Channel Clip | 1/4 | 10 |
| RPC-0038 | RPC Channel Clip | 3/8 | 10 |
| RPC-0012 | RPC Channel Clip | 1/2 | 10 |
| RPC-0058 | RPC Channel Clip | 5/8 | 10 |
| RPC-0034 | RPC Channel Clip | 3/4 | 10 |
| RPC-0078 | RPC Channel Clip | 7/8 | 10 |
| RPC-0118 | RPC Channel Clip | 1-1/8 | 10 |
| RPC-0138 | RPC Channel Clip | 1-3/8 | 10 |
| RPC-0158 | RPC Channel Clip | 1-5/8 | 10 |



RPC studding clips



The studding clips from RPC have a unique way of attaching themselves to the threaded rod.

Simply insert the clip and snap to secure. The ratchet design locks the pipework in place. It will overcome the problems of using cable ties for piping, electrical, optical and network cabling.



| Code | Stud Size | Tube OD (inches) | Pack Quantity |
|---------|------------------|------------------|---------------|
| SC08-15 | Studding Clip M8 | 5/8 | 10 |
| SC08-20 | Studding Clip M8 | 3/4 | 10 |
| SC08-22 | Studding Clip M8 | 7/8 | 10 |
| SC08-25 | Studding Clip M8 | 1 | 10 |
| SC08-28 | Studding Clip M8 | 1-1/8 | 10 |
| SC08-32 | Studding Clip M8 | 1-1/4 | 10 |
| SC08-35 | Studding Clip M8 | 1-3/8 | 10 |
| SC08-40 | Studding Clip M8 | 1-1/2 | 10 |
| SC08-42 | Studding Clip M8 | 1-5/8 | 10 |
| SC08-50 | Studding Clip M8 | 2 | 10 |
| SC08-54 | Studding Clip M8 | 2-1/8 | 10 |

| Code | Stud Size | Tube OD (inches) | Pack Quantity |
|---------|-------------------|------------------|---------------|
| SC10-15 | Studding Clip M10 | 5/8 | 10 |
| SC10-20 | Studding Clip M10 | 3/4 | 10 |
| SC10-22 | Studding Clip M10 | 7/8 | 10 |
| SC10-25 | Studding Clip M10 | 1 | 10 |
| SC10-28 | Studding Clip M10 | 1-1/8 | 10 |
| SC10-32 | Studding Clip M10 | 1-1/4 | 10 |
| SC10-35 | Studding Clip M10 | 1-3/8 | 10 |
| SC10-40 | Studding Clip M10 | 1-1/2 | 10 |
| SC10-42 | Studding Clip M10 | 1-5/8 | 10 |
| SC10-50 | Studding Clip M10 | 2 | 10 |
| SC10-54 | Studding Clip M10 | 2-1/8 | 10 |

RPC InsulClips

The InsulClips allows an uninterrupted vapour seal and eliminates the problem of sweating on metal fittings.

This makes the InsulClip the ideal product to secure the installation of the refrigerant pipes, allowing the vapour seal to run the length of the pipework without cutting the insulation material.

Made from a composite polyamide (nylon) alloy, which has similar tensile strength properties to nylon but better impact strength, especially at low temperatures.



| Code | Tube OD (inches) | Pack Quantity |
|---------|------------------|---------------|
| IC00-15 | 5/8 | 10 |
| IC00-20 | 3/4 | 10 |
| IC00-22 | 7/8 | 10 |
| IC00-25 | 1 | 10 |
| IC00-28 | 1-1/8 | 10 |
| IC00-32 | 1-1/4 | 10 |
| IC00-35 | 1-3/8 | 10 |
| IC00-40 | 1-1/2 | 10 |
| IC00-42 | 1-5/8 | 10 |
| IC00-50 | 2 | 10 |
| IC00-54 | 2-1/8 | 10 |



RPC Cable Tie Clips

Channel cable tie clips accommodate PVC or metal cable ties up to a width of 17mm. They come in three support base lengths of 50, 65 and 80mm. The channel clips are secured on the channel with a twist lock motion, ready for the cable tie to be inserted to secure the refrigeration pipework.

Clips can be used in temperatures ranging from -40 to 140°C. They have a melting point of 220°C. They can withstand pressures up to 40 MPa, with less than 4% deformation, and provide high resistance to mechanical stress creep. As well as resisting all known solvents, the clips have a low moisture sensitivity.

They also have stable electrical and vibration properties and a high resistance to UV light.



50mm channel clip



65mm channel clip



80mm channel clip

| Code | Size (mm) | Pack Quantity |
|---------|-----------|---------------|
| CTC-050 | 50 | 10 |
| CTC-065 | 65 | 10 |
| CTC-080 | 80 | 10 |



Easy-Fit



Fixings



Flexi



Install +



Partners



PH Family



PH Motors



Portable



Service +



Squeazy

Clamps and Clips

Bronco® Insulation Tube & Pipe Saddle



Put piping in its place with Hydra-Zorb's saddle for insulated tube and pipe. Our patented saddle is one piece, secure, and ultra-fast to install. Requiring no tools or assembly, Bronco® is made of high-strength plastic, making it one of the most stable products on the market. Bronco® fits perfectly on any industry standard anchor channel and includes a self-tapping screw locator. Easy to install onto the channel. Available in white or black to match insulation.



Technical Specification

High strength polypropylene copolymer (PPC)

UV resistant

Temperature range -40 to 178°F



| | Size in inches | | Insulation Wall Thickness | | | | |
|---------------------|----------------|---------|---------------------------|---------|---------|---------|----|
| | | | 1/2" | 3/4" | 1" | 1-1/2" | 2" |
| Copper Tube OD Size | 3/8" | HZSB225 | HZSB225 | HZSB325 | HZSB425 | HZSB525 | |
| | 1/2" | HZSB225 | HZSB225 | HZSB325 | HZSB425 | HZSB525 | |
| | 5/8" | HZSB225 | HZSB225 | HZSB325 | HZSB425 | HZSB525 | |
| | 3/4" | HZSB225 | HZSB325 | HZSB325 | HZSB425 | HZSB525 | |
| | 7/8" | HZSB225 | HZSB325 | HZSB325 | HZSB425 | HZSB525 | |
| | 1-1/8" | HZSB225 | HZSB325 | HZSB325 | HZSB425 | HZSB525 | |
| | 1-3/8" | HZSB325 | HZSB325 | HZSB425 | HZSB525 | HZSB625 | |
| | 1-5/8" | HZSB325 | HZSB325 | HZSB425 | HZSB525 | HZSB625 | |
| | 2-1/8" | HZSB325 | HZSB425 | HZSB425 | HZSB525 | HZSB625 | |
| | 2-5/8" | HZSB425 | HZSB425 | HZSB525 | HZSB625 | HZSB825 | |
| | 3-1/8" | HZSB425 | HZSB525 | HZSB525 | HZSB625 | HZSB825 | |
| | 3-5/8" | HZSB525 | HZSB525 | HZSB625 | HZSB825 | HZSB825 | |
| | 4-1/8" | HZSB525 | HZSB625 | HZSB625 | HZSB825 | HZSB825 | |



| Code (Black) | Code (White) | Dimension A in (inches) |
|--------------|--------------|-------------------------|
| HZSB225 | HZSW225 | 2-1/4 |
| HZSB325 | HZSW325 | 3-1/4 |
| HZSB425 | HZSW425 | 4-1/4 |
| HZSB525 | HZSW525 | 5-1/4 |
| HZSB625 | HZSW625 | 6-1/4 |
| HZSB825 | HZSW825 | 8-1/4 |

90° Elbow (CxC)



| Code | Size (inches) | Pack Qty. |
|--------------|---------------|-----------|
| C235-0001-PH | 1/4 | 100 |
| C235-0002-PH | 3/8 | 100 |
| C235-0025-PH | 1/2 | 100 |
| C235-0050-PH | 5/8 | 100 |
| C235-0090-PH | 3/4 | 50 |
| C235-0100-PH | 7/8 | 50 |
| C235-0150-PH | 1-1/8 | 25 |
| C235-0215-PH | 1-3/8 | 10 |
| C235-0295-PH | 1-5/8 | 10 |
| C235-0390-PH | 2-1/8 | 1 |
| C235-0520-PH | 2-5/8 | 1 |
| C235-0650-PH | 3-1/8 | 1 |
| C235-0750-PH | 3-5/8 | 1 |
| C235-0850-PH | 4-1/8 | 1 |

90° Street Elbow (FxC)



| Code | Size (inches) | Pack Qty. |
|--------------|---------------|-----------|
| C254-0002-PH | 3/8 | 100 |
| C254-0025-PH | 1/2 | 100 |
| C254-0050-PH | 5/8 | 100 |
| C254-0090-PH | 3/4 | 50 |
| C254-0100-PH | 7/8 | 25 |
| C254-0150-PH | 1-1/8 | 20 |
| C254-0215-PH | 1-3/8 | 10 |
| C254-0295-PH | 1-5/8 | 10 |
| C254-0390-PH | 2-1/8 | 1 |
| C254-0520-PH | 2-5/8 | 1 |
| C254-0650-PH | 3-1/8 | 1 |
| C254-0750-PH | 3-5/8 | 1 |
| C254-0850-PH | 4-1/8 | 1 |

90° Long Turn Elbow (CxC)



| Code | Size (inches) | Pack Qty. |
|--------------|---------------|-----------|
| C242-0001-PH | 1/4 | 100 |
| C242-0002-PH | 3/8 | 100 |
| C242-0025-PH | 1/2 | 100 |
| C242-0050-PH | 5/8 | 50 |
| C242-0090-PH | 3/4 | 50 |
| C242-0100-PH | 7/8 | 25 |
| C242-0150-PH | 1-1/8 | 10 |
| C242-0215-PH | 1-3/8 | 10 |
| C242-0295-PH | 1-5/8 | 5 |
| C242-0390-PH | 2-1/8 | 1 |
| C242-0520-PH | 2-5/8 | 1 |
| C242-0650-PH | 3-1/8 | 1 |
| C242-0750-PH | 3-5/8 | 1 |
| C242-0850-PH | 4-1/8 | 1 |

90° Long Turn Street Elbow (FxC)



| Code | Size (inches) | Pack Qty. |
|--------------|---------------|-----------|
| C272-0002-PH | 3/8 | 100 |
| C272-0025-PH | 1/2 | 100 |
| C272-0050-PH | 5/8 | 50 |
| C272-0090-PH | 3/4 | 50 |
| C272-0100-PH | 7/8 | 25 |
| C272-0150-PH | 1-1/8 | 10 |
| C272-0215-PH | 1-3/8 | 10 |
| C272-0295-PH | 1-5/8 | 5 |
| C272-0390-PH | 2-1/8 | 1 |
| C272-0520-PH | 2-5/8 | 1 |
| C272-0650-PH | 3-1/8 | 1 |
| C272-0750-PH | 3-5/8 | 1 |
| C272-0850-PH | 4-1/8 | 1 |



Easy-Fit



Fittings



Flexi



Install +



Partners



PH Family



PH Motors



Portable



Service +



Squeazy

Copper Fittings

45° Elbow (CxC)



| Code | Size (inches) | Pack Qty. |
|--------------|---------------|-----------|
| C290-0002-PH | 3/8 | 100 |
| C290-0025-PH | 1/2 | 100 |
| C290-0050-PH | 5/8 | 50 |
| C290-0090-PH | 3/4 | 50 |
| C290-0100-PH | 7/8 | 50 |
| C290-0150-PH | 1-1/8 | 25 |
| C290-0215-PH | 1-3/8 | 10 |
| C290-0295-PH | 1-5/8 | 10 |
| C290-0390-PH | 2-1/8 | 1 |
| C290-0520-PH | 2-5/8 | 1 |
| C290-0650-PH | 3-1/8 | 1 |
| C290-0750-PH | 3-5/8 | 1 |
| C290-0850-PH | 4-1/8 | 1 |

45° Street Elbow (FxC)



| Code | Size (inches) | Pack Qty. |
|--------------|---------------|-----------|
| C295-0002-PH | 3/8 | 100 |
| C295-0025-PH | 1/2 | 100 |
| C295-0050-PH | 5/8 | 50 |
| C295-0090-PH | 3/4 | 50 |
| C295-0100-PH | 7/8 | 25 |
| C295-0150-PH | 1-1/8 | 20 |
| C295-0215-PH | 1-3/8 | 10 |
| C295-0295-PH | 1-5/8 | 5 |
| C295-0390-PH | 2-1/8 | 1 |
| C295-0520-PH | 2-5/8 | 1 |
| C295-0650-PH | 3-1/8 | 1 |
| C295-0750-PH | 3-5/8 | 1 |
| C295-0850-PH | 4-1/8 | 1 |

Straight Coupler (Cx-C)



| Code | Size (inches) | Pack Qty. |
|--------------|---------------|-----------|
| C165-0001-PH | 1/4 x 1/4 | 100 |
| C165-0002-PH | 3/8 x 3/8 | 100 |
| C165-0025-PH | 1/2 x 1/2 | 100 |
| C165-0050-PH | 5/8 x 5/8 | 100 |
| C165-0090-PH | 3/4 x 3/4 | 100 |
| C165-0100-PH | 7/8 x 7/8 | 50 |
| C165-0150-PH | 1-1/8 x 1-1/8 | 25 |
| C165-0215-PH | 1-3/8 x 1-3/8 | 25 |
| C165-0295-PH | 1-5/8 x 1-5/8 | 10 |
| C165-0390-PH | 2-1/8 x 2-1/8 | 5 |
| C165-0520-PH | 2-5/8 x 2-5/8 | 1 |
| C165-0650-PH | 3-1/8 x 3-1/8 | 1 |
| C165-0750-PH | 3-5/8 x 3-5/8 | 1 |
| C165-0850-PH | 4-1/8 x 4-1/8 | 1 |

End Cap



| Code | Size (inches) | Pack Qty. |
|--------------|---------------|-----------|
| C154-0002-PH | 3/8 | 100 |
| C154-0025-PH | 1/2 | 100 |
| C154-0050-PH | 5/8 | 50 |
| C154-0090-PH | 3/4 | 50 |
| C154-0100-PH | 7/8 | 25 |
| C154-0150-PH | 1-1/8 | 25 |
| C154-0215-PH | 1-3/8 | 10 |
| C154-0295-PH | 1-5/8 | 10 |
| C154-0390-PH | 2-1/8 | 5 |
| C154-0520-PH | 2-5/8 | 1 |
| C154-0650-PH | 3-1/8 | 1 |
| C154-0750-PH | 3-5/8 | 1 |
| C154-0850-PH | 4-1/8 | 1 |

Reducer Coupler (Cx C)



| Code | Size (inches) | | Pack Qty. |
|--------------|---------------|---|-----------|
| | 1 | 2 | |
| C165-0007-PH | 3/8 x 1/4 | | 100 |
| C165-0032-PH | 1/2 x 3/8 | | 100 |
| C165-0033-PH | 1/2 x 1/4 | | 100 |
| C165-0058-PH | 5/8 x 1/2 | | 100 |
| C165-0059-PH | 5/8 x 3/8 | | 100 |
| C165-0093-PH | 3/4 x 5/8 | | 50 |
| C165-0094-PH | 3/4 x 1/2 | | 100 |
| C165-0107-PH | 7/8 x 5/8 | | 50 |
| C165-0108-PH | 7/8 x 1/2 | | 50 |
| C165-0149-PH | 7/8 x 3/4 | | 50 |
| C165-0159-PH | 1-1/8 x 7/8 | | 25 |
| C165-0160-PH | 1-1/8 x 5/8 | | 25 |
| C165-0161-PH | 1-1/8 x 1/2 | | 25 |
| C165-1498-PH | 1-1/8 x 3/4 | | 25 |
| C165-0222-PH | 1-3/8 x 1-1/8 | | 25 |
| C165-0223-PH | 1-3/8 x 7/8 | | 25 |
| C165-0224-PH | 1-3/8 x 5/8 | | 10 |
| C165-0030-PH | 1-5/8 x 1-3/8 | | 10 |
| C165-0304-PH | 1-5/8 x 1-1/8 | | 10 |
| C165-0305-PH | 1-5/8 x 7/8 | | 10 |
| C165-0398-PH | 2-1/8 x 1-5/8 | | 10 |
| C165-0399-PH | 2-1/8 x 1-3/8 | | 10 |
| C165-0400-PH | 2-1/8 x 1-1/8 | | 10 |
| C165-0401-PH | 2-1/8 x 7/8 | | 10 |
| C165-0531-PH | 2-5/8 x 2-1/8 | | 1 |
| C165-0532-PH | 2-5/8 x 1-5/8 | | 1 |
| C165-0533-PH | 2-5/8 x 1-3/8 | | 1 |
| C165-0662-PH | 3-1/8 x 2-5/8 | | 1 |
| C165-0663-PH | 3-1/8 x 2-1/8 | | 1 |
| C165-0664-PH | 3-1/8 x 1-5/8 | | 1 |
| C165-0790-PH | 3-5/8 x 3-1/8 | | 1 |
| C165-0852-PH | 4-1/8 x 2-5/8 | | 1 |

Reducer Coupler (Fx C)



| Code | Size (inches) | | Pack Qty. |
|--------------|---------------|---|-----------|
| | 1 | 2 | |
| C410-0007-PH | 3/8 x 1/4 | | 100 |
| C410-0032-PH | 1/2 x 3/8 | | 100 |
| C410-0033-PH | 1/2 x 1/4 | | 100 |
| C410-0058-PH | 5/8 x 1/2 | | 100 |
| C410-0059-PH | 5/8 x 3/8 | | 100 |
| C410-0093-PH | 3/4 x 5/8 | | 50 |
| C410-0094-PH | 3/4 x 1/2 | | 50 |
| C410-0095-PH | 3/4 x 3/8 | | 50 |
| C410-0107-PH | 7/8 x 5/8 | | 50 |
| C410-0108-PH | 7/8 x 1/2 | | 50 |
| C410-0109-PH | 7/8 x 3/8 | | 50 |
| C410-0149-PH | 7/8 x 3/4 | | 50 |
| C410-0159-PH | 1-1/8 x 7/8 | | 25 |
| C410-1498-PH | 1-1/8 x 3/4 | | 25 |
| C410-0160-PH | 1-1/8 x 5/8 | | 25 |
| C410-0161-PH | 1-1/8 x 1/2 | | 25 |
| C410-0222-PH | 1-3/8 x 1-1/8 | | 25 |
| C410-0223-PH | 1-3/8 x 7/8 | | 25 |
| C410-0224-PH | 1-3/8 x 5/8 | | 25 |
| C410-0303-PH | 1-5/8 x 1-3/8 | | 10 |
| C410-0304-PH | 1-5/8 x 1-1/8 | | 10 |
| C410-0305-PH | 1-5/8 x 7/8 | | 10 |
| C410-0306-PH | 1-5/8 x 5/8 | | 10 |
| C410-0398-PH | 2-1/8 x 1-5/8 | | 10 |
| C410-0399-PH | 2-1/8 x 1-3/8 | | 10 |
| C410-0400-PH | 2-1/8 x 1-1/8 | | 10 |
| C410-0401-PH | 2-1/8 x 7/8 | | 10 |
| C410-0402-PH | 2-1/8 x 5/8 | | 10 |
| C410-0531-PH | 2-5/8 x 2-1/8 | | 1 |
| C410-0532-PH | 2-5/8 x 1-5/8 | | 1 |
| C410-0533-PH | 2-5/8 x 1-3/8 | | 1 |
| C410-0662-PH | 3-1/8 x 2-5/8 | | 1 |
| C410-0663-PH | 3-1/8 x 2-1/8 | | 1 |
| C410-0664-PH | 3-1/8 x 1-5/8 | | 1 |
| C410-0754-PH | 3-5/8 x 3-1/8 | | 1 |
| C410-0850-PH | 4-1/8 x 2-1/8 | | 1 |
| C410-0852-PH | 4-1/8 x 2-5/8 | | 1 |
| C410-0854-PH | 4-1/8 x 3-1/8 | | 1 |



Easy-Fit



Fixings



Flexi



Install



Partners



PH Family



PH Motors



Portable



Service



Squeeze

Copper Fittings

Male Adaptor (C x Male NPT)



| Code | Size (inches) | | Pack Qty. |
|--------------|---------------|---|-----------|
| | 1 | 2 | |
| C101-0005-PH | 3/8 x 1/2 | | 50 |
| C101-0007-PH | 3/8 x 1/8 | | 50 |
| C101-0025-PH | 1/2 x 3/8 | | 50 |
| C101-0050-PH | 5/8 x 1/2 | | 50 |
| C101-0057-PH | 5/8 x 3/4 | | 50 |
| C101-0058-PH | 5/8 x 3/8 | | 50 |
| C101-0100-PH | 7/8 x 3/4 | | 10 |
| C101-0150-PH | 1-1/8 x 1 | | 5 |
| C101-0159-PH | 1-1/8 x 3/4 | | 5 |
| C101-0215-PH | 1-3/8 x 1-1/4 | | 5 |
| C101-0295-PH | 1-5/8 x 1-1/2 | | 2 |
| C101-0390-PH | 2-1/8 x 2 | | 1 |

Female Adaptor (C x Female NPT)



| Code | Size (inches) | | Pack Qty. |
|--------------|---------------|---|-----------|
| | 1 | 2 | |
| C105-0025-PH | 3/8 x 1/2 | | 50 |
| C105-0050-PH | 5/8 x 1/2 | | 50 |
| C105-0057-PH | 5/8 x 3/4 | | 25 |
| C105-0058-PH | 3/8 x 5/8 | | 50 |
| C105-0059-PH | 1/4 x 5/8 | | 50 |
| C105-0100-PH | 7/8 x 3/4 | | 10 |
| C105-0107-PH | 7/8 x 1/2 | | 10 |
| C105-0150-PH | 1-1/8 x 1 | | 5 |
| C105-0159-PH | 1-1/8 x 3/4 | | 5 |
| C105-0215-PH | 1-3/8 x 1-1/4 | | 5 |
| C105-0295-PH | 1-5/8 x 1-1/2 | | 2 |
| C105-0390-PH | 2-1/8 x 2 | | 1 |

180° Return Bend



| Code | Size (inches) | | Pack Qty. |
|--------------|---------------|---|-----------|
| | 1 | 2 | |
| C180-0002-PH | 3/8 x 1-1/2 | | 100 |
| C180-0025-PH | 1/2 x 1-1/2 | | 100 |
| C180-0050-PH | 5/8 x 1-7/8 | | 50 |
| C180-0090-PH | 3/4 x 2-1/4 | | 50 |
| C180-0100-PH | 7/8 x 2-1/2 | | 50 |
| C180-0150-PH | 1-1/8 x 3 | | 50 |
| C180-0215-PH | 1-3/8 x 3 | | 25 |
| C180-0295-PH | 1-5/8 x 3-1/2 | | 25 |
| C180-0390-PH | 2-1/8 x 5-1/2 | | 25 |

U-Type Strap



| Code | Size (inches) | | Pack Qty. |
|--------------|---------------|---|-----------|
| | 1 | 2 | |
| C947-0025-PH | 1/2 | | 100 |
| C947-0050-PH | 5/8 | | 50 |
| C947-0090-PH | 3/4 | | 50 |
| C947-0100-PH | 7/8 | | 50 |
| C947-0150-PH | 1-1/8 | | 10 |
| C947-0215-PH | 1-3/8 | | 10 |
| C947-0295-PH | 1-5/8 | | 10 |
| C947-0390-PH | 2-1/8 | | 5 |

Reducing Tee (Cx CxC)



| Code | Size (inches) | | | Pack Qty. |
|--------------|-----------------------|---|---|-----------|
| | 1 | 2 | 3 | |
| C460-0005-PH | 3/8 x 3/8 x 1/4 | | | 100 |
| C460-0006-PH | 3/8 x 3/8 x 1/2 | | | 100 |
| C460-0031-PH | 1/2 x 1/2 x 5/8 | | | 100 |
| C460-0032-PH | 1/2 x 1/2 x 3/8 | | | 100 |
| C460-0033-PH | 1/2 x 1/2 x 1/4 | | | 100 |
| C460-0040-PH | 1/2 x 3/8 x 1/2 | | | 100 |
| C460-0041-PH | 1/2 x 3/8 x 3/8 | | | 100 |
| C460-0056-PH | 5/8 x 5/8 x 1-1/8 | | | 25 |
| C460-0057-PH | 5/8 x 5/8 x 7/8 | | | 25 |
| C460-0058-PH | 5/8 x 5/8 x 1/2 | | | 50 |
| C460-0059-PH | 5/8 x 5/8 x 3/8 | | | 50 |
| C460-0066-PH | 5/8 x 1/2 x 5/8 | | | 90 |
| C460-0067-PH | 5/8 x 1/2 x 1/2 | | | 50 |
| C460-0068-PH | 5/8 x 1/2 x 3/8 | | | 50 |
| C460-0076-PH | 5/8 x 3/8 x 1/2 | | | 50 |
| C460-0087-PH | 5/8 x 5/8 x 3/4 | | | 50 |
| C460-0092-PH | 3/4 x 3/4 x 7/8 | | | 50 |
| C460-0093-PH | 3/4 x 3/4 x 5/8 | | | 50 |
| C460-0094-PH | 3/4 x 3/4 x 1/2 | | | 50 |
| C460-0095-PH | 3/4 x 3/4 x 3/8 | | | 50 |
| C460-0098-PH | 3/4 x 5/8 x 5/8 | | | 50 |
| C460-0106-PH | 7/8 x 7/8 x 1-1/8 | | | 25 |
| C460-0107-PH | 7/8 x 7/8 x 5/8 | | | 25 |
| C460-0108-PH | 7/8 x 7/8 x 1/2 | | | 25 |
| C460-0109-PH | 7/8 x 7/8 x 3/8 | | | 25 |
| C460-0111-PH | 7/8 x 1/2 x 7/8 | | | 25 |
| C460-0117-PH | 7/8 x 5/8 x 7/8 | | | 25 |
| C460-0118-PH | 7/8 x 5/8 x 5/8 | | | 25 |
| C460-0119-PH | 7/8 x 5/8 x 1/2 | | | 25 |
| C460-0127-PH | 7/8 x 1/2 x 5/8 | | | 25 |
| C460-0157-PH | 1-1/8 x 1-1/8 x 1-5/8 | | | 10 |
| C460-0158-PH | 1-1/8 x 1-1/8 x 1-3/8 | | | 10 |
| C460-0159-PH | 1-1/8 x 1-1/8 x 7/8 | | | 10 |
| C460-1498-PH | 1-1/8 x 1-1/8 x 3/4 | | | 10 |
| C460-0160-PH | 1-1/8 x 1-1/8 x 1/2 | | | 10 |
| C460-0169-PH | 1-1/8 x 7/8 x 1-1/8 | | | 10 |
| C460-0170-PH | 1-1/8 x 7/8 x 7/8 | | | 10 |
| C460-0171-PH | 1-1/8 x 7/8 x 5/8 | | | 10 |
| C460-0180-PH | 1-1/8 x 5/8 x 1-1/8 | | | 10 |
| C460-0181-PH | 1-1/8 x 5/8 x 7/8 | | | 10 |

| Code | Size (inches) | | | Pack Qty. |
|--------------|-----------------------|---|---|-----------|
| | 1 | 2 | 3 | |
| C460-0220-PH | 1-3/8 x 1-3/8 x 2-1/8 | | | 5 |
| C460-0221-PH | 1-3/8 x 1-3/8 x 1-5/8 | | | 10 |
| C460-0222-PH | 1-3/8 x 1-3/8 x 1-1/8 | | | 10 |
| C460-0223-PH | 1-3/8 x 1-3/8 x 7/8 | | | 10 |
| C460-0224-PH | 1-3/8 x 1-3/8 x 5/8 | | | 10 |
| C460-0234-PH | 1-3/8 x 1-1/8 x 1-3/8 | | | 10 |
| C460-0235-PH | 1-3/8 x 1-1/8 x 1-1/8 | | | 10 |
| C460-0237-PH | 1-3/8 x 1-1/8 x 5/8 | | | 10 |
| C460-0245-PH | 1-3/8 x 7/8 x 1-3/8 | | | 10 |
| C460-0246-PH | 1-3/8 x 7/8 x 1-1/8 | | | 10 |
| C460-0247-PH | 1-3/8 x 7/8 x 7/8 | | | 10 |
| C460-0302-PH | 1-5/8 x 1-5/8 x 2-1/8 | | | 5 |
| C460-0303-PH | 1-5/8 x 1-5/8 x 1-3/8 | | | 5 |
| C460-0304-PH | 1-5/8 x 1-5/8 x 1-1/8 | | | 5 |
| C460-0305-PH | 1-5/8 x 1-5/8 x 7/8 | | | 5 |
| C460-0306-PH | 1-5/8 x 1-5/8 x 5/8 | | | 5 |
| C460-0315-PH | 1-5/8 x 1-3/8 x 1-5/8 | | | 5 |
| C460-0316-PH | 1-5/8 x 1-3/8 x 1-3/8 | | | 5 |
| C460-0328-PH | 1-5/8 x 1-1/8 x 1-5/8 | | | 5 |
| C460-0330-PH | 1-5/8 x 1-1/8 x 1-1/8 | | | 5 |
| C460-0331-PH | 1-5/8 x 1-1/8 x 7/8 | | | 5 |
| C460-0339-PH | 1-5/8 x 7/8 x 1-5/8 | | | 5 |
| C460-0397-PH | 2-1/8 x 2-1/8 x 2-5/8 | | | 1 |
| C460-0398-PH | 2-1/8 x 2-1/8 x 1-5/8 | | | 1 |
| C460-0399-PH | 2-1/8 x 2-1/8 x 1-3/8 | | | 1 |
| C460-0400-PH | 2-1/8 x 2-1/8 x 1-1/8 | | | 1 |
| C460-0401-PH | 2-1/8 x 2-1/8 x 7/8 | | | 1 |
| C460-0414-PH | 2-1/8 x 1-5/8 x 1-5/8 | | | 1 |
| C460-0416-PH | 2-1/8 x 1-5/8 x 1-1/8 | | | 1 |
| C460-0417-PH | 2-1/8 x 1-5/8 x 7/8 | | | 1 |
| C460-0429-PH | 2-1/8 x 1-3/8 x 2-1/8 | | | 1 |
| C460-0431-PH | 2-1/8 x 1-3/8 x 1-3/8 | | | 1 |
| C460-0432-PH | 2-1/8 x 1-3/8 x 1-1/8 | | | 1 |
| C460-0531-PH | 2-5/8 x 2-5/8 x 2-1/8 | | | 1 |
| C460-0532-PH | 2-5/8 x 2-5/8 x 1-5/8 | | | 1 |
| C460-0533-PH | 2-5/8 x 2-5/8 x 1-3/8 | | | 1 |
| C460-0534-PH | 2-5/8 x 2-5/8 x 1-1/8 | | | 1 |
| C460-0535-PH | 2-5/8 x 2-5/8 x 7/8 | | | 1 |
| C460-0549-PH | 2-5/8 x 2-1/8 x 2-1/8 | | | 1 |
| C460-0663-PH | 3-1/8 x 3-1/8 x 2-1/8 | | | 1 |
| C460-0664-PH | 3-1/8 x 3-1/8 x 1-5/8 | | | 1 |



Easy-Fit



Flanges



Flexi



Install



Partners



PH Family



PH Motors



Portable



Service



Squeeze

Copper Fittings

Equal Tee (CxCxC)



| Code | Size (inches) | Pack Qty. |
|--------------|---------------|-----------|
| C460-0001-PH | 1/4 | 100 |
| C460-0002-PH | 3/8 | 100 |
| C460-0025-PH | 1/2 | 100 |
| C460-0050-PH | 5/8 | 50 |
| C460-0090-PH | 3/4 | 50 |
| C460-0100-PH | 7/8 | 25 |
| C460-0150-PH | 1-1/8 | 10 |
| C460-0215-PH | 1-3/8 | 10 |
| C460-0295-PH | 1-5/8 | 5 |
| C460-0390-PH | 2-1/8 | 1 |
| C460-0520-PH | 2-5/8 | 1 |
| C460-0650-PH | 3-1/8 | 1 |
| C460-0750-PH | 3-5/8 | 1 |
| C460-0850-PH | 4-1/8 | 1 |

P Trap



| Code | Size (inches) | Pack Qty. |
|--------------|---------------|-----------|
| C533-0050-PH | 5/8 | 5 |
| C533-0090-PH | 3/4 | 2 |
| C533-0100-PH | 7/8 | 2 |
| C533-0150-PH | 1-1/8 | 1 |
| C533-0215-PH | 1-3/8 | 1 |
| C533-0295-PH | 1-5/8 | 1 |
| C533-0390-PH | 2-1/8 | 1 |

We will match it all!



We've Data Sheets to match our ancillaries to all major manufacturers' condensing units. These Matching Sheets are available on request. Call us today to get your perfect match!



Short Machine Flare Nut



| Code | Size (inches) | Pack Quantity |
|--------|---------------|---------------|
| DN1-3 | 3/16 | 10 |
| DN1-4 | 1/4 | 10 |
| DN1-5 | 5/16 | 10 |
| DN1-6 | 3/8 | 10 |
| DN1-8 | 1/2 | 10 |
| DN1-10 | 5/8 | 10 |
| DN1-12 | 3/4 | 10 |
| DN1-14 | 7/8 | 5 |

Short Forged Flare Nut



| Code | Size (inches) | Pack Quantity |
|---------|---------------|---------------|
| DNS4-4 | 1/4 | 10 |
| DNS4-6 | 3/8 | 10 |
| DNS4-8 | 1/2 | 10 |
| DNS4-10 | 5/8 | 10 |
| DNS4-12 | 3/4 | 10 |
| DNS4-14 | 7/8 | 5 |

Flare Tee



| Code | Size (inches) | Pack Quantity |
|--------|---------------|---------------|
| DT2-4 | 1/4 | 10 |
| DT2-6 | 3/8 | 10 |
| DT2-8 | 1/2 | 10 |
| DT2-10 | 5/8 | 10 |

Cap



| Code | Size (inches) | Pack Quantity |
|-------|---------------|---------------|
| DN5-4 | 1/4 | 10 |
| DN5-6 | 3/8 | 10 |

Plug



| Code | Size (inches) | Pack Quantity |
|--------|---------------|---------------|
| DP2-4 | 1/4 | 10 |
| DP2-6 | 3/8 | 10 |
| DP2-8 | 1/2 | 10 |
| DP2-10 | 5/8 | 10 |

Flare and MPT Elbow



| Code | Size (inches) | Pack Quantity |
|---------|---------------|---------------|
| DE1-4B | 1/4 | 10 |
| DE1-6C | 3/8 | 10 |
| DE1-8D | 1/2 | 10 |
| DE1-12E | 5/8 | 10 |

Flare & MPT Red Elbow



| Code | Size (inches) | Pack Quantity |
|---------|---------------|---------------|
| DE1-6B | 3/8 x 1/4 MPT | 10 |
| DE1-6D | 3/8 x 1/2 MPT | 10 |
| DE1-8E | 1/2 x 3/4 MPT | 10 |
| DE1-10D | 5/8 x 1/2 MPT | 10 |
| DE1-12D | 3/4 x 1/2 MPT | 10 |

Fare Union



| Code | Size (inches) | Pack Quantity |
|--------|---------------|---------------|
| DU2-4 | 1/4 | 10 |
| DU2-6 | 3/8 | 10 |
| DU2-8 | 1/2 | 10 |
| DU2-10 | 5/8 | 10 |
| DU2-12 | 3/4 | 10 |

R410a & R32 Transitional Fitting



| Code | Size (inches) | Pack Quantity |
|-------|---------------|---------------|
| 20128 | 5/16 x 1/4 | 1 |



Easy-Fit



Fixings



Flexi



Install



Partners



PH Family



PH Motors



Portable



Service



Squeezy

Brass & Access Fittings

Flare Union x MPT



DU1-8B

| Code | Size (inches) | Pack Quantity |
|---------|---------------|---------------|
| DU1-4A | 1/4 x 1/8 MPT | 10 |
| DU1-4B | 1/4 x 1/4 MPT | 10 |
| DU1-6B | 3/8 x 1/4 MPT | 10 |
| DU1-6C | 3/8 x 3/8 MPT | 10 |
| DU1-6D | 3/8 x 1/2 MPT | 10 |
| DU1-6E | 3/8 x 3/4 MPT | 10 |
| DU1-8B | 1/2 x 1/4 MPT | 10 |
| DU1-8C | 1/2 x 3/8 MPT | 10 |
| DU1-8D | 1/2 x 1/2 MPT | 10 |
| DU1-8E | 1/2 x 3/4 MPT | 10 |
| DU1-10D | 5/8 x 1/2 MPT | 10 |
| DU1-10E | 5/8 x 3/4 MPT | 10 |
| DU1-12D | 3/4 x 1/2 MPT | 10 |
| DU1-12E | 3/4 x 3/4 MPT | 10 |



DUS4-6

Flare x Flare Swivel Union

| Code | Size (inches) | Pack Quantity |
|--------|---------------|---------------|
| DUS4-4 | 1/4 x 1/4 | 10 |
| DUS4-6 | 3/8 x 3/8 | 10 |
| DUS4-8 | 1/2 x 1/2 | 10 |

Flare x FPT Union

| Code | Size (inches) | Pack Quantity |
|---------|---------------|---------------|
| DU3-6C | 3/8 x 3/8 FPT | 10 |
| DU3-6D | 3/8 x 1/2 FPT | 10 |
| DU3-8C | 1/2 x 3/8 FPT | 10 |
| DU3-8D | 1/2 x 1/2 FPT | 10 |
| DU3-10D | 5/8 x 1/2 FPT | 10 |
| DU3-10E | 5/8 x 3/4 FPT | 10 |

Access Fittings



VAU-24



VST-46



VST-44X



VA-3-346



VT-24

| Code | Description | Size (inches) | Pack Quantity |
|----------|-------------------------------|--|---------------|
| VA-3-356 | 3-Way Solder Fitting | 3/16 OD to 1/4 & 3/8 | 6 |
| VA-34 | Straight Solder Fitting | 3/16 ODS x 1/4 ODF | 6 |
| VA-A6 | Straight Solder Fitting | 1/4 ODS x 3/8 ODF | 6 |
| VA-68 | Straight Solder Fitting | 3/8 ODS x 1/2 ODF | 6 |
| VAU-24 | Half Union | 1/8 MPT | 6 |
| VAU-45 | Half Union | 1/4 MPT | 6 |
| VAX-3 | Extended Copper Tube Fitting | 1/4 SAE Flare with 3/16 OD x 1/8 ID with 2inch tail | 6 |
| VAX-4 | Extended Copper Tube Fitting | 1/4 SAE Flare with 1/4 OD x 3/16 ID with 2inch tail | 6 |
| VAX-4B | Extended Copper Tube Fitting | 1/4 SAE Flare with 1/4 OD x 3/16 ID with 2inch tail | 100 |
| VAX-4B-6 | Extended Copper Tube Fitting | 1/4 SAE Flare with 1/4 OD x 3/16 ID with 6inch tail | 1 |
| VAX-5 | Extended Copper Tube Fitting | 1/4 SAE Flare with 5/16 OD x 1/4 ID with 2inch tail | 3 |
| VAX-5-PH | Extended Copper Tube Fitting | 5/16 SAE Flare (R410a) with 1/4 OD x 3/16 ID with 2inch tail | 1 |
| VAX-6 | Extended Copper Tube Fitting | 1/4 SAE Flare with 3/8 OD x 5/16 ID with 2inch tail | 3 |
| VC-4 | SAE Flare Cap 1/4 | Plain Cap | 12 |
| VC-4R | SAE Flare Cap 1/4 | Cap with Core Remover | 12 |
| VS-4 | Access Fitting - Female Flare | Female 1/4 SAE Swivel Nut w/Depressor x 1/4 SAE male flare | 3 |
| VST-4 | Swivel Tee 1/4 | 1/4 SAE Flare x 1/4 SAE Flare on run x 1/4 Female Swivel on branch | 3 |
| VST-44 | Swivel Tee 1/4 | 1/4 SAE Flare x 1/4 Female Swivel on run x 1/4 SAE Flare on branch | 3 |
| VST-4X | Swivel Tee 1/4 with depressor | 1/4 SAE Flare x 1/4 SAE Flare on run x 1/4 Female Swivel on branch | 3 |
| VST-44X | Swivel Tee 1/4 with depressor | 1/4 SAE Flare x 1/4 Female Swivel on run x 1/4 SAE Flare on branch | 3 |
| VTR-24 | Threaded Tee Fitting | 1/8 MPT x 1/4 Male SAE Flare on run x 1/4 SAE Male Flare on branch | 3 |
| VTS-10 | Solder Tee Fitting | 5/8 ODS x 5/8 ODS on run with 1/4 SAE Male Flare on branch | 2 |
| VTS-46 | Solder Tee Fitting | 1/4 ODS x 1/4 ODS on run with 1/4 SAE Male Flare on branch | 3 |
| VTS-68 | Solder Tee Fitting | 3/8 ODS x 3/8 ODS on run with 1/4 SAE Male Flare on branch | 3 |
| VTS-810 | Solder Tee Fitting | 1/2 ODS x 1/2 ODS on run with 1/4 SAE Male Flare on branch | 3 |
| VUR-4 | Full Union | 1/4 OD SAE Flare x 1/4 SAE Flare with Cap | 6 |
| MSA-44 | Adaptor - SAE Female to MNPT | 1/4 SAE Female Swivel x 1/4 MNPT | 2 |

More products than you'll ever need

**80,000 sq ft across our 3 different
storage facilities**

We trade in over 30 countries

**What you want,
when you want it,
where you want it**



Service & Maintenance

5 Litre Concentrated Cleaners - PRO RANGE

Already established as a leading brand of professional coil cleaning and maintenance products, the DiversiTech PRO-RANGE of concentrated coil cleaners are designed to provide outstanding cleaning results combined with minimal environmental impact and maximum economy. Pro Universal is registered as NSF Food Safe, making it ideal to use in and around food processing areas.



| Code | Description | Size | Suitable for use on ... |
|--------------|---|---------|--|
| PRO-UNIV-GB | Concentrated – Indoor & Outdoor NSF Registered Food Safe Coil Cleaner | 5 Litre | Condensers / Evaporators / Air Filters |
| PRO-FOAM+GB | Concentrated – Heavy Duty Alkaline Based Condensing Coil Cleaner | 5 Litre | Condensers |
| PRO-CARE-GB | Concentrated – Evaporator Coil Cleaner with Disinfectant | 5 Litre | Evaporators / Protecting & Disinfectants |
| PRO-CLEAN-GB | Concentrated – Alkaline Based Evaporator & Condensing Coil Cleaner | 5 Litre | Condensers / Evaporators |
| PRO-COOL-GB | Concentrated – Non-Odour Liquid Ice Machine Cleaner | 5 Litre | Ice Machines |
| PRO-SCALE-GB | Concentrated - Lime Scale Remover | 5 Litre | Condensers / Exchangers |
| PRO-GREEN-GB | Concentrated - Environmentally Friendly Indoor and Outdoor Coil Cleaner | 5 Litre | Condensers / Evaporators / Air Filters |

1 Litre Pre-Mixed Cleaners G2G RANGE

The DiversiTech G2G-RANGE (Good to Go) are pre-mixed coil cleaners in a 1 litre convenient trigger bottle for quick and easy application.

G2G Universal is registered as NSF Food Safe, making it ideal to use in and around food processing areas.



| Code | Description | Size | Suitable for use on ... |
|---------------|---|---------|---|
| G2G-UNIV-GB | Pro Universal Pre-Mixed Coil Cleaner | 1 Litre | Condensers / Evaporators / Air Filters |
| G2G-FOAM+GB | Foaming Alkaline Based Pre-Mixed Coil Cleaner | 1 Litre | Condensers |
| G2G-CARE-GB | Liquid Coil Cleaner with Disinfectant | 1 Litre | Evaporators / Protecting & Disinfectant |
| G2G-GREEN+GB | Environmentally Friendly Pre-Mixed Coil Cleaner | 1 Litre | Condensers / Evaporators / Air Filter |
| G2G-BUBBLE-GB | Bubble Up Leak Detector Pre-Mixed | 1 Litre | Leak Detector |

Aerosols

Pump House are proud to present our re-branded range of aerosol cleaners. These professional aerosols are the perfect blend of high performance and excellent economy.

The range has seen improvements in formulation, scent, name and appearance.



| Code | Description | Size | Suitable for use on ... |
|-----------|---|-------|--|
| AER-D-600 | Coil Clean - Universal Coil Cleaner | 600ml | Condensers / Evaporators |
| AER-F-600 | Coil Foam - Heavy Duty Condenser Cleaner | 600ml | AC & Refrigeration Condenser Coils |
| AER-I-600 | Coil Care - Evaporator Cleaner & Disinfectant | 600ml | Condensers / Evaporators |
| AER-C-600 | Case Clean - Case, Fascia & Glass Cleaner | 600ml | Fan Coils, Cassette Units & Boiler Cases |
| AER-O-500 | Grease Buster - Solvent Based Cleaner & Degreaser | 600ml | Fan Coils, Cassette Units & Boiler Cases |
| AER-B-500 | Leak Seek - Bubble Up Detector Spray | 500ml | Leak Detector |

Odour Elimination

The Smell Buster range is a unique odour elimination product that effectively neutralises bad smells in air conditioning systems.

Available in 1 Litre pre-mixed spray bottles, 60g twin pack, 12g ten pack and 225g tray.



| Code | Description | Size | Suitable for use on ... |
|--------------------|---|------------------|-------------------------|
| SMELL-BUSTER-SMALL | Smell Buster - 12g tablets (pack of 10) | 12g (pack of 10) | RAC Systems |
| SMELL-BUSTER | Smell Buster - 60g tablets (pack of 2) | 60g (pack of 2) | RAC Systems |
| SMELL-BUSTER-B | Smell Buster - 225g (Tub) | 225g (Tub) | RAC Systems |
| G2G-SMELL-BUSTER | Smell Buster Pre Mixed | 1 Litre | RAC Systems |

Compression Sprayers

Various hand held and compression sprayers are available for applying coil cleaners to the coils. Designed for a fast and easy application.



| Code | Description | Capacity |
|------|--------------------------------|-------------|
| 1002 | Hand Held Sprayer | 1.4 Litres |
| 2601 | Compression Sprayer - 1 Gallon | 3.8 Litres |
| 2602 | Compression Sprayer - 2 Gallon | 7.4 Litres |
| 2603 | Compression Sprayer - 3 Gallon | 11.4 Litres |



Easy-Fit



Fixings



Flexi



Install



Partners



PH Family



PH Motors



Portable



Service



Squeezy

Service & Maintenance

Power Sprayer

The DiversiTech PS-1 portable power sprayer is a highly efficient machine designed for fast and easy application of coil cleaning products. Powered by a 12V/10Ah rechargeable battery, the sprayer saves labour time and is up to 3 - 4 times more efficient than a conventional compression sprayer. The sprayer can be operated continuously for up to 10 hours, included are three changeable nozzles to give you the right spray for any situation.



| Code | Description | Capacity |
|------|-------------------------------|-------------|
| PS-1 | Rechargeable Backpack Sprayer | 15.2 Litres |

Diversi-Flush™

Dirty and contaminated system? We have a unique system and line cleaning solution, ideal for dealing with compressor burn outs, R22 retrofits and equipment upgrades and replacements.

Effectively removes all traces of residual oil and contaminants, this easy-to-use kit includes everything needed to quickly and effectively clean the entire system.



| Code | Description | Size | Suitable for use on – |
|------------|---|-------|--|
| PF-KIT-EU | Diversi-Flush HVAC Flushing Kit – includes refill | 480ml | Compressor Burnouts, R22 retrofits, upgrades |
| PF-16-EU | Diversi-Flush Solvent Refill | 480ml | Compressor Burnouts, R22 retrofits, upgrades |
| PF-ADAPTOR | Line Set Adaptor | | Compressor Burnouts, R22 retrofits, upgrades |

DrainGun™

Blocked drain line - no problem with our DrainGun™. This lightweight, portable tool is designed to unblock condensate drain lines and other pipework instantly.

Simply insert a CO₂ cartridge in to the DrainGun and with a press of the trigger, SWOOSH, 800 psi of food grade CO₂ blows the blockage out.



| Code | Description | Size |
|-------|--|-------------|
| GG-1 | Drain Gun Line Cleaner | Single Pack |
| GGC-6 | Drain Gun – Pack of 6, CO ₂ Cartridges | Pack of 6 |
| GG-1A | Drain Gun – Adaptor Kit – for larger tubes, oil lines and 90 degree angles | 3 adaptors |
| GG-1H | Drain Gun – Hose Assembly | Single Pack |

Nitrogen Purge Tool

The DP-1 Nitrogen Purge Tool is a quick and easy way to purge copper pipes with nitrogen. Connect and turn the dial, this switches to a very low flow of nitrogen to braze the copper. It has a durable aluminium design so you can just throw it into your tool bag when you are done.



| Code | Description | Qty | Suitable for use on |
|------|---------------------|-----|--|
| DP-1 | Nitrogen Purge Tool | 1 | Purging and controlling the flow of nitrogen through pipework during brazing |

Universal Copper Spun Driers

Manufactured with the latest generation molecular sieves and compatible with many refrigerants including R134a, our universal copper spun driers can be used in all hermetic and open compressor refrigeration systems. This includes commercial and domestic refrigerators, freezers and air conditioners up to 2.0 HP. The driers are hermetically sealed with extended ends.



| Code | Outlet | Inlet | Diameter | Length | Desiccant R12 | Tonnage | Qty |
|-------|------------|------------|-------------|------------------|---------------|--------------|-----|
| DX-3 | 1/4" (6mm) | 1/4" (6mm) | 3/4" (19mm) | 7-11/16" (195mm) | 10 | 1/2 (1.75kW) | 1 |
| DX-4 | Multiple | 1/4" (6mm) | 1" (6mm) | 9" (228mm) | 18 | 1-1/2 (5kW) | 1 |
| DXA-5 | 1/4" (6mm) | 1/4" (6mm) | 1" (6mm) | 9-1/4" (235mm) | 20 | 1-1/2 (5kW) | 1 |

Telescopic Inspection Mirrors

Fast, accurate visual inspection of hidden areas with an almost limitless number of positions. Double ball joint links swivel mirrors for viewing 360 degrees. Precision engineered links are made from tempered spring steel to withstand the stresses of constant repositioning. Moves freely and holds in the desired position.



| Code | Description | Qty |
|------|---|-----|
| M-1 | Mirror 1-1/4" circular – extends 6-1/4" to 18-1/4" | 1 |
| M-1R | Replacement Head for M-1 | 1 |
| M-2 | Mirror 2-1/4" circular – extends 10" to 14" | 1 |
| M-2R | Replacement Head for M-2 | 1 |
| M-3 | Mirror 2-1/8" x 3-1/2" rectangular – extends 11-1/4" to 15-1/4" | 1 |
| M-3R | Replacement Head for M-3 | 1 |
| M-4 | Mirror 7/8" Circular – extends 6-1/2" | 1 |
| M-5 | Mirror 1" x 2" Oval – extends 8-1/2" | 1 |



Easy-Fit



Fixings



Flexi



Install +



Partners



PH Family



PH Motors



Portable



Service +



Squeezy

Tools

Fin-Tools & SuperComb

The Multihead fin-tool conveniently straightens and cleans condenser and evaporator fins. Each nylon head slides into the master handle and tightens in place. Heads are coloured and engraved with the size for fast identification. The metal fin straighteners have heavy duty spring wire bristles. The SuperComb has 6 coloured fins. The fin brush is a plastic handled fin brush to clean condenser and evaporator fins.

| Code | Description | Qty |
|-------|---|-----------|
| T-1 | Handle Only | 1 |
| T-100 | Kit 1 - Handle with 6 Heads - 8,9,10,11,12,14 | 1 |
| T-101 | Kit 2 - Handle with 6 Heads - 13,15,16,17,18,20 | 1 |
| T-8 | Head 8 FPI - Orange | Pack of 3 |
| T-9 | Head 9 FPI - Yellow | Pack of 3 |
| T-10 | Head 10 FPI - Neutral | Pack of 3 |
| T-11 | Head 11 FPI - Blue | Pack of 3 |
| T-12 | Head 12 FPI - Green | Pack of 3 |
| T-13 | Head 13 FPI - Pink | Pack of 3 |
| T-14 | Head 14 FPI - Light Green | Pack of 3 |
| T-15 | Head 15 FPI - Aqua | Pack of 2 |
| T-16 | Head 16 FPI - Brown | Pack of 3 |
| T-20 | Head 20 FPI - Purple | Pack of 3 |
| T-21 | Head 21& 22 FPI - Rose | Pack of 3 |

| Code | Description | Qty |
|-------|---|-----|
| T-200 | Fin Tool | 1 |
| T-300 | Fin Tool with Heavy Duty Bicycle Handle | 1 |

| Code | Description | Qty |
|-------|---|-----|
| T-400 | Set of 6 T-408, T-409, T-410, T-411, T-417, T-418 | 1 |
| T-408 | 8 and 10 FPI - Orange | 1 |
| T-409 | 9 and 15 FPI - Yellow | 1 |
| T-411 | 11 and 13 FPI - Blue | 1 |
| T-412 | 12 and 14 FPI - Green | 1 |
| T-417 | 16 and 17 FPI - Lime | 1 |
| T-418 | 18 and 20 FPI - Red | 1 |

| Code | Description | Qty |
|------|-------------|-----|
| B-26 | Fin Brush | 12 |



Compressor TOTE

Makes light work of a heavy job. Made from a strong powder coated steel. Recommended for use with all compressors up to 5 tons.

| Code | Description | Qty |
|-------|-----------------|-----|
| ACT-6 | Compressor Tote | 6 |

Cliplight - Pivot™ Torches

The Pivot™ range has a 360 degree swivel hook and is magnetic at the base and back. Available in colours Yellow/Black and Camo. All models are supplied with three AAA batteries.



| Code | Description | Colour | Lumens | UOM | Master Qty |
|--------|---|----------------|--------|------|------------|
| 111114 | Pivot – 5 LED Work Light | Yellow / Black | 240 | Each | Pack of 9 |
| 111115 | Pivot Mini – 18 LED Front Light / 3 LED Top | Yellow / Black | 120 | Each | Pack of 12 |
| 111117 | Pivot Mini – 18 LED Front Light / 3 LED Top | Camo | 120 | Each | Pack of 12 |
| 24-458 | Pivot 33 – 28 LED Front Light / 5 LED Top | Yellow / Black | 160 | Each | Pack of 9 |
| 24-460 | Pivot 33 – 28 LED Front Light / 5 LED Top | Camo | 160 | Each | Pack of 9 |

Cliplight - Clipstrip™ Torches

The Clipstrip™ range is a powerful pocket light with clip, available in colours Yellow/Black and Camo.

A waterproof aqua clipstrip is available. All models are supplied with three AAA batteries.



| Code | Description | Colour | Lumens | UOM | Master Qty |
|--------|-------------------------------|----------------|--------|------|------------|
| 111112 | Clipstrip – Pocket Light | Yellow / Black | 140 | Each | Pack of 12 |
| 111116 | Clipstrip – Pocket Light | Camo | 140 | Each | Pack of 12 |
| 111113 | Clipstrip – Aqua Pocket Light | Yellow / Black | 180 | Each | Individual |

Cliplight - HEMI™ Torches

The HEMI™ torches are available in Hemi Mini and Hemi Plus versions.

Available in colours Yellow & Black, these models are supplied a rechargeable cable, are super bright and have a top clip to hang the torch in most locations.



| Code | Description | Colour | Lumens | UOM | Master Qty |
|--------|--------------------------------|----------------|----------|------|------------|
| 114301 | Hemi – Mini Rechargeable Light | Black | 1000/500 | Each | Individual |
| 114302 | Hemi – Plus Rechargeable Light | Yellow / Black | 1200 | Each | Individual |



Easy-Fit



Fixings



Flexi



Install



Partners



PH Family



PH Motors



Portable



Service



Squeezy

Torches, Lights

Cliplight Seeker™ Torches

The Seeker™ range has a mini and max version. The UV light provides a circular spotlight with wide, focused or strobing capacities.

The mini can fit easily in your pocket and runs from AAA batteries. The max runs from a rechargeable lithium battery.



| Code | Description | Colour | Lumens | UOM | Master Qty |
|----------|---|--------|----------|------|------------|
| 84DCPLUS | Seeker – Mini UV LED Circular Spotlight | Red | UV Light | Each | Individual |
| 87DCPLUS | Seeker – Max UV LED Rechargeable Circular Spotlight | Red | UV Light | Each | Individual |

Cliplight Focus & Strobe

The Focus & Strobe light packs a big punch for a small light. The powerful single blue LED delivers a constant or stobe beam, which can be focused for intensity.



| Code | Description | Colour | Lumens | UOM | Master Qty |
|--------|----------------|--------|--------|------|------------|
| 111201 | Focus & Strobe | Blue | 180 | Each | Individual |

Pure-Beam™ Ultraviolet Light

Pure-Beam™ ultraviolet light is designed for HVAC air disinfection and surface irradiation. The 17 watt UV-C lamp is a powerful tool to improve indoor air quality. It can be installed in the HVAC system or ductwork on either the return or supply air side of the furnace or air handler.

Exposure to Pure-Beam™ significantly reduces air contamination caused by fungus, mold, and viruses and can cleanse surfaces overcome by mold and slime. Includes the UV lamp, a UL listed ceramic base, and mounting bracket.



| Code | Description | Colour | Lumens | UOM | Master Qty |
|------|---|--------|--------|------|------------|
| UV-1 | Ultraviolet Light with 24 VAC elec. Ballast | Blue | 180 | Each | Individual |

The Purifier - Fresh Ozone Machine

The purifier fresh ozone machine incorporates the latest in ozone purification technology to eliminate VOC's, mold, mildew, bacteria and viruses. Ideal for use in homes, offices, hotels, businesses to combat lingering odours.



| Code | Description | Dimensions (H x W x L) in mm | Colour | Voltage | Weight |
|---------|--|---------------------------------|--------|---------|--------|
| 170AIRP | The Purifier - Fresh Air Ozone Machine | 139.7mm x 139.7mm x 343mm | Silver | 240V | 2.3kg |

| Code | Description |
|-----------|--|
| 170AIRFAN | The Purifier - Replacement Fan |
| 410212 | The Purifier - Replacement Bulb |
| 170AIRPCB | The Purifier - Replacement Circuit Board |
| UVEC-07G | The Purifier - 12V Charger |

Super Seal Premium & Platinum™ - Pro A/C Stop Leak

Super Seal Premium and Platinum seals leaks in evaporators, condensers, accumulators as well as o-rings, gaskets, metal lines and rubber hoses. Actively prevents future leaks.

Easily installed in minutes and is compatible with all mobile A/C refrigerants including R12, R134A, and R1234YF. Hose included.



| Code | Description | Capacity | UOM | Master Qty |
|--------|---|--------------|------|------------|
| 946KIT | Super Seal Premium - with Pro A/C Stop Leak | 1.5oz / 45ml | Each | 12 |
| 976KIT | Super Seal Platinum - with Dry R & FLASH UV Dye | 1.7oz / 51ml | Each | 12 |

RETROCHILL™

Retrochill™ is a fast and effective solution to retrofit from R12 to 134A with conversion additives. 5 simple steps to convert. Once you have removed the R12 from your system, attach the hose, add retrochill, attach the refrigerant label and add the R134a retrofit oil. Hose included.



| Code | Description | Capacity | UOM | Master Qty |
|----------|---|------------|------|------------|
| 70501KIT | Retrochill R12 to R134A Kit | 3oz / 89ml | Each | 12 |
| 70510KIT | Retrochill R12 to R134A Kit - 10 x cans | 3oz / 89ml | Each | 1 |



Easy-Fit



Fixings



Flexi



Install



Partners



PH Family



PH Motors



Portable



Service



Squeezy

Super Seal™

Super Seal Advanced™ AC/R Stop Leak & Dry R

Super Seal™ is a 2-in-1 system additive that will find and seal leaks in refrigeration systems. It also contains an eliminator to dry any moisture in the system, preventing waxing and acid formation.

Super Seal is a light, low viscosity particle free liquid that is directly placed into the system as a mist - as it travels with the refrigerant and oil throughout the system, the sealant exits the leak point and reacts with moisture in the air - this forms a low tensile crystalline structure that creates a permanent seal. Super Seal Advanced™ comes with a reusable hose.



| Code | Description | Capacity | UOM | Master Qty |
|--------|--|------------|------|------------|
| 947KIT | Super Seal Advanced – up to 1.5 tons (5kW) | 1oz / 30ml | Each | 12 |
| 944KIT | Super Seal Advanced – 1.5 to 5 tons (5-17kW) | 2oz / 59ml | Each | 12 |
| 948KIT | Super Seal Advanced – 5+ tons (17Kw) | 3oz / 89ml | Each | 12 |

Super Seal Total™ AC/R Stop Leak & Dry R & Flash

Super Seal Total™ 3-in-1 dries, seals and includes Flash UV dye for a complete repair solution. Super Seal Total is fast and easy to install and requires no pump down or recovery. It's compatible with all oils and refrigerants and ideal for all systems including microchannel, heat pump and geothermal. Super Seal Total™ stops leaks now and prevents future ones too. Super Seal Total™ comes with a reusable hose.



| Code | Description | Capacity | UOM | Master Qty |
|--------|---|------------|------|------------|
| 971KIT | Super Seal Total – up to 1.5 tons (5kW) | 1oz / 30ml | Each | 12 |
| 972KIT | Super Seal Total – 1.5 to 5 tons (5-17kW) | 2oz / 59ml | Each | 12 |

Super Change™

Super Change™ is the fast and easy way to complete a R22 system retrofit. It creates a strong compatibility link between all oils to any HFC refrigerants, including POE-based R407C & R410A – eliminating compressor downtime and line set flush. It boosts efficiency plus extends compressor life by maximizing heat transfer and oil return with drop-in refrigerants. Ideal for dry charge units, retrofits and drop-in refrigerants. One can treats systems up to 6 tons. The 20122 reusable hose is required - sold separately



| Code | Description | Capacity | UOM | Master Qty |
|------|-----------------------------|----------|------|------------|
| 981 | Super Change – up to 6 tons | 2oz / ml | Each | 6 |

Flash™

Flash™ UV dye is an advanced class of highly concentrated ultra violet dye that uses DRY R™ instead of POE oil as its carrier. This, combined with our patented misting action, enables the dye to travel at the speed of the refrigerant while keeping the dye stable. One can treats up to 64 oz (1.8L) of oil. Flash UV dye uses the systems refrigerant as the propellant, creating a clean, no-mess injection every time. The 20122 reusable hose is required - sold separately.



| Code | Description | Capacity | UOM | Master Qty |
|------|-----------------------------|--------------|------|------------|
| 980 | Flash - up to 5 tons (17kW) | 0.14oz / 4ml | Each | 12 |

Flash™ UV Detection Kits

Two kits are available which include 3 cans of the Flash™ UV dye, reusable clear hose, heavy duty storage case and a choice of UV torch light.



98087KIT

| Code | Description | UOM |
|----------|---|-----|
| 98084KIT | Flash Kit - 3 cans of Flash - Hose - with SEEKER Mini | 1 |
| 98087KIT | Flash Kit - 3 cans of Flash - Hose - with SEEKER Max | 1 |

Dry R™

Dry R eliminates moisture and increases system efficiency. It also dissolves blockages and frees up TEVs - preventing acid and waxing formation. Dry R is compatible with all oils and refrigerants and one can treats systems up to 5 tons.



| Code | Description | Capacity | UOM | Master Qty |
|--------|---|------------|------|------------|
| 973KIT | Dry R Moisture Eliminator - up to 5 tons (17kW) | 1oz / 30ml | Each | 12 |

Accessories

| Code | Description | UOM |
|-------|---|-----|
| 20122 | Reusable Hose | 1 |
| 20128 | R410a & R32 Transitional Fitting 5/16 x 1/4 | 1 |



20122



20128



Easy-Fit



Fixings



Flexi



Install



Partners



PH Family



PH Motors



Portable



Service



Squeezy

Super Seal™

Sure Shot

Sure Shot™ Sealant Advanced with Eco Boost is a compressor-friendly method of permanently sealing leaks in AC/R systems. Eco Boost reduces noise and energy consumption, extends compressor life, plus eliminates 10 drops of water. It also enhances sealant performance, increases drier efficiency, while preventing waxing and acid formation. Sure Shot is added through an easy to inject syringe. One application works for systems up to 6 tons.

| Code | Description | UOM | Master Qty |
|--------|---|------|------------|
| 983KIT | Sure Shot Sealant Advanced HVAC/R Stop leak with hose | Each | 12 |
| 984 | Sure Shot Replacement Cartridge | Each | 12 |
| 940 | Sure Shot 1/4" SAE Reusable Hose | Each | 1 |



Flex Inject®

Flex Inject Sealant Advanced is the fastest, most effective proven way to permanently seal and prevent minor air conditioning and refrigeration (AC/R) leaks. With no tools or gauges required, the Flex Inject sealant works by travelling through the system with the oil and refrigerant fixing leaks immediately. Flex Inject works with all compressors, heat pumps, condensers, and other system components and it will not plug up manifold gauges, metering devices, thermostatic expansion valves (TEVs), pistons or cause cap tube blockages. It meets the ASHRAE ARI 700 refrigerant standard and is compatible with any refrigerant including R-410A with no pump downs or recoveries required. Flex Inject is suitable for use in aluminium and copper coils and is microchannel friendly.



| Code | Description | UOM | Master Qty |
|------|--|------|------------|
| 985 | Flexi Inject Sealant Advanced for systems up to 6 tons | Each | 6 |

Seal-N-Go™

Seal-N-Go makes charging 410A systems faster and easier than ever. Portable, easy to handle, self sealing refrigerant, permanently seals & prevents leaks. Reusable charging hose with easy to read gauge is sold separately.

| Code | Description | UOM | Master Qty |
|---------|--|------|------------|
| 9410SSR | Seal-N-Go 410A Refrigerant & Super Seal Advanced | Each | 6 |
| 20133 | Reusable Charging hose with easy to read gauge | Each | 1 |

* Only suitable where local F Gas Regulations permit



Oil & Cleaner

PAO 68 OIL



PAO 68 OIL & UV DYE



HYBRID A/C
COMPRESSOR OIL



DYE
CLEANER



AC Dye

900008



900006B



900012B



Multi Purpose Dye

909008



909006B



909012B



Radiator Dye

990008



990006B



990012B



Pag & Dye

511046 / 511101 / 511150



Ester & Dye

511102



| Code | Brand | Description | Size | Type |
|---------|----------|-----------------------------|----------------|-------------------|
| 51105 | Ciplight | PAO 68 Oil | 500ml (17oz) | Lubricant |
| 51110 | Ciplight | PAO 68 Oil | 1 Litre (34oz) | Lubricant |
| 51111 | Ciplight | PAO 68 Oil & Dye | 1 Litre (34oz) | Lubricant & Dye |
| 51112 | Ciplight | Hybrid a/c Compressor Oil | 236ml (8oz) | Compressor Oil |
| 805CLN | Ciplight | Dye Cleaner | 500ml (17oz) | Dye Remover |
| 900008 | Ciplight | A/C Dye | 236ml (8oz) | A/C Dye |
| 900006B | Ciplight | A/C Dye | 30ml (1oz) | A/C Dye |
| 900012B | Ciplight | A/C Dye | 7.5ml (0.25oz) | A/C Dye |
| 909008 | Ciplight | Multi-Purpose Dye | 236ml (8oz) | Multi-Purpose Dye |
| 909006B | Ciplight | Multi-Purpose Dye | 30ml (1oz) | Multi-Purpose Dye |
| 909012B | Ciplight | Multi-Purpose Dye | 7.5ml (0.25oz) | Multi-Purpose Dye |
| 990008 | Ciplight | Radiator Dye | 236ml (8oz) | Radiator Dye |
| 990006B | Ciplight | Radiator Dye | 30ml (1oz) | Radiator Dye |
| 990012B | Ciplight | Radiator Dye | 7.5ml (0.25oz) | Radiator Dye |
| 511046 | Ciplight | Pag & Dye (46 Viscosity) | 236ml (8oz) | Pag & Dye |
| 511101 | Ciplight | Pag & Dye (100 Viscosity) | 236ml (8oz) | Pag & Dye |
| 511150 | Ciplight | Pag & Dye (150 Viscosity) | 236ml (8oz) | Pag & Dye |
| 511102 | Ciplight | Ester & Dye (100 Viscosity) | 236ml (8oz) | Ester & Dye |



Easy-Fit



Fixings



Flexi



Install +



Partners



PH Family



PH Motors



Portable



Service +



Squeezy



Accessories

Pro Bubble Leak Detector Spray

Pro Bubble is an easy to use leak detector spray, ideal for locating gas and air leaks in pipes and equipment. It will not attack or react with metal surfaces and is highly efficient for the detection of ammonia, refrigerant gas and air leaks at below freezing temperatures.

| Code | Description | UOM | Master Qty |
|---------------|--|------|------------|
| PRO-BUBBLE-32 | Pro-Bubble Leak Detector Spray – 32oz with spray top | Each | 12 |



Cool-Weld™ Heat Barrier Spray

Cool-Weld™ is a spray on gel heat shield for soldering, sweating and welding. Ideal for use on filter driers, pipes, valves, sheet metals, etc. Can be used on porous surfaces such as fabrics or drywall. As long as there is some Cool-Weld™ present the surface will resist charring.

| Code | Description | UOM | Master Qty |
|-------------|--|------|------------|
| COOLWELD-32 | Cool-Weld Heat Barrier Spray – 32oz with spray top | Each | 12 |



Pull A Spout Oiler

All purpose oiler with a 35cm telescoping spout. Zooms out for long shots, and in for short shots, even zooms around corners. Squeeze bottle action. Perfect lubricant for general industrial use. Contains four ounces of finest quality carbon free, rust and oxidation inhibited lubricating oil. Plastic container won't short out around electrical connections. No leakage.

| Code | Description | UOM | Master Qty |
|------|---|------|------------|
| CO-1 | Pull a spout oiler – 4oz (118ml) with telescoping spout | Each | 12 |



Wypall Cloths

Heavy duty towels that absorb grease, oil, water and solvents from floors, hands, parts, tools and machinery.



| Code | Description | UOM | Master Qty |
|---------|----------------------------|------|------------|
| 5-05790 | WypAll Plus Towels – White | Each | Box of 9 |

Expanding Foam Sealant

A one component closed-cell expanding polyurethane foam sealant that is tack free in 20 minutes. Can be painted to prevent UV damage after 12 hours of drying time. Used to seal around doors, windows, pipes, ducts and vents - in fact, virtually anywhere. Foam contains fire retarding chemicals but is not rated as a fire stop product.

| Code | Description | UOM | Master Qty |
|-------|----------------------|------|------------|
| 01714 | Foam Sealant - 355ml | Each | 12 |
| 01724 | Foam Sealant - 591ml | Each | 12 |



Silicone Sealants

Available in clear or white, DiversiTech silicone sealants are 100% food grade and can be used in applications for continuous use up to 232°C. It is UV and water resistant and has long term flexibility.

| Code | Description | UOM | Master Qty |
|--------|--------------------------------|------|------------|
| 7-4000 | Clear Silicone Sealant - 305ml | Each | 12 |
| 7-4100 | White Silicone Sealant - 305ml | Each | 12 |



Diversi-Gum Sealing Compound

Diversi-Gum is a non-hardening, non-corrosive sealing compound that is immediately paintable and has a temperature usage range between -4°C and 49°C. It is ideal for sealing openings through foundations or refrigeration pipe entries.

| Code | Description | UOM | Master Qty |
|---------|--------------------------|------|------------|
| 6-202-1 | Diversi-Gum - 0.5kg Slug | Each | 24 |
| 6-202-2 | Diversi-Gum - 1kg Slug | Each | 20 |



Pro-Tite™ Resin Based Thread Sealant

A resin-based thread sealant that adheres to internal surfaces and fills voids while forming a fluid tight seal. Sealing from full vacuum up to 10,000 psi, Pro-Tite is specially formulated for use on metals and plastics subject to extreme vibration. Having a temperature range between -73°C to 204°C, Pro-Tite is impervious to most chemicals, including refrigerants, petroleum products, gases, steam etc.

| Code | Description | UOM | Master Qty |
|-------|------------------------------|------|------------|
| CLL-1 | Pro Tite Squeeze Tube - 39ml | Each | 12 |



Easy-Fit



Fixings



Flexi



Install



Partners



PH Family



PH Motors



Portable



Service



Squeezy

Accessories

Acid Test Kits

Detects acid in refrigeration oil. Convenient one step test means no chemicals are needed. Easy to evaluate, the colour change indicates acidity, the intensity of the colour indicates the amount of acid that is present in the oil sample.



| Code | Description | UOM | Master Qty |
|--------|------------------------------|------|------------|
| ATK-4 | Acid Test Kit – Pack of 4 | Each | 4 |
| ATK-1 | Acid Test Kit | Each | 1 |
| ATL-1P | Acid Test Kit – with POE Oil | Each | 1 |

Acid Eliminator

Keeps acid away; compatible with all refrigerants and oils. Chemically neutralises and prevents acids that are formed in air conditioning and refrigeration systems due to refrigerant and refrigeration oil break-down, moisture, and compressor burnout. Easy-to-use, no complicated charts. Works fast, circulates quickly, and leaves no solids or solid residual. Will not harm system components. Can prevent system breakdown.



ACID-ELIM

| Code | Description | UOM | Master Qty |
|-----------|-------------------------|------|------------|
| ACID-ELIM | Acid Eliminator - 115ml | Each | 12 |

Flow-Plus™ & Pro-Treat™ Condensate Pan Treatment

A range of Drain Pan treatments to help prevent blockages resulting in condensate overflow. Simply place the tablets in the drain pan, where they will slowly dissolve in the condensate to give a prolonged cleaning action on the sludge. One or two tablets are recommended in each pan per month.



FLOW-PLUS-25



FLOW-PLUS-6



PRO-TREAT 151



PRO-TREAT 152



PRO-TREAT 161

| Code | Description | Equipment Tonnage | UOM | Master Qty |
|---------------|--|----------------------|------|------------|
| FLOW-PLUS-25 | Flow Plus Condensate Drain Pan Tablets – 25 Tablets per Jar | 1/2 to 3 tons | Each | 12 |
| FLOW-PLUS-6 | Flow Plus Condensate Drain Pan Tablets – 6 x 1oz blocks | 3 to 5 tons | Each | 12 |
| PRO-TREAT 151 | Pro-Treat 151 Premium Drain Pan Tablets – 100 Tablets per Jar | 1 tablet per 3 tons | Each | 12 |
| PRO-TREAT 152 | Pro-Treat 152 King Size Premium Drain Pan Tablets – 12 Tablets per Jar | 1 tablet per 3 tons | Each | 6 |
| PRO-TREAT 161 | Pro-Treat 161 Condensate Drain Pan Tablets – 100 Tablets per Jar | 2 tablets per 3 tons | Each | 12 |

Quick Tap

Features a valve core in the 1/4in. male port. Simply pierce the line and back seat the needle. Flow starts when depressor type charging hose is connected.

| Code | Description | UOM | Master Qty |
|------|--|------|------------|
| QT-1 | Quick Tap – 1/4", 5/16", 3/8" OD (6.4mm, 8mm, 9mm) | Each | 1 |
| QT-2 | Quick Tap – 1/2", 5/8" OD (13mm, 16mm) | Each | 1 |



QT-1

QT-2

Quick Tap-2

Identical to the quick tap except that a nylon handle replaces the hex wrench, Phillips-head screws are used

| Code | Description | UOM | Master Qty |
|-------|--|------|------------|
| QTH-1 | Quick Tap 2 – 1/4", 5/16", 3/8" OD (6.4mm, 8mm, 9mm) | Each | 1 |
| QTH-2 | Quick Tap 2 – 1/2", 5/8" OD (13mm, 16mm) | Each | 1 |



QTH-1

MAC - The Ultimate in Line Piercing Valves

Install valve, connect charging hose, then service. That's all there is to it with a MAC line piercing valve. MAC valves feature a uniport single connection for piercing and servicing. Sealed with refrigerant resistant 'O' rings, the needle automatically back seats after servicing to leave the line free of restriction.

| Code | Description | UOM | Master Qty |
|-------|--|------|------------|
| QTM-1 | Line Piercing Valve – 1/4", 5/16", 3/8" OD (6.4mm, 8mm, 9mm) | Each | 1 |
| QTM-2 | Line Piercing Valve – 1/2", 5/8" OD (13mm, 16mm) | Each | 1 |



QTM-1

Insta-Tap Refrigerant Recovery Tool

The fastest, easiest way to evacuate refrigerant before disposal of a unit. Snaps onto refrigerant line for full and immediate flow. Punctures super large hole for maximum full flow discharge to recovery unit. One tool fits all sizes from 3/16in. to 7/8in. (4.76mm to 22.2mm) O.D. hard tubing. Replaceable needle.



QT-100

| Code | Description | UOM | Master Qty |
|---------|--|------|------------|
| QT-100 | Quick Tap 2 – 1/4", 5/16", 3/8" OD (6.4mm, 8mm, 9mm) | Each | 1 |
| QT-100N | Replacement Hardened Steel Needle and Gasket | Each | 1 |
| QT-100G | Replacement Gasket Only | Each | 3 |



Easy-Fit



Fixings



Flexi



Install



Partners



PH Family



PH Motors



Portable



Service



Squeezy

Line Piercing Valves and Tools

Line Tap and Swivel Valves

The quick, safe and easy option to charge, discharge and test a line. Simply clamp on the DLT valve, attach the DLV-1G control valve and pierce the line. The valve can swivel to any position and can also be removed and re-used. Available in three sizes from 4.8mm OD tube to 9.5mm



DLT-4G

| Code | Description | UOM | Master Qty |
|--------|---------------------------------|-----|------------|
| DLT-3G | Line Tap Valve - 4.75mm OD Tube | 1 | 1 |
| DLT-4G | Line Tap Valve - 6.35mm OD Tube | 1 | 1 |
| DLT-5G | Line Tap Valve - 8mm OD Tube | 1 | 1 |
| DCV-1G | Valve for DLT Line Taps | 1 | 1 |

Core Storer

All steel valve core remover and storage container. Completely knurled for easier grip, eliminating slippage when using with oily or greasy hands. Core Storer features a compartment for storing extra valve cores. Four replacement cores are included with each tool.



VCR-1

| Code | Description | UOM | Master Qty |
|-------|-------------------------|-----|------------|
| VCR-1 | Core Removal and Storer | 1 | 1 |

Core Removal Tool

Designed to remove and replace valve cores without losing the refrigerant charge. Connects to any 1/4in. male flare fitting. Saves time, saves refrigerant.



VCRT-1

| Code | Description | UOM | Master Qty |
|---------|---------------------------|-----|------------|
| VCRT-1 | Core Removal Tool | 1 | 1 |
| VCRT-1R | Replacement Rod Assembly | 1 | 1 |
| VCRT-1S | Replacement Shut-Off Stem | 1 | 1 |

RC-1 Insta-Charge

Faster, safer and a more economical method for charging LIQUID refrigerant through the low pressure side of an air conditioning or refrigeration system, without damaging the compressor. Insta-Charge's unique internal restrictor reduces liquid flow to a level below the capacity of the compressor. Converts liquid refrigerant to a saturated vapour for fast entry. Insta-Charge connects directly to the refrigerant can or cylinder valve. Adds liquid tracing dye faster. Eliminates heating of refrigerant cylinder. Made of light weight aluminium. Sold at a fraction of the cost of other fast charging devices.



RC-1

| Code | Description | UOM | Master Qty |
|------|--------------|-----|------------|
| RC-1 | Insta-Charge | 1 | 1 |

Cork & Foam Insulation Tape

Cork insulation tape adheres firmly to all metals, the foam insulation tape is a superior self-adhesive foam tape both of which can be used on hot or cold pipes to prevent heat loss and condensation dips. Easily cut and moulded, it fits well around valves and fittings.

Aluminium Foil Tape

An easy to handle aluminium tape that prevents heating and cooling losses and blocks odours and moisture. Has a 3-5 year shelf life and a working temperature range of -37°C to 127°C (-35°F to 260°F)

| Code | Description | UOM | Master Qty |
|----------|--|-----|------------|
| 6-330 | Cork Insulation Tape – Black 1/8" x 2" x 30ft Roll | 1 | 1 |
| 6-9718 | Foam Insulation Tape – Black 1/8" x 2" x 30ft Roll | 1 | 1 |
| 640-AF-2 | Aluminium Foil Tape - 2" x 50 yards Roll | 1 | 1 |

Abrasive Cloth

A high quality aluminium oxide 120 grit abrasive cloth, that can be used wet or dry to thoroughly clean steel and copper tubing.

Grip-Cut Cloth

A 180 grit open mesh sand screen cloth with aluminium oxide bonding, that is 100% waterproof. Can be used by hand or with portable tools and is most effective where clogging would be a problem such as soft materials.

| Code | Description | UOM | Master Qty |
|-------|---|-----|------------|
| SC-10 | Abrasive Cloth – 120 Grit – 1-1/2" x 10 yards | 1 | 1 |
| SCM-5 | Grip-Cut Open Mesh Sand Screen Cloth – 1-1/2" x 5 yards | 1 | 1 |

Braze Barrier Mats

This flame barrier drop cloth withstands temperatures to (1600°C) 3000°F No asbestos. Protects walls, floors, equipment components and adjacent surfaces from torch flames when soldering, brazing or welding.

| Code | Description | UOM | Master Qty |
|-------|---------------------------------------|-----|------------|
| 16500 | Plain Braze Barrier Mat 18" x 18" | 1 | 1 |
| 16510 | Keyhole Braze Barrier Mat - 18" x 18" | 1 | 1 |

6-330

6-9718

640-AF-2

SC-10

SCM-5

16500

16510



Easy-Fit



Fixings



Flexi



Install +



Partners



PH Family



PH Motors



Portable



Service +



Squeezy

Accessories

Portable Hand Torch

The combustion tip concentrates heat - reducing brazing time by 40%. This series has been redesigned with a patent pending ceramic igniting 1 piece stainless tip feature as well as a new diaphragm type regulator. Extremely durable with a full 3 year warranty.

| Code | Description | UOM | Master Qty |
|-----------|---------------------|------|------------|
| 525-TORCH | Portable Hand Torch | Each | 1 |



525-TORCH

Spark Key™

The Spark Key™ ignites all butane, propane and gas torches. 100,000 sure-fire sparks in a water resistant unit. No batteries are required.

| Code | Description | UOM | Master Qty |
|-----------|-------------------------|------|------------|
| SPARK KEY | Spark Key Torch Igniter | Each | 1 |



SPARK KEY

Flexi Patch™

Flexi-Patch™ is an easy to use flexible repair patch ideal for repairing almost any surface. It cures quickly using only UV light from sunlight or a UV flashlight for a long lasting, permanent repair.

Flexi-Patch is a fibreglass-reinforced polyester ideal for use on PVC, plastics, metal, wood, concrete and more. It's the easy way to permanently patch almost any surface. It dries hard for permanent repair. Can be drilled and painted once dry.



FP-36

| Code | Description | UOM | Master Qty |
|-------|--|------|------------|
| FP-36 | Flexi Patch Fibreglass repair patch - 75mm x 150mm - 10 per pack | Each | 20 |

Little Helper™ - all purpose cutter

Cuts up to 1-1/4inch. Polyethylene, thinwall PVC, ABS, rubber hose, NM conduit and clear vinyl tubing. Reversible stainless steel blade, like two blades in one. Sturdy all metal construction.



548-001

| Code | Description | UOM | Master Qty |
|---------|-------------------------------------|------|------------|
| 548-001 | Little Helper™ - all purpose cutter | Each | 1 |

Boiler, Heating & Renewables



Boiler Condensate Pumps

Tank Pumps

Pump House stock a range of boiler condensate removal pumps that are ideal when the boiler condensate can not be removed via gravity. The tank pumps use a small bore of flexible hose which can be routed above or below doors, windows or under kitchen cabinets.

When routing hose through any area which could be exposed to freezing temperatures, such as lofts, basements or garages, we strongly recommend increasing to at least 32mm plastic pipe and insulating.



PH-0.8LC



PH-0.8L-HL



VCMX-20STA



PH-20-STA

| Code | Brand | Description | Max Head | Max Flow | Drinks Cycle | Dimensions mm (HxWxD) | Discharge Size (inch) |
|------------|--------------|--------------------------------|----------|----------|--------------|-----------------------|-----------------------|
| PH-0.8LC | Pump House | 0.8 Litre Tank Pump with Cover | 3m | 150LPH | 200ml | 128x210x86 | 9.5mm (3/8) |
| PH-0.8L-HL | Pump House | 0.8 Litre Tank Pump | 6m | 270LPH | 300ml | 122x220x134 | 9.5mm (3/8) |
| VCMX-20STA | Little Giant | 1.4 Litre Tank Pump | 4.8m | 284LPH | 350ml | 165x260x122 | 9.5mm (3/8) |
| PH-20-STA | Pump House | 2 Litre Tank Pump | 5.5M | 402LPH | 650ML | 166x286x135 | 9.5mm (3/8) |

High Temperature & Pressure Relief Pumps

PRVSure PRV & Condensate Pump

This pump is manufactured from high temperature plastic, and comes complete with 10m of higher specification hose

It meets EN Standards and can handle temperatures up to 110 degrees. Supplied with 10 metres of 'no sag' high grade braided hose. The unique design also cools the PRV discharge so it is safe for use with solvent weld pipework. For installers who are audited or working to EN Standards.



PH-3.8L-HW

| Code | Brand | Description | Max Head | Max Flow | Temperature | Dimensions mm (HxWxD) | Discharge Size (inch) |
|------------|------------|--|----------|----------|-------------|-----------------------|-----------------------|
| PH-3.8L-HW | Pump House | Pressure Relief & Boiler Condensate Pump * | 8m | 312LPH | 110°C | 249x225x160 | 9.5mm (3/8) |

* meeting BS6798:2014 PRV requirements

High Temperature Pressure Relief Pump - PH-5L-HW

Designed for unvented cylinder T&P discharge and steam humidifiers. Having one of the largest discharge rates of 32 litres per minute this pump can handle both high temperature up to 100 degrees and high flow rates.

Manufactured in the UK this heavy duty, high temperature tank pump incorporates thermal overload protection and a high level alarm switch.



PH-5L-HW

| Code | Brand | Description | Max Head * | Max Flow | Temperature | Dimensions mm (HxWxD) | Discharge Size mm |
|----------|------------|---|------------|------------------|-------------|-----------------------|-------------------|
| PH-5L-HW | Pump House | High Temperature & Pressure Relief Pump | 8m / 20m | 32 LPM (1920LPH) | 100°C | 350x190x260 | 15mm |

* Max Heads - 8 metre for flow rates up to 25 Litres per minute / 20 metre for flow rates of 5 Litres per minute



Easy-Fit



Fixings



Flexi



Install



Partners



PH Family



PH Motors



Portable



Service



Squeezy

Condensate Neutralisers

Commercial Condensate Neutraliser - 20 & 30 Litres

Installing a neutraliser will reduce the impact of damage to existing boiler concrete drainage gullies and allow for the condensate to be disposed of safely.

The 20 litre stainless steel version can handle condensate from boilers up to 600kW by gravity. The 30 litre version comes complete with a pump to provide a 5.9 metre lift and a flow rate of up to 900 litres per hour. Both come with lime chippings for instant installation and are suitable for 2.8pH boiler condensate.



BCONDNEUT-20L*



BCONDNEUT-30L*

* Modular & bespoke designs are available for boilers over 600kW.

| Code | Brand | Description | Tank Capacity | Dimensions mm (HxWxD) | Discharge Size (inch) | Inlet | Weight |
|---------------|------------|-------------------------------------|---------------|-----------------------|-----------------------|-------|--------|
| BCONDNEUT-20L | Pump House | 20 Litre with lime chippings | 20 Litre | 200x400x300 | 9.5mm (3/8) | 40mm | 27kg |
| BCONDNEUT-30L | Pump House | 30 Litre with pump & lime chippings | 30 Litre | 200x550x305 | 9.5mm (3/8) | 40mm | 30kg |

Submersible Drainage Basement Pump

Little Giant have the perfect pump solution for the removal of clean, non-aggressive residual water.

This pump can be used to assist with the extraction of flood water in properties with basements and can be used with a sump to provide the removal of water below floor level.



6E-CIA-SFS

| Code | Brand | Description | Max Head | Max Flow | Dimensions mm (HxWxD) | Discharge Size (inch) | Weight |
|------------|--------------|------------------------|----------|-----------|-----------------------|-----------------------|--------|
| 6E-CIA-SFS | Little Giant | Drainage Basement Pump | 4.6m | 96(10)LPH | 258x269x213 | 38mm (1/2) | 12.7kg |

Swimming Pool Cover Pump - APCP-1700

The Little Giant APCP pool cover pump helps safeguard and protect the pool cover from prolonged accumulation of rain or melting snow. This automatic version is certified for use on pool covers, all of which can attach to a standard garden hose for easy water removal.

It removes standing water from pool covers and is ideal for household water transfer applications.



APCP-1700

| Code | Brand | Description | Max Head | Max Flow | Dimensions mm (HxWxD) | Discharge Size (inch) | Weight |
|-----------|--------------|---------------------------|----------|----------|-----------------------|-----------------------|--------|
| APCP-1700 | Little Giant | Automatic Pool Cover Pump | 6.6m | 6814LPH | 210x305x305 | 1" FNPT | 5.4kg |



Easy-Fit



Fixings



Flexi



Install



Partners



PH Family



PH Motors



Portable



Service



Squeezy

Soakaway & Condensate Bypass Valve

Soakaway Kit for Condensing Boilers

'Soak up' boiler condensate with our soakaway. Where a suitable gravity drain is not available the soakaway can be used in conjunction with 10mm lime chippings.

Compatible with the following pipe sizes:
22mm (3/4") overflow, 32mm (1-1/4") and
40mm (1-1/2").



Top View

SOAK 1



1. Dig hole (min depth) 400mm x 300mm in diameter, at least 500mm from the wall
2. Fill the bottom of the hole with 100mm depth of lime chippings.
3. Insert the soakaway tube with the lower drain holes facing away from the property.
4. Fill the remaining part of the hole and tube with lime chippings.
5. Feed the pipework either into the top or through the side of the soakaway.

| Code | Description | Height | Diameter | Inlet (inch) |
|-------|-------------------------------------|--------|----------|--------------------------------------|
| SOAK1 | Soakaway Kit for Condensing Boilers | 300mm | 110mm | 22mm (3/4) 32mm (1-1/4) 40mm (1-1/2) |

'Freezing Condensate Solution' Boiler Buoy Condensate Bypass Valve

Low cost, easy to install solution to bypass freezing pipes. Cutting a condensate pipe due to freezing has been common place over winter periods. The BB-1 Boiler Buoy condensate bypass valve is a solution that has been designed to be fitted during install, emergency call outs or whilst performing annual service visits.

A red float which when visible, indicates that the condensate pipe has a blockage or may be frozen.

The built in tap allows the householder to drain the condensate away safely and ensures that the heating of the property can continue to work.



BB-1

| Code | Description | Height | Diameter | Outlet | Hose Length |
|------|---------------------------------------|--------|----------|--------|-------------|
| BB-1 | Boiler Buoy - Condensate Bypass Valve | 115mm | 29mm | 9.5mm | 1.5m |

Accessories

Pump House stock a range of adaptors, connectors, clamps, clips and hose to connect the unit and pump.



| Code | Description | Pump Type Application | Pack Qty |
|---------------|---|--------------------------------|----------|
| ADAP-1 | Condensate Drain Adaptor - 22mm to 9.5mm (7/8 to 3/8) | Tank Pump - 9.5mm (3/8) outlet | Single |
| CV-38-3 | Non-return check valve - 9.5mm (3/8) | Tank Pump - 9.5mm (3/8) outlet | 3 Pack |
| PH-PUMP-NRV | Non-return check valve - 9.5mm (3/8) | Tank Pump - 9.5mm (3/8) outlet | Single |
| 154724 | Non-return check valve - 9.5mm (3/8) | VCMX-20STA pump | Single |
| ANTI-SYPH-KIT | Anti Syphon Kit - 9.5mm (3/8) | Tank Pump - 9.5mm (3/8) outlet | Single |
| 701-038 | Hose 'T' Connector - Nylon 9.5mm (3/8) | Tank Pump - 9.5mm (3/8) outlet | 2 pack |
| 701-032 | Hose Connector - Nylon 9.5mm (3/8) | Tank Pump - 9.5mm (3/8) outlet | 2 pack |
| B-6H | Hose Clamp - 6.3mm - 9.5mm (1/4 - 3/8) | All Pumps | Single |
| 927033 | Hose Clip - 9.5mm (3/8) | Tank Pump - 9.5mm (3/8) outlet | Single |
| RVT-1/4 | Condensate Drain Hose - 6.3mm (1/4) | Tank Pumps / Hot Water Pumps | 30m |
| RVT-3/8 | Condensate Drain Hose - 9.5mm (3/8) | Tank Pumps / Hot Water Pumps | 30m |
| RVT-1/2 | Condensate Drain Hose - 12.7mm (1/2) | Tank Pumps / Hot Water Pumps | 30m |

Self-Sealing Pipe Adaptor

The self-sealing adaptor is used to form a connection between condensate hose and a soil & vent pipe. Drill a 13mm hole (for SVA-3) or a 10mm hole (for SVA-6), insert and twist in to seal the connection.



SV-ADAPTOR

SV-ADAPTOR-6

| Code | Description | Pack Qty |
|--------------|--|----------|
| SVA-3 | Self-sealing pipe adaptor - 6mm & 9.5mm (1/4 & 3/8) hose to soil & vent pipe | 3 Pack |
| SV-ADAPTOR | Self-sealing pipe adaptor - 6mm & 9.5mm (1/4 & 3/8) hose to soil & vent pipe | Single |
| SVA-6-3 | Self-sealing pipe adaptor - 6mm (1/4) hose to soil & vent pipe | 3 pack |
| SV-ADAPTOR-6 | Self-sealing pipe adaptor - 6mm (1/4) hose to soil & vent pipe | Single |

Audible Alarm

This audible alarm can be wired into all pumps with a high level switch.



| Code | Brand | Description | Pack Qty |
|---------------|--------------|--|----------|
| AUDIBLE ALARM | Little Giant | Audible Alarm for all pumps with a high level switch | Single |



Easy-Fit



Fixings



Flexi



Install



Partners



PH Family



PH Motors



Portable



Service



Squeeze

Mounting

Flexi Lite Slab & Foot Kit

A low cost, lightweight floor mounting solution for air conditioning equipment and air source heat pumps.

Easy to transport, locate and construct.

The kit comes complete with two anti-vibration feet, a lightweight slab and all the fixings.



| Code | Description | Dimensions mm (HxWxL) | Weight | Safe Working Load* |
|-----------------|---|-----------------------|--------|--------------------|
| FF-UC3-S | Flexi Slab & Foot Kit (41mm Strut) 2 x 400mm Feet | 150x400x900 | 16kg | 400kg |
| FF-UC3 | Flexi Slab & Foot Kit (41mm Strut) 2 x 600mm Feet | 175x600x1200 | 25.5kg | 600kg |
| FF-UC3-3 | Flexi Slab & Foot Kit (41mm Strut) 3 x 600mm Feet | 175x600x1200 | 31kg | 600kg |
| FF-UC3-XL | Flexi Slab & Foot Kit (41mm Strut) 2 x 600mm Feet | 175x865x1200 | 31kg | 600kg |
| FF-UC3-ASN | Flexi Slab & Foot Kit (M10 strut) 2 x 600mm Narrow feet | 175x600x1200 | 47kg | 600kg |
| FF-UC-PLATE-KIT | Fixing Plate Kit - 4 Plates and Fixings | | | |



Ultralite® Slab

Don't be fooled - Ultralite® Slabs look and perform like a concrete slab, starting at only 7kg, they are lightweight and very easy to handle and transport. So give your aching back a rest and use Ultralite® slabs to mount AC units and air source heat pumps.



| Code | Description | Dimensions mm (HxWxL) | Weight | Safe Working Load* |
|----------|-------------------------|-----------------------|--------|--------------------|
| UC1636-2 | Ultralite Equipment Pad | 50x400x900 | 7kg | 300kg |
| UC2424-2 | Ultralite Equipment Pad | 50x600x600 | 7kg | 300kg |
| UC2436-3 | Ultralite Equipment Pad | 75x600x900 | 12kg | 485kg |
| UC2442-3 | Ultralite Equipment Pad | 75x600x1050 | 16kg | 595kg |
| UC2448-3 | Ultralite Equipment Pad | 75x600x1200 | 16kg | 700kg |

Flexi Foot Universal

The Flexi foot universal has three M10 inserts, offering support for small pipework and runs of cable tray, air source heat pumps and a variety of outdoor equipment. The installer is free to bolt their own strut of various lengths to suit any installation from 500mm to 3000mm in length. It can also be used to support both solar thermal and solar photovoltaic on flat roof installations.



FF-250-UNI



| Code | Description | Length mm | Width mm | Height mm | Safe Working Load* | Weight |
|-----------------------|---|-----------|----------|-----------|--------------------|--------|
| FF-250-UNI | Flexi Foot Universal – 250mm | 250 | 185 | 100 | 125kg | 2.8kg |
| Item | Material | | | | | |
| RUBBER | Compression moulded using milled, sieved and graded, recycled rubber bound with high quality adhesive | | | | | |
| DENSITY | 1.0kg / cm³ | | | | | |
| INSERTS | M10 (metric coarse thread) x 20mm zinc plated steel, through inserts | | | | | |
| MAX. TORQUE (INSERTS) | 15Nm | | | | | |
| MAX. LOAD (INSERTS) | 25kg | | | | | |

* The maximum load quoted is 25kg per insert and have been tested with a 4:1 safety ratio.

Flexi Fix Clamp

The Flexi Fix Clamp is used to add stability particularly with twin fan units. The Fix Clamp can be secured to the floor with anchor bolts.

FF-FIXCLAMP



| Code | Description | Length mm | Width mm | Height mm |
|-------------|----------------------|-----------|----------|-----------|
| FF-FIXCLAMP | Flexi Foot Fix Clamp | 240 | 60 | 103 |

Flexi Fix Packs

To complement our range of Flexi Feet we have created two versions of fix packs in either spring nut or T bolt. The packs contain bolts, nuts and washers for the installation of a pair of feet for a single condensing unit.



FF-FIX2

| Code | Description |
|-------------|--|
| FF-FIX-PACK | Components with spring bolts to secure an outdoor AC unit – for 2 Flexi Feet |
| FF-FIX-2 | Components with T bolts to secure an outdoor AC unit – for 2 Flexi Feet |

Anti-Vibration Mounting Bolts

The anti-vibration mounting bolts are in a convenient pack of 4. Each pack can be used with our wall brackets and is used as a method to absorb the vibrations generated by an ASHP or condensing unit.



AVMB-1

| Code | Description | For use with | Pack Qty |
|--------|-------------------------------|--------------|----------|
| AVMB-1 | Anti-vibration Mounting Bolts | All brackets | 4 |

Mounting



Flexi Foot With Strut Kits

These kits can be used to support air source heat pumps and come with a pair of feet, along with fixings to secure to unit to the feet.



| Code | Description | Length mm | Width mm | Height mm | Safe Working Load* | Weight |
|---------------|---|--------------|-------------|--------------|--------------------------|--------|
| FF-400-S-KIT | 2 x Flexi Foot with Strut 400mm with Fixings | 400 | 185 | 100 | 400kg | 9.2kg |
| FF-600-S-KIT | 2 x Flexi Foot with Strut 600mm with Fixings | 600 | 185 | 100 | 840kg | 15.2kg |
| FF-1000-S-KIT | 2 x Flexi Foot with Strut 1000mm with Fixings | 1000 | 185 | 100 | 1400kg | 24kg |

Flexi Foot With Strut

Flexi Foot With Strut – These feet can support pipework, cable tray, and can also be used to mount air conditioning units, air source heat pumps and a variety of outdoor equipment.

Solar thermal and solar photovoltaic on flat roof installations can also be accommodated. Made from heavy duty recycled rubber. The 21x41mm galvanised steel strut is supplied bonded to the rubber. Drain Slots are molded to the underside of the foot.



| Item | Material |
|---------|---|
| RUBBER | Compression moulded using milled, sieved and graded, recycled rubber bound with high quality adhesive |
| DENSITY | 1.0kg / cm ³ |
| STRUT | 41 x 21 x 1.5mm galvanised steel |

| Code | Description | Length mm | Width mm | Height mm | Safe Working Load* | Weight |
|-----------|--------------------------------|--------------|-------------|--------------|--------------------------|--------|
| FF-250-S | Flexi Foot With Strut – 250mm | 250 | 185 | 100 | 175kg | 2.8kg |
| FF-400-S | Flexi Foot With Strut – 400mm | 400 | 185 | 100 | 280kg | 4.6kg |
| FF-600-S | Flexi Foot With Strut – 600mm | 600 | 185 | 100 | 420kg | 7.6kg |
| FF-1000-S | Flexi Foot With Strut – 1000mm | 1000 | 185 | 100 | 700kg | 12.0kg |

* It is the installer's responsibility to ensure that equipment weights do not exceed the safe working loads quoted and that the roof structure onto which these products are being applied is sufficiently sound to withstand the weight and point loading. If these products are used in contact with a PVC roof membrane the installer should seek advice from the membrane manufacturer on the possible migration of plasticizers and the effect of this on the roof guarantee. These products should not be used for any purpose other than that for which they have been designed and the products must not be modified in any way. Pump House accepts no liability for damage caused by the incorrect application or installation of these products

Easy~Fit Brackets



Pump House offer a range of brackets which come flat packed, the Type 1 bracket has uprights and mounts directly onto the wall. Type 2 comes with a crossbar so that the uprights can be spaced exactly as required. The integral spirit level makes installation easier.

For improved corrosion resistance all metal now receives a 100% zinc plating, followed by a hard ED coating, before being finished with an external grade polyester textured powder coating in RAL 7032.



We also offer a range of stainless steel brackets, which are recommended for coastal locations exposed to sea salt or in other corrosive environments.

| Code | Size | Description | Crossbar mm | Upright mm | Support Arm mm | Safe Working Load* | Max Load | Weight |
|------------|------|--------------------------------|----------------|---------------|----------------------|--------------------------|-------------|--------|
| CBR1-S | S | Type 1 Bracket | | 450 | 480 | 60kg | 120kg | 3.6kg |
| CBR1-M | M | Type 1 Bracket | | 500 | 530 | 90kg | 180kg | 4.6kg |
| CBR1-L | L | Type 1 Bracket | | 550 | 580 | 140kg | 280kg | 4.7kg |
| CBR1-XL | XL | Type 1 Bracket | | 550 | 660 | 250kg | 500kg | 8.8kg |
| CBR1-XXL | XXL | Type 1 Bracket | | 550 | 1000 | 250kg | 500kg | 11kg |
| CBR2-S | S | Type 2 Bracket | 720 | 400 | 400 | 60kg | 120kg | 3.8kg |
| CBR2-M | M | Type 2 Bracket | 900 | 500 | 500 | 90kg | 180kg | 4.6kg |
| CBR2-L | L | Type 2 Bracket | 1100 | 550 | 540 | 140kg | 280kg | 6.6kg |
| CBR2-XL | XL | Type 2 Bracket | 1040 | 550 | 660 | 250kg | 500kg | 16.2kg |
| CBR2-XL-3A | XL | Type 2 Bracket (3 arms) | 1040 | 550 | 660 | 250kg | 500kg | 21.4kg |
| CBR2-M-SS | M | Type 2 Stainless Steel Bracket | 900 | 500 | 500 | 90kg | 180kg | 4.6kg |
| CBR2-L-SS | L | Type 2 Stainless Steel Bracket | 1040 | 550 | 540 | 140kg | 280kg | 6.7kg |
| CBR2-XL-SS | XL | Type 2 Stainless Steel Bracket | 1040 | 550 | 660 | 160kg | 280kg | 16.3kg |

* All brackets are tested to twice the safe working loads at an independent UK facility.

Collection Trays / Accessories / ASHP Soakaway

Easy~Fit Condensate Trays

The metal tray has a concave profile to ensure effective drainage. Supplied with fixing arms to hook over the bracket arms. For improved corrosion resistance all metal receives a 100% zinc plating, followed by a hard ED coating, before being finished with an external grade polyester textured powder coating in RAL 7032.



| Code | Size | Description | Dimensions mm (LxW) | Drain Connection | Weight |
|-----------|------|-------------------|---------------------|---------------------|--------|
| CCTM-800 | S | Metal Tray Small | 800x400 | 1/2 BSP Male Thread | 5.3kg |
| CCTM-1100 | M | Metal Tray Medium | 1100x400 | 1/2 BSP Male Thread | 7kg |
| CCTM-1400 | L | Metal Tray Large | 1400x400 | 1/2 BSP Male Thread | 8.3kg |

Floor Bracket Kit

When units are mounted at floor level, condensate discharge needs to be directed towards a drain or soakaway to avoid condensate causing a slip hazard.

This floor bracket kit allows the metal tray to be mounted onto a flexi foot kit. The ASHP can then be mounted onto the bracket.



| Code | Description | For use with | Pack Qty |
|---------------------|---------------------------------------|--------------------|----------|
| CCTM-FLOOR-BRKT-KIT | Stainless Steel brackets with fixings | Flexi Feet / Trays | 4 |

ASHP Soakaway

Removing air source heat pump condensate made easy! This unique pre-bagged textile soakaway is used to safely dispose of the condensate from all domestic sized ASHP where drain routing is not available.

The volume of condensate created from an ASHP up to 16kW can be between 10-15 litres per hour up to 2000 litres per year. This method prevents the condensate from flowing onto paths and driveways, which can freeze and cause a slip hazard.



* helps with MIS 3005 compliance and BRE 365

| Code | Description | Inlet | Diameter | Height |
|-----------|---|-------|----------|--------|
| ASHP-SDAK | Pre-bagged geo textile with rubber chippings* | 32mm | 400mm | 400mm |

Easy~Fit ASHP Guards

Pump House manufacture a range of weather-resistant, steel mesh guards, offering a safe solution to avoid vandalism or accidental damage of your expensive ASHP. The range is ideal for all manufacturers of ASHP units. The unique sliding panel system allows for easy installation, which are secured into place when the front panel is fitted. Back panels are also available to make the guard free standing. For high wall mounted units, we can offer a base panel for full security.



| Code | Size | External Dimensions mm (HxWxD) | | | Internal Dimensions mm (HxWxD) | | | Weight |
|--------------|-------|-----------------------------------|------|------|-----------------------------------|------|------|--------|
| CG-500-S | S | 620 | 1050 | 500 | 590 | 990 | 470 | 13kg |
| CG-500-M | M | 1020 | 1050 | 500 | 990 | 990 | 470 | 18kg |
| CG-500-L | L | 1420 | 1050 | 500 | 1390 | 990 | 470 | 23kg |
| CG-750-S | S | 950 | 1150 | 750 | 920 | 1120 | 740 | 25kg |
| CG-750-M | M | 1150 | 1150 | 750 | 1120 | 1120 | 740 | 32kg |
| CG-750-L | L | 1450 | 1150 | 750 | 1420 | 1120 | 740 | 33kg |
| CG-750-INV | INV | 1150 | 1450 | 750 | 1120 | 1420 | 740 | 33kg |
| CG-900L-INV | L-INV | 1150 | 1450 | 900 | 1120 | 1420 | 890 | 34kg |
| CG-900L-SQ | L-SQ | 1450 | 1450 | 900 | 1420 | 1370 | 890 | 51kg |
| CG-900-XXL | XXL | 1800 | 1450 | 900 | 1770 | 1370 | 890 | 60kg |
| CG-VRF-BP | BP-S | 2000 | 1160 | 1200 | 1970 | 1130 | 1200 | 64kg |
| CG-VRF-EP-6 | EP-S | 2000 | 580 | 1200 | 1970 | | 1200 | 24kg |
| CG-VRF-EP-12 | EP-M | 2000 | 1160 | 1200 | 1970 | | 1200 | 41kg |

Easy~Fit Wooden Guards

Made from tanalised, pressure-treated timber. All panels are louvered to optimise air flow. Sized to protect both ASHP and AC units, these guards offer a solution for listed buildings and sites where aesthetics are a consideration. All components are flat packed, easy to install, assemble and transport.



| Code | Size | External Dimensions mm (HxWxD) | | | Internal Dimensions mm (HxWxD) | | | Weight |
|-----------------|--------|-----------------------------------|------|-----|-----------------------------------|------|-----|--------|
| CG-750S-WOOD | S | 905/960 | 1275 | 865 | 850/890 | 1055 | 753 | 35kg |
| CG-750M-WOOD | M | 1135/1135 | 1275 | 865 | 1075/1115 | 1055 | 753 | 40kg |
| CG-750M+WOOD | M+ | 255/1310 | 1275 | 865 | 1200/1240 | 1055 | 753 | 44kg |
| CG-750L-WOOD | L | 1530/1585 | 1275 | 865 | 1475/1515 | 1055 | 753 | 51kg |
| CG-750LINV-WOOD | L-INV | 1130/1185 | 1630 | 865 | 1075/1115 | 1405 | 753 | 47kg |
| CG-750L+WOOD | L+ | 1600/1655 | 1275 | 865 | 1545/1585 | 1055 | 753 | 57kg |
| CG-750L+INVWOOD | L+ INV | 1655/1690 | 1630 | 865 | 1580/1620 | 1405 | 753 | 59kg |



Easy-Fit



Fixings



Flexi



Install +



Partners



PH Family



PH Motors



Portable



Service +



Squeezey

Flexi - Base & Extender Frames

The BASE & EXTENDER frames are designed to provide stability and spread loads evenly across flat roof surfaces. Modular frames for ASHP systems and VRV/VRF systems.

The galvanised steel frame raises equipment up to 405mm (higher heights available) above the flat roof level, permitting quick and easy access for roof maintenance.



Step One: Assemble a BASE FRAME



ORDER - PH-BF-B

Step Two: Need a bigger frame? Add an EXTENDER FRAME



ORDER - PH-EF-B

Step Three: Connect the BASE & EXTENDER FRAMES together



ORDER - PH-BF-B & PH-EF-B

| Item | Material |
|--------------|---|
| FEET | Square - 320mm square UV stabilised - 90% polypropylene and 10% grp |
| LEGS | 48mm diameter, 3mm galvanised steel tube. M24 galvanised steel height adjuster. 3mm galvanised steel U-clevis |
| BOX BEAMS | 40mm x 40mm x 2.5mm galvanised box section |
| CROSS BEAMS | 41mm x 41mm x 2.5mm galvanised steel slotted strut |
| FIXING BOLTS | M12 spun galvanised |



| Code | Description | Length | Width | Min. Height | Max. Height | Safe Working Load* | Weight |
|---------|----------------------|--------|--------|-------------|-------------|--------------------|--------|
| PH-BF-B | Flexi Base Frame | 1200mm | 1200mm | 300mm | 405mm | 500kg | 30kg |
| PH-EF-B | Flexi Extender Frame | 1200mm | 1200mm | 300mm | 405mm | 500kg | 24kg |

Flexi Foot Eco-Packs

An economical solution for the support of solar PV and solar thermal.

Flexi eco-packs offer the installer a simplistic and fast solution for the support of photovoltaic panels and solar thermal units where value engineering is required. Supplied in pairs, and available in 400mm, 600mm and 1000mm lengths these feet come with a fixing pack (M10 and spring nuts), for rigid securing to the A frame. These feet offer a base foundation to secure a length of cable tray which in turn acts as a carrier for the concrete paving slab ballast.



| Code | Description | Length mm | Width mm | Height mm | Safe Working Load* | Weight |
|-----------|--------------------------------|-----------|----------|-----------|--------------------|--------|
| FF-400-S | Flexi Foot with Strut – 400mm | 400 | 185 | 100 | 280kg | 4.6kg |
| FF-600-S | Flexi Foot with Strut – 600mm | 600 | 185 | 100 | 420kg | 7.6kg |
| FF-1000-S | Flexi Foot with Strut – 1000mm | 1000 | 185 | 100 | 700kg | 12.0kg |

Portables - Cool Only & Heat / Cool Pump

The portable air conditioners are suitable for offices, computer rooms and light commercial use.

The heat and cool model can be used as an energy efficient form of heating along with cooling. The cooling only model is ideal for cooling flats, conservatories or loft conversions during hot summer months.

The units come with a hose, tray, remote control and wall kit. Spare parts are available upon request.



PAC-C-12S



PAC-C-12

| Code | Description | Cool Capacity Btu / kW | Heat Capacity Btu / kW | Watts | Amps | Air Flow Volume | EER | COP | Sound Power Level dBA |
|-----------|----------------------|------------------------|------------------------|-------|------|-----------------|-----|-----|-----------------------|
| PAC-C-12 | Portable (Cooling) | 12,000 / 3.5 | N/A | 1350 | 5.9 | 370m³/h | 2.6 | N/A | 65 |
| PAC-C-12S | Portable (Cooling) | 12,000 / 3.5 | N/A | 1350 | 5.9 | 420m³/h | 2.6 | N/A | 56 |
| PAC-H-12 | Portable (Heat Pump) | 12,000 / 3.5 | 10,000 / 2.9 | 1350 | 5.9 | 370m³/h | 2.6 | 2.6 | 65 |
| PAC-H-12S | Portable (Heat Pump) | 12,000 / 3.5 | 12,000 / 3.5 | 1380 | 6 | 420m³/h | 2.6 | 2.7 | 56 |

| Code | Description | Height mm | Width mm | Depth mm | Weight | Hose Length | Refrigerant | Cooling Area |
|-----------|----------------------|-----------|----------|----------|--------|-------------|-------------|--------------|
| PAC-C-12 | Portable (Cooling) | 765mm | 467mm | 397mm | 34kg | 1.5m | R410A | 18-25m² |
| PAC-C-12S | Portable (Cooling) | 730mm | 485mm | 360mm | 28kg | 1.5m | R410A | 25-30m² |
| PAC-H-12 | Portable (Heat Pump) | 765mm | 467mm | 397mm | 37.5kg | 1.5m | R410A | 18-25m² |
| PAC-H-12S | Portable (Heat Pump) | 730mm | 485mm | 360mm | 28.5kg | 1.5m | R410A | 25-30m² |



Easy-Fit



Fixings



Flexi



Install



Partners



PH Family



PH Motors



Portable



Service



Squeezy

Flexible Hose & Insulation

Flexible Hose

Our flexible hose is designed to meet the requirements of the MCS MIS 3005 installation specification to allow the flow and return pipe work to connect to a heat pump. The flexible hose helps to avoid transmission of vibration in the pipe work and allows for a smooth blend when connecting the flow and return pipe to the heat pump or biomass boiler.

The 28mm hose is sleeved within a stainless steel braid for added protection, available in female or male BSP (British Standard Pipe) thread at one end and 28mm compression fitting at the other. The hose comes with 19mm thick weather proof, PVC coated insulation for UV stability and added robustness.



1" BSP Male



1" BSP Female



| Code | Description | Length | Diameter | Fitting 1 | Fitting 2 | Insulation |
|----------------------|--------------------------------|--------|----------|-------------|------------------|------------|
| FH-300-28-F-ELB | ASHP Flexible Hose 300 F Elbow | 300mm | 28mm | 1" FBSP | 28mm compression | 19mm |
| FH-300-28-11/4-F-ELB | ASHP Flexible Hose 300 F Elbow | 300mm | 28mm | 1-1/4" FBSP | 28mm compression | 19mm |
| FH-500-28-F | ASHP Flexible Hose 500 F | 500mm | 28mm | 1" FBSP | 28mm compression | 19mm |
| FH-750-28-F | ASHP Flexible Hose 750 F | 750mm | 28mm | 1" FBSP | 28mm compression | 19mm |
| FH-750-28-F-ELB | ASHP Flexible Hose 750 F Elbow | 750mm | 28mm | 1" FBSP | 28mm compression | 19mm |
| FH-750-28-11/4-F | ASHP Flexible Hose 750 F | 750mm | 28mm | 1-1/4" FBSP | 28mm compression | 19mm |
| FH-750-28-M | ASHP Flexible Hose 750 M | 750mm | 28mm | 1" MBSP | 28mm compression | 19mm |
| FH-1000-28-F | ASHP Flexible Hose 1000 F | 1000mm | 28mm | 1" FBSP | 28mm compression | 19mm |

PVC Coated External Grade Insulation

External condensate pipe work needs to be insulated in a tough PVC coated weather protected covering to avoid UV degradation and animal damage. Boiler installation standards BS 6798-2104 makes specific reference to this grade of insulation. ASHP and Biomass Boilers tend to be located externally and this hot water pipe work needs to be protected and insulated to avoid heat loss, MIS3005 and building regulations advise a certain thickness of insulation to meet heat loss requirements. Our PVC coated range helps installations comply in both boiler condensate and ASHP installations.



| Code | Description | Length | Diameter | Thickness | ID |
|--------------|--|--------|----------|-----------|------|
| FH-I-1000-15 | PVC Coated Weather & Waterproof Insulation | 1000mm | 41mm | 13mm | 15mm |
| FH-I-1000-22 | PVC Coated Weather & Waterproof Insulation | 1000mm | 60mm | 19mm | 22mm |
| FH-I-1000-28 | PVC Coated Weather & Waterproof Insulation | 1000mm | 66mm | 19mm | 28mm |
| FH-I-1000-35 | PVC Coated Weather & Waterproof Insulation | 1000mm | 73mm | 19mm | 35mm |

| Code | Description | Length | Width | Thickness | Qty |
|----------------|--------------------------------------|--------|-------|-----------|---------|
| INS-TAPE-10-PK | PVC Coated Weather & Waterproof Tape | 250mm | 50mm | 1mm | 10 pack |

Pre-Slit & Seal Weatherproof Insulation

Our new pre-slit & seal PVC coated insulation provides outstanding protection against freezing, for external boiler condensate pipe work and external heating pipe work on ASHP & biomass boilers. This new design offers a quick and secure 'tape free' installation, with its peel and seal join and its self-adhesive wrap over flap. Fully compliant with the Boiler Installation Standards BS6798:2014, the tough PVC coating is both weatherproof and UV stable.



Step One



Open the pre-slit insulation

Step Two



Wrap around the pipe, peel away yellow cover and seal together. Use the adhesive flap to secure.

Step Three



Condensate pipework is now fully protected with NEW pre-slit weatherproof insulation



Meets
BS 6798:2014
Boiler Installation
requirements

| Code | Description | Length | Thickness | ID |
|-------------------|-------------------------------|--------|-----------|------|
| FH-I-1000-35-SLIT | Pre-Slit Insulation – 35mm ID | 2000mm | 19mm | 35mm |
| FH-I-1000-28-SLIT | Pre-Slit Insulation – 28mm ID | 2000mm | 19mm | 28mm |
| FH-I-1000-22-SLIT | Pre-Slit Insulation – 22mm ID | 2000mm | 19mm | 22mm |

Through Wall Insulation Kit

Running pipe work from an externally mounted air source heat pump or biomass boiler into a property requires the pipe work to be run through the exterior wall. The hot pipe work will be affected by cold bridging and heat loss if it is not insulated correctly. MIS 3005 requires external pipe work to be adequately insulated. This kit provides both thermal insulation within the wall and comes complete with an elbow section to cover the external copper pipe connection.



Step One



Select a 65mm core drill

Step Two



Drill 2x 65mm holes next to each other

Step Three



Insert the PVC sleeve insulation, recess it to allow room for the elbow

Step Four



Fit the elbow over the copper pipes

| Code | Description |
|--------|--|
| TW-KIT | Sleeved PVC coated insulation kit – 19mm (2 x elbow & 2 x straight connectors) |



Easy-Fit



Fixings



Flexi



Install



Partners



PH Family



PH Motors



Portable



Service



Squeeze

100mm Trunking

The Inaba Denko 100mm trunking will ensure that the refrigeration pipes from an air source heat pump are protected with a professional finish. Available in Ivory and black to match most brands of condensing units available. MIS 3005 requires all external refrigeration pipe work on split and hybrid systems to be housed in trunking.



| Ivory | Black | Description | Depth mm | Width mm |
|--------------|-------------|-----------------------------------|----------|----------|
| ID-NSD-100-I | ID-SD-100-K | Slimduct Trunking (2000mm Length) | 70mm | 100mm |
| ID-SW-100-I | ID-SW-100-K | Slimduct Wall Cover | 70mm | 100mm |
| ID-SJ-100-I | ID-SJ-100-K | Slimduct Connector Piece | 70mm | 100mm |
| ID-SC-100-I | ID-SC-100-K | Slimduct 90 Degree Elbow Bend | 70mm | 100mm |
| ID-SK-100-I | ID-SK-100-K | Slimduct 90 Degree Flat Bend | 70mm | 100mm |

140mm Trunking

Pipe work and insulation running from air source heat pumps or biomass boilers should be protected. Our 140mm external trunking comes in Ivory and Black. The width of the trunking will accommodate the insulated flow and return pipes up to 28mm diameter along with any associated cabling.



| Ivory | Description | Depth mm | Width mm |
|-----------|--------------------------|----------|----------|
| TR-D-140 | Trunking (2000mm Length) | 90mm | 140mm |
| TR-WC-140 | Wall Cover | 90mm | 140mm |
| TR-CP-140 | Straight Connector | 90mm | 140mm |
| TR-IC-140 | 90 Degree Internal Bend | 90mm | 140mm |
| TR-FB-140 | 90 Degree Flat Bend | 90mm | 140mm |
| TR-EC-140 | 90 Degree External Bend | 90mm | 140mm |

| Black | Description | Depth mm | Width mm |
|-------------|--------------------------|----------|----------|
| TR-D-140-B | Trunking (2000mm Length) | 80mm | 140mm |
| TR-WC-140-B | Wall Cover | 80mm | 140mm |
| TR-CP-140-B | Straight Connector | 80mm | 140mm |
| TR-IC-140-B | 90 Degree Internal Bend | 80mm | 140mm |
| TR-FB-140-B | 90 Degree Flat Bend | 80mm | 140mm |
| TR-EC-140-B | 90 Degree External Bend | 80mm | 140mm |

Fused Spur Switches

| Code | Description |
|--------------|--|
| X-FSBBMC | Fused Spur Metal Clad – with Back Box |
| X-FSNBBMC | Fused Spur Metal Clad – with Back Box & Neon |
| X-FS | Fused Spur Plastic – without neon |
| X-FSN | Fused Spur Plastic – with neon |
| X-BBSM-25 | Back Box Surface Mount – 25mm |
| X-BBSM-35 | Back Box Surface Mount – 35mm |
| X-BBSM26-25 | Back Box 2 Gang – 25mm |
| X-BBSM2G-35 | Back Box 2 Gang – 35mm |
| X-BSPS-10A | Plug Socket – 10 Amp |
| X-2GSW2W-10A | Switch 2 Gang – 10 Amp |
| X-3GSW2W-10A | Switch 3 Gang – 10 Amp |
| X-1GDPSW-13A | Switch 1 Gang – 13 Amp |
| X-2GDPSW-13A | Switch 2 Gang – 13 Amp |
| X-DPSW-20A | Switch Double Pole – 20 Amp |
| X-PT | Plug Top – 13 Amp |

Fused Spur Metal



Fused Spur Plastic



Rotary Enclosed Isolators

Our insulated 3 and 4 pole rotary enclosed isolators are CE marked and suitable for disconnecting the power supply to outdoor air source heat pumps and air conditioning units.

The isolators are weatherproof to IP65, easy to install, conform to IEC 60947-3. They have a lockable off position and interlockable cover which can be removed only in the off position. Earth and neutral terminals included and M20/25 knockouts up to 63A.

Rotary Enclosed Isolators



| Code | No. of poles | Amps AC21 | AC23A 240VA | AC23A 400VA | Cable Capacity Solid | Cable Capacity Stranded | Height | Width | Depth |
|-------------|--------------|-----------|-------------|-------------|----------------------|-------------------------|--------|-------|-------|
| IS-3P-20A | 3 | 20 Amp | 5.5 kW | 3.7 kW | 1-16mm ² | 0.75-10mm ² | 175mm | 114mm | 135mm |
| IS-3P-32A | 3 | 32 Amp | 11 kW | 7.5 kW | 1-16mm ² | 0.75-10mm ² | 175mm | 114mm | 135mm |
| IS-3P-40A | 3 | 40 Amp | 15 kW | 11 kW | 1-16mm ² | 0.75-10mm ² | 175mm | 114mm | 135mm |
| IS-3P-63A | 3 | 63 Amp | 22 kW | 18.5 kW | 1-16mm ² | 0.75-10mm ² | 175mm | 114mm | 135mm |
| IS-4P-20A-S | 4 | 20 Amp | 5.5 kW | 3.7 kW | 1-16mm ² | 0.75-10mm ² | 125mm | 100mm | 120mm |
| IS-4P-20A | 4 | 20 Amp | 5.5 kW | 3.7 kW | 1-16mm ² | 0.75-10mm ² | 175mm | 114mm | 135mm |
| IS-4P-32A-S | 4 | 32 Amp | 11 kW | 7.5 kW | 1-16mm ² | 0.75-10mm ² | 125mm | 100mm | 120mm |
| IS-4P-32A | 4 | 32 Amp | 11 kW | 7.5 kW | 1-16mm ² | 0.75-10mm ² | 175mm | 114mm | 135mm |
| IS-4P-40A | 4 | 40 Amp | 15 kW | 11 kW | 1-16mm ² | 0.75-10mm ² | 175mm | 114mm | 135mm |
| IS-4P-63A | 4 | 63 Amp | 22 kW | 18.5 kW | 1-16mm ² | 0.75-10mm ² | 175mm | 114mm | 135mm |



Easy-Fit



Fixings



Flexi



Install



Partners



PH Family



PH Motors



Portable



Service




Squeazy

Pro Universal™

A frequent maintenance programme is vital for the efficient running and cost effective operation of Air Source Heat Pumps. DiversiTech has developed this range which not only cleans very effectively, but also has virtually no detrimental long-term effect on the equipment.

Pro-Universal™ features a special inhibitor that prevents its alkaline ingredient from attacking the coil. Instead it concentrates solely on actively breaking down soil and dirt. Pro-Universal & G2G Universal are NSF registered as food safe for use in food preparation areas.



Clean Coil



Dirty Coil



| Code | Description | Size | Suitable for use on ... |
|-------------|---|---------|--|
| PRO-UNIV-GB | Concentrated – Indoor & Outdoor NSF Registered Food Safe Coil Cleaner | 5 Litre | Condensers / Evaporators / Air Filters |
| G2G-UNIV-GB | Pro Universal Pre-Mixed Coil Cleaner | 1 Litre | Condensers / Evaporators / Air Filters |

Pro Green™

Pro-Green and G2G Green are friendlier on the environment. This coil cleaner is non-toxic, non-corrosive and readily biodegradable.

Ideal for condensers, evaporators and air filters and is NSF registered as food safe for use in food preparation areas.



| Code | Description | Size | Suitable for use on ... |
|--------------|--|---------|--|
| PRO-GREEN-GB | Concentrated – Environmentally Friendly Coil Cleaner | 5 Litre | Condensers / Evaporators / Air Filters |
| G2G-GREEN-GB | Pre-Mixed Environmentally Friendly Coil Cleaner | 1 Litre | Condensers / Evaporators / Air Filters |

Aerosols

Pump House are proud to present our re-branded range of aerosol cleaners. These professional aerosols are the perfect blend of high performance and excellent economy.

The range has seen improvements in formulation, scent, name and appearance.



| Code | Description | Size | Suitable for use on |
|-----------|---|-------|--|
| AER-D-600 | Coil Clean - Universal Coil Cleaner | 600ml | Condensers / Evaporators |
| AER-F-600 | Coil Foam - Heavy Duty Condenser Cleaner | 600ml | AC & Refrigeration Condenser Coils |
| AER-I-600 | Coil Care - Evaporator Cleaner & Disinfectant | 600ml | Condensers / Evaporators |
| AER-C-600 | Case Clean - Case, Fascia & Glass Cleaners | 600ml | Fan Coils, Cassette Units & Boiler Cases |
| AER-O-500 | Grease Buster - Solvent Based Cleaner & Degreaser | 600ml | Fan Coils, Cassette Units & Boiler Cases |
| AER-B-500 | Leak Seek - Bubble Up Detector Spray | 600ml | Leak Detector |

Compression Sprayers

Various hand held and compression sprayers are available for applying coil cleaners to the coils. Designed for fast and easy application.

| Code | Description | Capacity |
|------|--------------------------------|-------------|
| 1002 | Hand Held Sprayer | 1.4 Litres |
| 2601 | Compression Sprayer - 1 Gallon | 3.8 Litres |
| 2602 | Compression Sprayer - 2 Gallon | 7.4 Litres |
| 2603 | Compression Sprayer - 3 Gallon | 11.4 Litres |



DrainGun™

Blocked drain line - no problem with our DrainGun™. This lightweight, portable tool is designed to unblock condensate drain lines and other pipework instantly.

Simply insert a CO₂ cartridge in to the DrainGun and with a press of the trigger, SWOOSH... 800 psi of food grade CO₂ blows the blockage out.



| Code | Description | Size |
|-------|--|-------------|
| GG-1 | Drain Gun Line Cleaner | Single Pack |
| GGC-6 | Drain Gun - Pack of 6 CO ₂ Cartridges | Pack of 6 |
| GG-1A | Drain Gun - Adaptor Kit - for larger tubes, oil lines and 90 degree angles | 3 adaptors |
| GG-1H | Drain Gun - Hose Assembly | Single Pack |



Easy-Fit



Fixings



Flexi



Install



Partners



PH Family



PH Motors



Portable



Service



Squeezzy

Cliplight - Pivot™ Torches

The Pivot™ range has a 360 degree swivel hook and is magnetic at the base and back. Available in colours Yellow/Black and Camo. All models are supplied with three AAA batteries.



| Code | Description | Colour | Lumens | UOM | Master Qty |
|--------|---|----------------|--------|------|------------|
| 111114 | Pivot - 5 LED Work Light | Yellow / Black | 240 | Each | Pack of 9 |
| 111115 | Pivot Mini - 18 LED Front Light / 3 LED Top | Yellow / Black | 120 | Each | Pack of 12 |
| 111117 | Pivot Mini - 18 LED Front Light / 3 LED Top | Camo | 120 | Each | Pack of 12 |
| 24-458 | Pivot 33 - 28 LED Front Light / 5 LED Top | Yellow / Black | 160 | Each | Pack of 9 |
| 24-460 | Pivot 33 - 28 LED Front Light / 5 LED Top | Camo | 160 | Each | Pack of 9 |

Abrasive Cloth

A high quality aluminium oxide 120 grit abrasive cloth, that can be used wet or dry to thoroughly clean steel and copper tubing.

| Code | Description | UOM | Master Qty |
|-------|---|-----|------------|
| SC-10 | Abrasive Cloth - 120 Grit - 1-1/2" x 10 yards | 1 | 1 |



Grip-Cut Cloth

A 180 grit open mesh sand screen cloth with aluminium oxide bonding, that is 100% waterproof. Can be used by hand or with portable tools and is most effective where clogging would be a problem such as soft materials.

| Code | Description | UOM | Master Qty |
|-------|---|-----|------------|
| SCM-5 | Grip-Cut Open Mesh Sand Screen Cloth - 1-1/2" x 5 yards | 1 | 1 |



Braze Barrier Mats

This flame barrier drop cloth withstands temperatures to (1600°C) 3000°F. No asbestos. Protects walls, floors, equipment, components and adjacent surfaces from torch flames when soldering, brazing or welding.

| Code | Description | UOM | Master Qty |
|-------|---------------------------------------|-----|------------|
| 16500 | Plain Braze Barrier Mat 18" x 18" | 1 | 1 |
| 16510 | Keyhole Braze Barrier Mat - 18" x 18" | 1 | 1 |



16500



16510

Cool-Weld™ Heat Barrier Spray

Cool-Weld™ is a spray on gel heat shield for reducing heat transfer during soldering, brazing and welding. Ideal for use on pipes, valves, sheet metals, etc. Can be used on porous surfaces such as fabrics or drywall. As long as there is some Cool-Weld™ present the surface will resist charring. Easy to wipe off with a damp cloth after use.

| Code | Description | UOM | Master Qty |
|-------------|--|------|------------|
| COOLWELD-32 | Cool-Weld Heat Barrier Spray – 946ml with spray top. | Each | 12 |



Telescopic Inspection Mirrors

Fast, accurate visual inspection of hidden and hard to reach areas with an almost limitless number of positions. Double ball joint links swivel mirrors for viewing 360 degrees. Precision engineered links are made from tempered spring steel to withstand the stresses of constant repositioning. Moves freely and holds in the desired position.



| Code | Description | Qty |
|------|--|-----|
| M-1 | Mirror 1-1/4" circular – extends 32mm - 463mm (6-1/4" to 18-1/4") | 1 |
| M-1R | Replacement Head for M-1 | 1 |
| M-2 | Mirror 57mm (2-1/4") circular – extends 254mm - 355mm (10" to 14") | 1 |
| M-2R | Replacement Head for M-2 | 1 |
| M-3 | Mirror 54mm x 183mm (2-1/8" x 3-1/2") rectangular – extends 285mm - 387mm (11-1/4" to 15-1/4") | 1 |
| M-3R | Replacement Head for M-3 | 1 |
| M-4 | Mirror 22mm (7/8") Circular – extends 165mm (6-1/2") | 1 |
| M-5 | Mirror 25mm x 50mm (1" x 2") Oval – extends 191mm (8-1/2") | 1 |

Wypall Cloths

Heavy Duty towels that absorb grease, oil, water and solvents from floors, hands, parts, tools and machinery.



| Code | Description | UOM | Qty |
|---------|---|------|-------------|
| 5-05790 | WypAll Plus Towels – White, pack of 100 | Each | Pack of 100 |



Easy-Fit



Fixings



Flexi



Install



Partners



PH Family



PH Motors



Portable



Service



Squeazy

Expanding Foam Sealant

A one component closed-cell expanding polyurethane foam sealant that is tack free in 20 minutes. Can be painted to prevent UV damage after 12 hours of drying time. Used to seal around doors, windows, pipes, ducts and vents - in fact, virtually anywhere. Foam contains fire retarding chemicals but is not rated as a fire stop product.

| Code | Description | UOM | Master Qty |
|-------|----------------------|------|------------|
| 01714 | Foam Sealant - 355ml | Each | 12 |
| 01724 | Foam Sealant - 591ml | Each | 12 |



Silicone Sealants

Available in clear or white, DiversiTech silicone sealants are 100% food grade and can be used in applications for continuous use up to 232°C. It is UV and water resistant and has long term flexibility.

| Code | Description | UOM | Master Qty |
|--------|--------------------------------|------|------------|
| 7-4000 | Clear Silicone Sealant - 305ml | Each | 12 |
| 7-4100 | White Silicone Sealant - 305ml | Each | 12 |



Diversi-Gum Sealing Compound

Diversi-Gum is a non-hardening, non-corrosive sealing compound that is immediately paintable and has a temperature usage range between -4°C and 49°C. It is ideal for sealing openings through walls from pipe work.

| Code | Description | UOM | Master Qty |
|---------|--------------------------|------|------------|
| 6-202-1 | Diversi-Gum - 0.5kg Slug | Each | 24 |
| 6-202-2 | Diversi-Gum - 1kg Slug | Each | 20 |



Flexi Patch™

Flexi-Patch™ is an easy to use flexible repair patch ideal for repairing almost any surface. It cures quickly using only UV light from sunlight or a UV flashlight for a long lasting, permanent repair.

Flexi-Patch is a fiberglass-reinforced polyester ideal for use on PVC, plastics, metal, wood, concrete and more. It's the easy way to permanently patch almost any surface. It dries hard for permanent repair. Can be drilled and painted once dry. Capable of handling pressures upto 500psi and temperature range -26°C to 150°C



| Code | Description | UOM | Master Qty |
|-------|--|------|------------|
| FP-36 | Flexi Patch Fibreglass repair patch - 75mm x 150mm - 10 per pack | Each | 20 |

Plastic Pipe Fixings




| Code White | Code Black | Description | Pipe Size (mm) | Quantity |
|----------------|----------------|-----------------------------------|----------------|------------|
| PP-90EL-21.5-W | PP-90EL-21.5-B | Plastic Pipe - 90 Degree Elbow | 21.5mm | Pack of 10 |
| PP-45EL-21.5-W | PP-45EL-21.5-B | Plastic Pipe - 45 Degree Elbow | 21.5mm | Pack of 10 |
| PP-CON-21.5-W | PP-CON-21.5-B | Plastic Pipe - Straight Connector | 21.5mm | Pack of 10 |
| PP-T-21.5-W | PP-T-21.5-B | Plastic Pipe - T Connector | 21.5mm | Pack of 10 |
| PP-PIPE-21.5-W | PP-PIPE-21.5-B | Plastic Pipe | 21.5mm | 3 metre |

| Code White | Code Black | Code Grey | Description | Pipe Size (mm) | Quantity |
|------------|------------|------------|-------------------|----------------|-------------|
| PP-CL-15-W | | | Plastic Pipe Clip | 15mm | Pack of 100 |
| PP-CL-22-W | | | Plastic Pipe Clip | 22mm | Pack of 100 |
| PP-CL-28-W | | | Plastic Pipe Clip | 28mm | Pack of 100 |
| PP-CL-32-W | PP-CL-32-B | PP-CL-32-G | Plastic Pipe Clip | 32mm | Pack of 10 |
| PP-CL-40-W | PP-CL-40-B | PP-CL-40-G | Plastic Pipe Clip | 40mm | Pack of 10 |

| Code | Description | Size | Quantity |
|----------|----------------|-------|----------|
| X-SOLCEM | Solvent Cement | 250ml | 1 |

Plastic Pipe Clamps / Non-Return Valves

Our plastic pipe clamps are designed to connect overflow or waste hose pipe to an existing 32mm (1-1/4") or 40mm (1-1/2") pipe. To avoid waste water flowing back up the pipe work our non-return valves can be used on overflow pipe or waste hose pipe.



| Code | Description | Quantity |
|--------------------|---|----------|
| PP-CL-21.5-W-32-40 | Pipe Clamp Kit - 21.5mm overflow to 32mm (1-1/4") and 40mm (1-1/2") | 1 |
| PP-UNI-CL-W-32-40 | Pipe Clamp - Hose Connector 32mm (1-1/4") and 40mm (1-1/2") | 1 |
| PP-21.5-NRV | Non-Return Valve - for 21.5mm overflow pipe | 1 |
| PP-UNI-NRV | Non-Return Valve - with Hose Fitting | 1 |



Easy-Fit



Fixings



Flexi



Install +



Partners



PH Family



PH Motors



Portable



Service +



Squeazy

Strap On Boss

Using a Strap On Boss allows you to add condensate drain pipe to a soil and vent pipe, or to add a waste connection into an existing PVCu and cast iron soil pipe.

For use with 32mm or 40mm pipes.
Must be solvent welded into position.



PP-SOBoss-110-B-40



PP-SOBoss-110-G-40

| Code | Description | Quantity |
|--------------------|--|----------|
| PP-SOBoss-110-G-32 | Strap On Boss - 110mm Pipe with 32mm (1-1/4") Rubber - GREY | 1 |
| PP-SOBoss-110-G-40 | Strap On Boss - 110mm Pipe with 40mm (1-1/2") Rubber - GREY | 1 |
| PP-SOBoss-110-B-32 | Strap On Boss - 110mm Pipe with 32mm (1-1/4") Rubber - BLACK | 1 |
| PP-SOBoss-110-B-40 | Strap On Boss - 110mm Pipe with 40mm (1-1/2") Rubber - BLACK | 1 |
| X-PVCU-SOBSC-110MM | Strap On Boss - 110mm PVCU | 10 |

PVC Pipes



PVC-U - Elbow 3/4"
90 Degree



PVC-U - 3/4" Socket



PVC-U - 3/4" T Piece



PVC-U - 3/4"
Macflow Clips

| Code % inch | Code 1 inch | Code 1-1/4 inch | Description | Quantity |
|----------------|----------------|--------------------|------------------------------|----------|
| X-PVCU-3/4E-45 | | X-PVCU-1-1/4E-45 | PVCU - Elbow - 45 Degree | 10 |
| X-PVCU-3/4-45T | | X-PVCU-1-1/4-45T | PVCU - 45 Degree T | 10 |
| X-PVCU-3/4E-90 | X-PVCU-1E-90 | X-PVCU-1-1/4E-90 | PVCU - Elbow - 90 Degree | 10 |
| X-PVCU-3/4-MAC | X-PVCU-1-MAC | X-PVCU-1-1/4-MAC | PVCU - Macflow Clips | 10 |
| X-PVCU-3/4-EC | | | PVCU - End Cap | 10 |
| X-PVCU-3/4P-3M | X-PVCU-1P-3M | X-PVCU-1-1/4-3M | PVCU - Pipe - 3 Metre Length | 10 |
| X-PVCU-3/4-SOC | X-PVCU-1-SOC | X-PVCU-1-1/4-SOC | PVCU - Socket | 10 |
| X-PVCU-3/4-CAP | | X-PVCU-1-1/4-CAP | PVCU - Threaded Cap | 10 |
| X-PVCU-3/4-PIN | | X-PVCU-1-1/4-PIN | PVCU - Pin / Barrel | 10 |
| X-PVCU-3/4-R | | X-PVCU-1-1/4-R | PVCU - Reducer | 10 |
| X-PVCU-3/4-RE | | X-PVCU-1-1/4-RE | PVCU - Rodding Eye | 10 |
| X-PVCU-3/4-TP | X-PVCU-1TP | X-PVCU-1-1/4-TP | PVCU - T Piece | 10 |

Flexi Support



Light - Flexi Base & Extender Frames

BASE & EXTENDER frames are designed to provide stability and spread loads evenly across flat roof surfaces. Modular frames are ideal for a/c split systems and VRV/VRF systems.

The galvanised steel frame raises equipment up to 405mm (higher heights available) above the flat roof level, permitting quick and easy access for roof maintenance.



Step One: Assemble a BASE FRAME



ORDER - PH-BF-B

Step Two: Need a bigger frame? Add an EXTENDER FRAME



ORDER - PH-EF-B

Step Three: Connect the BASE & EXTENDER FRAMES together



ORDER - PH-BF-B & PH-EF-B

| Item | Material |
|--------------|---|
| FEET | Square - 320mm square UV stabilised - 90% polypropylene and 10% grp |
| LEGS | 48mm diameter, 3mm galvanised steel tube, M24 galvanised steel height adjuster, 3mm galvanised steel U-clevis |
| BOX BEAMS | 40mm x 40mm x 2.5mm galvanised box section |
| CROSS BEAMS | 41mm x 41mm x 2.5mm galvanised steel slotted strut |
| FIXING BOLTS | M12 spun galvanised |



| Code | Description | Length | Width | Min. Height | Max. Height | Safe Working Load** | Weight |
|---------|----------------------|--------|--------|-------------|-------------|---------------------|--------|
| PH-BF-B | Flexi Base Frame | 1200mm | 1200mm | 300mm | 405mm | 500kg | 30kg |
| PH-EF-B | Flexi Extender Frame | 1200mm | 1200mm | 300mm | 405mm | 500kg | 24kg |

Everyday - Flexi H-Frame Kits

Our H-frame kits offer the installer full flexibility by providing a solution where they can supply their own strut to suit their installation requirements.

The H-frame kits are supplied with a pair of either our 320mm feet, most widely used in the majority of installations, or where heavier more demanding loads are present, then our 500mm foot version kit is available.

All kits are supplied with hot dip galvanised angle brackets together with all the necessary fixings to assist the installer in a low cost, versatile and fast assembly solution on site. Complete strut assembled frameworks, (H-frame kits where the strut is also supplied), are available upon request.

F-HF-500



F-HF-320



| Code | Description | Foot Size | Safe Working Load** | Weight |
|----------|--|---------------|---------------------|--------|
| F-HF-320 | Flexi H-Frame Kit - 2 square black feet with fittings* | 320mm x 320mm | 250kg | 4kg |
| F-HF-500 | Flexi H-Frame Kit - 2 square black feet with fittings* | 500mm x 500mm | 600kg | 13kg |

| Item | Material |
|----------------|---|
| FEET | Square - 320mm and 500mm square UV stabilised - 90% polypropylene and 10% grp |
| MAT | 100% natural rubber, (mat is adhered to the feet) |
| FIXINGS | M10 ZP sets, spring washers and nuts |
| ANGLE BRACKETS | Mild steel, hot dipped galvanised BS EN ISO 1461:2009 |

* NB - the lengths of the strut are not supplied with this kit. ** As the strut is not supplied with the kit, the maximum load is a guide only



** It is the installer's responsibility to ensure that equipment weights do not exceed the safe working loads quoted and that the roof structure onto which these products are being applied is sufficiently sound to withstand the weight and point loading. If these products are used in contact with a PVC/TPO roof membrane the installer should seek advice from the membrane manufacturer on the possible migration of plasticizers and the effect of this on the roof guarantee. These products should not be used for any purpose other than that for which they have been designed and the products must not be modified in any way. Pump House accepts no liability for damage caused by the incorrect application or installation of these products..



Easy-Fit



Fixings



Floor



Install



Partners



PH Family



PH Motors



Portables



Service



Squeezey

Everyday - Flexi Foot With Strut

Flexi Foot With Strut – These feet can support pipework, cable tray, and can also be used to mount air conditioning units, air source heat pumps and a variety of outdoor equipment.

Solar thermal and solar photovoltaic on flat roof installations can also be accommodated. Made from heavy duty recycled rubber. The 21x41mm galvanised steel strut is supplied bonded to the rubber. Drain slots are molded to the underside of the foot.



| Item | Material |
|---------|---|
| RUBBER | Compression moulded using milled, sieved and graded, recycled rubber bound with high quality adhesive |
| DENSITY | 1.0kg / cm ³ |
| STRUT | 41 x 21 x 1.5mm galvanised steel |



| Code | Description | Length mm | Width mm | Height mm | Safe Working Load* | Weight |
|-----------|--------------------------------|--------------|-------------|--------------|--------------------------|--------|
| FF-250-S | Flexi Foot With Strut – 250mm | 250 | 185 | 100 | 175kg | 2.8kg |
| FF-400-S | Flexi Foot With Strut – 400mm | 400 | 185 | 100 | 280kg | 4.6kg |
| FF-600-S | Flexi Foot With Strut – 600mm | 600 | 185 | 100 | 420kg | 7.6kg |
| FF-1000-S | Flexi Foot With Strut – 1000mm | 1000 | 185 | 100 | 700kg | 12.0kg |

| Code | Description | Length mm | Width mm | Height mm | Safe Working Load* | Weight |
|--------------|---|--------------|-------------|--------------|--------------------------|--------|
| FF-250-S-P-L | Flexi Foot With Strut – 250mm – Low Profile | 250 | 185 | 50 | 100kg | 1.4kg |
| FF-400-S-P-L | Flexi Foot With Strut – 400mm – Low Profile | 400 | 185 | 50 | 150kg | 2.3kg |

Everyday - Flexi Foot Universal

The Flexi Foot Universal has three M10 inserts, offering support for small pipework and runs of cable tray, for air source heat pumps and a variety of outdoor equipment. The installer is free to bolt their own strut of various lengths to suit any installation from 500mm to 3000mm in length. It can also be used to support both solar thermal and solar photovoltaic on flat roof installations.



FF-250-UNI



| Code | Description | Length mm | Width mm | Height mm | Safe Working Load* | Weight |
|------------|------------------------------|--------------|-------------|--------------|--------------------------|--------|
| FF-250-UNI | Flexi Foot Universal – 250mm | 250 | 185 | 100 | 125kg | 2.8kg |

| Item | Material |
|-----------------------|---|
| RUBBER | Compression moulded using milled, sieved and graded, recycled rubber bound with high quality adhesive |
| DENSITY | 1.0kg / cm ³ |
| INSERTS | M10 (metric coarse thread) x 20mm zinc plated steel, through inserts |
| MAX. TORQUE (INSERTS) | 15Nm |
| MAX. LOAD (INSERTS) | 25kg |

* The maximum load quoted is 25kg per insert and have been tested with a 4:1 safety ratio.

Flexi Fix Clamp

The Flexi Fix Clamp is used to add stability particularly with twin fan units. The Fix Clamp can be secured to the floor with anchor bolts.

| Code | Description | Length mm | Width mm | Height mm |
|-------------|----------------------|--------------|-------------|--------------|
| FF-FIXCLAMP | Flexi Foot Fix Clamp | 240 | 60 | 103 |



FF-FIXCLAMP

Flexi Fix Packs

To complement our range of Flexi Feet we have created two versions of fix packs in either spring nut or T bolt. The packs contain bolts, nuts and washers for the installation of a pair of feet for a single condensing unit.



FF-FIXPACK



FF-FIX2

| Code | Description |
|-------------|--|
| FF-FIX-PACK | Components with spring bolts to secure an outdoor AC unit – for 2 Flexi Feet |
| FF-FIX-2 | Components with T bolts to secure an outdoor AC unit – for 2 Flexi Feet |

Protection Fleece

Geotextile polyester fleece for PVC/TPO field membrane protection. Sold by linear metre. Please specify requirements.

| Code | Description | Density |
|--------|-------------------------------------|---------|
| MPF-12 | Protection Fleece – 2000mm x 1000mm | 300gsm |



MPF-12



Easy-Fit



Fixings



Fleece



Install +



Partners



PH Family



PH Material



Products



Service +



Support

Support Systems for Building Services

Flexi Foot - Variations

To complement our range of Flexi Feet we have an number of variations on the standard flexi foot with strut. The foot only options are available in 200, 350 and 500mm with angle pitch variants.

PH-FO-350-5.0-S

PH-FO-200



| Code | Description | Length mm | Width mm | Height mm | Safe Working Load** | Weight |
|-----------------|--|-----------|----------|-----------|---------------------|--------|
| PH-FO-200 | Flexi Foot - 200mm for vertical strut / M10 thread | 200 | 200 | 85 | 100kg | 2.3kg |
| PH-FO-350 | Flexi Foot - 350mm for vertical strut | 350 | 350 | 110 | 150kg | 5.7kg |
| PH-FO-350-2 | Flexi Foot - 350mm for vertical 82x41mm strut | 350 | 350 | 110 | 150kg | 5.7kg |
| PH-FO-350-2.5-S | Flexi Foot - 350mm for vertical 2.5 degree | 350 | 350 | 125 | 150kg | 5.9kg |
| PH-FO-350-5.0-S | Flexi Foot - 350mm for vertical 5.0 degree | 350 | 350 | 140 | 150kg | 6.1kg |
| PH-FO-500 | Flexi Foot - 500mm for vertical strut | 500 | 500 | 110 | 150kg | 10.5kg |
| PH-FO-500-2 | Flexi Foot - 500mm for vertical 82x41mm strut | 500 | 500 | 110 | 150kg | 10.5kg |
| PH-FO-500-2.5 | Flexi Foot - 500mm for vertical 2.5 degree | 500 | 500 | 130 | 150kg | 10.7kg |
| PH-FO-500-5.0 | Flexi Foot - 500mm for vertical 5.0 degree | 500 | 500 | 150 | 150kg | 10.9kg |

Flexi Mini Foot

Lightweight support that may be used with horizontal or vertical strut to support low level cable tray and other services.

- Accepts 41mm x 41mm strut vertically into core
- Accepts 41mm x 41mm strut horizontally via fixing screw (supplied)
- Foam anti-vibration pad pre-fitted to the base
- Made from UV-stable pvc, strut not supplied

F-MF-160



| Code | Description | Length mm | Width mm | Height mm | Safe Working Load** | Weight |
|----------|-------------------------|-----------|----------|-----------|---------------------|--------|
| F-MF-160 | Flexi Mini Foot - 160mm | 160 | 160 | 60 | 50kg | 230g |

Walkway Mat

WW-MAT-500

Walkway mats may be combined to define a safe access path whilst protecting the roof surface.



| Code | Description | Length mm | Width mm | Height mm | Safe Working Load** | Weight |
|------------|---------------------|-----------|----------|-----------|---------------------|--------|
| WW-MAT-500 | Walkway Mat - 500mm | 500 | 500 | 45 | 150kg | 14kg |

** It is the installer's responsibility to ensure that equipment weights do not exceed the safe working loads quoted and that the roof structure onto which these products are being applied is sufficiently sound to withstand the weight and point loading. If these products are used in contact with a PVC/TPO roof membrane the installer should seek advice from the membrane manufacturer on the possible migration of plasticizers and the effect of this on the roof guarantee. These products should not be used for any purpose other than that for which they have been designed and the products must not be modified in any way. Pump House accepts no liability for damage caused by the incorrect application or installation of these products.

Heavy - Flexi Twin Frames

Frames for large pipes, air handling units, chillers and packaged plant rooms. These robust & versatile free standing modular frames are supplied with fully adjustable leg assemblies in 500mm square polypropylene feet, incorporating anti-vibration rubber mats adhered to the underside. Robust 50 x 50mm box cross bars are 5mm thick to cater for mid-span point loads, resulting in even load dispersal through the framework down to each foot.

The optional mounting plate can be purchased in addition or as an alternative to the adjustment being in the leg assemblies. Therefore a non-adjustable twin is also available.

Application: Suitable for heavier building services such as large air handling units, chillers and packaged plantrooms. An ideal solution when the criteria to target existing roof beams is necessary. The twin frames can be targeted immediately above to assist direct load transfer to existing roof beams below: a common requisite in weaker roof designs.



F-TWIN-500-A

| Item | Material |
|------------|--|
| FEET | Square - 500mm square UV stabilised - 90% polypropylene and 10% grp. |
| MAT | 100% natural rubber, (mat is adhered to the feet) |
| LEGS | 48mm dia. 3mm stud steel tube with M24 stud adjuster and 4mm thick U clevis to top |
| CROSS BARS | 50x50x5mm SHS (Square hollow section) with optional mounting plate if required |
| FINISH | Hot dip galvanised steelwork BS EN 10219-1: 2006 Galvanising BS EN ISO 1461:2009 Salt Mist Testing: BS EN 60068-2-52:2018 |



Double Mounting Plate
Part Code - F-TQ-ADJ-D



Single Mounting Plate
Part Code - F-TQ-ADJ-S

| Code | Description | Length mm | Width mm | Height mm | Weight | Max Load |
|--------------|----------------------------------|-----------|----------|--------------------|--------|----------|
| F-TWIN-500 | Flexi TWIN (non-adjustable legs) | 1200mm | 500mm | 300mm | 28kg | 1000kg |
| F-TWIN-500-A | Flexi TWIN (adjustable legs) | 1200mm | 500mm | 240-370mm | 30kg | 1000kg |
| F-TQ-ADJ-S | Single Mounting Plate | 250mm | 150mm | - | 3kg | - |
| F-TQ-ADJ-D | Double Mounting Plate | 250mm | 150mm | 170mm (adjustable) | 8kg | - |



Easy-Fit



Pavings



Flexi



Install



Partners



Pit Family



Pit Motors



Portals



Service



Squeaky

Support Systems for Building Services

Heavy - Flexi Quad Frames



These robust & versatile free standing modular frames are supplied with fully adjustable leg assemblies and 500 x 500mm polypropylene feet, which incorporates anti-vibration rubber mats adhered to the underside. Robust 50 x 50mm box end bars and cross bars both being 5mm thick in section, cater for picking up the point load mid span, resulting in even load dispersal through the framework down to the feet. The optional adjuster plate can also be purchased and these are supplied with fixings.



F-QUAD-500-A

Application: Suitable for heavier building services such as large air handling units, chillers and packaged plantrooms. Quads are particularly useful for managing heavy loads, and as a direct replacement for traditional concrete plinths, as they can be re-positioned to accommodate late design changes

| Item | Material |
|------------|--|
| FEET | Square - 500mm square UV stabilised - 90% polypropylene and 10% grp |
| MAT | 100% natural rubber, (mat is adhered to the feet) |
| LEGS | 48mm dia. 3mm stud steel tube with M24 stud adjuster and 4mm thick U clevis to top |
| END BARS | 50x50x5mm SHS (Square hollow section) |
| CROSS BARS | 50x50x5mm SHS (Square hollow section) with optional mounting plate if required |
| FINISH | Hot dip galvanised steelwork BS EN 10219-1:2006 Galvanising BS EN ISO 1461:2009. Salt Mist Testing: BS EN 60068-2-52:2018 |



Double Mounting Plate
Part Code - F-TQ-ADJ-D



Single Mounting Plate
Part Code - F-TQ-ADJ-S

| Code | Description | Length mm | Width mm | Height mm | Weight | Max Load |
|--------------|----------------------------------|-----------|----------|--------------------|--------|----------|
| F-QUAD-500 | Flexi QUAD (non-adjustable legs) | 1200mm | 500mm | 300mm | 60kg | 2000kg |
| F-QUAD-500-A | Flexi QUAD (adjustable legs) | 1200mm | 500mm | 240-370mm | 64kg | 2000kg |
| F-TQ-ADJ-S | Single Mounting Plate | 250mm | 150mm | - | 3kg | - |
| F-TQ-ADJ-D | Double Mounting Plate | 250mm | 150mm | 170mm (adjustable) | 8kg | - |

Heavy - Flexi Modular Frames

Modular robust frames for large air handling units.

These robust free standing modular frameworks are supplied with fully adjustable leg assemblies and 500 x 500mm polypropylene feet, incorporating anti-vibration rubber mats adhered to the underside. Robust 50 x 50mm square hollow section end bars are 2.5mm thick and are supplied with either 50 x 50mm, or 100 x 50mm cross bars. With a variety of sizes available for both our end bars and cross bars, a suitable framework can be designed to suit many applications where a strong support is key.

Application: Suitable for heavier building services such as large air handling units, chillers and air cooled condensers. Our unique 'drop on' cross bars offer a faster alternative when erecting the framework compared with some slide on systems.



| Item | Material |
|------------|---|
| FEET | Square - 500mm square UV stabilised - 90% polypropylene and 10% grp |
| MAT | 100% natural rubber, (mat is adhered to the feet) |
| LEGS | 48mm dia. 3mm stud steel tube with M24 stud adjuster and 4mm thick U clevis to top |
| END BARS | 50x50x2.5mm SHS (square hollow section) |
| CROSS BARS | 50x50x3mm SHS & 100x50x3mm (square/ rectangular hollow section) |
| FINISH | Hot dip galvanised steelwork BS EN 10219-1:2006 Galvanising BS EN ISO 1461:2009. Salt Mist Testing: BS EN 60068-2-52:2018 |



| Code | SHS Section | 1000mm | 1500mm | 2000mm | 2500mm | 3000mm | 3500mm |
|-----------|-------------|----------|----------|----------|----------|----------|----------|
| END BAR | 50x50x2.5 | PHF-005A | PHF-005B | PHF-005C | - | PHF-005D | - |
| CROSS BAR | 50x50x3.0 | - | PHF-015 | - | - | - | - |
| CROSS BAR | 100x50x3.2 | - | - | PHF016A | PHF-016B | PHF-016C | PHF-016D |



Easy-Fit



Frangs



Flexi



Install



Partners



PH Family



PH Motors



Portable



Service



Squeeze

Heavy - Flexi Custom Frames

Custom robust frameworks for the support of complex and heavy building services.

These custom solutions are frequently manufactured from 100 x 50mm parallel flange channel and/or 100x 100mm HEB (European Beam) and supported off fully adjustable leg assemblies utilising our larger 500 x 500mm polypropylene feet, incorporating anti-vibration rubber mats adhered to the underside. However larger steel sections are available dependant on project requirement and/or mass or size of the services being supported. All frameworks are hot dip galvanised. We will provide an AutoCAD drawing proposal together with load calculations prior to manufacture.



Application: Suitable for heavier chillers, packaged plantrooms, or complex shaped building services, typically air handling units. Steelwork comes with all necessary fixings and the correct amount of leg assemblies/feet. These are manufactured in the UK offering a very fast lead time.

| Item | Material |
|--------|---|
| FEET | Square - 500mm square UV stabilised - 90% polypropylene and 10% grp |
| MAT | 100% natural rubber, (mat is adhered to the feet) |
| LEGS | Custom manufactured to suit most heights and welded frames. Supplied with M24 adjuster stud for levelling |
| FRAME | Dependant on load/span |
| FINISH | Hot dip galvanised steelwork BS EN 10219-1:2006 Galvanising BS EN ISO 1461:2009. Salt Mist Testing: BS EN 60068-2-52:2018 |



| | AHU Requirements | Chiller Requirements | Packaged Plantroom Requirements |
|----------------------|-------------------------------|-------------------------------|---------------------------------|
| Information Required | 1 Sectional quantity | AVM quantity & point loads | Sectional quantity |
| | 2 Sectional dimensions | AVM dimensional locations | Sectional dimensions |
| | 3 Sectional weight | Total weight (operating mass) | Total weight (operating mass) |
| | 4 Overall dimensions & weight | Overall dimensions | Overall dimensions |

Access - Flexi Step-Overs & Hop-Overs



Safe access solutions designed and manufactured to current British Standards.

With the introduction of The Work at Height Regulations back in 2005, the regulations apply to all work at height where there is a risk of a fall liable to cause personal injury. This regulation places duty on employees, the self employed and any person that controls the work of others, e.g. facility managers, building owners/end users etc. Flexi access solutions are designed to current British Standards; we offer full working drawings, site surveys and all our access range is manufactured in the UK. GRP options are also available upon request. So whether it's a cat ladder, companion way ladder, stairs, ramps, walkways or a combination of all these, flexi access will provide you and your workforce with a safe access solution. We can also offer a custom design service to suit your needs.



Application: Step-Overs to bridge ducts, pipes and electrical containment; custom solutions to access maintenance doors to AHU's chillers or other rooftop services, ramped access solutions where wheel barrow / sack barrows are used and straight forward elevated access solutions. Cat ladders and companion way ladder also available.

| Item | Material |
|-------------------|--|
| FEET | Square - 320mm square UV stabilised - 100% polypropylene |
| MAT | 320mm feet only - 100% natural rubber. (mat is adhered to the feet) |
| LEGS | Step-Overs; 48mm dia. 3mm stud steel tube with M24 stud adjuster and 3mm thick U clevis to top |
| LEGS | Hop-Overs; 40x40x2mm SHS (Square hollow section) |
| HAND RAILS | 33.7mm diameter mild steel |
| TREADS / FLOORING | 25x3mm open grid flooring. (41/100 bearing bars) and designed to 7.5Kn/M² Loading BS4592 part 1 |
| FINISH | Hot dip galvanised steelwork BS EN 10219-1:2006 Galvanising BS EN ISO 1461:2009. Salt Mist Testing: BS EN 60068-2-52:2018 |



| Code | Description | Thread Qty | Landing Size mm | Clearance Height mm | Foot Size |
|-----------|-------------------------------|---------------|-----------------|---------------------|---------------|
| F-SO-2 | Flexi Step Over 2 up / 2 down | 2 up / 2 down | 1000mm x 1000mm | 560mm | 320mm x 320mm |
| F-SO-3 | Flexi Step Over 3 up / 3 down | 3 up / 3 down | 1000mm x 1000mm | 780mm | 320mm x 320mm |
| F-SO-4 | Flexi Step Over 4 up / 4 down | 4 up / 4 down | 1000mm x 1000mm | 1000mm | 320mm x 320mm |
| F-HO-600 | Flexi Hop Over - 600mm | - | 1000mm x 600mm | 180mm | 320mm x 320mm |
| F-HO-1000 | Flexi Hop Over - 1000mm | - | 1000mm x 1000mm | 180mm | 320mm x 320mm |
| F-HO-HR | Flexi Hand Rail for Hop Over | - | - | - | - |



Easy-Fit



Flange



Flexi



Install



Partworks



PH Family



PH Motors



Portable



Service



Safety

Access - Flexi Custom Platforms & Walkways



A tailored solution to fit around existing rooftop building services.

Flexi custom platforms and walkways are designed to provide solutions for maintenance and fire exit access. We can visit sites and carry out a thorough survey from which we generate AutoCAD drawings. These will be forwarded for approval to the project team prior to manufacture. They are manufactured from mild steel with a hot dip galvanised finish. Alternatively we can offer aluminium or GRP solutions upon request. Designed to comply with British Standards, these versatile and easy to assemble solutions are supplied with M24 adjustable legs, (to cater for the roof fall), and supported by our 320mm square feet



Application: Generally positioned on flat roofs providing access to rooftop building services and fire exit access solutions.

| Item | Material |
|-------------------|---|
| FEET | Square - 320mm square UV stabilised - 100% polypropylene |
| MAT | 320mm feet only - 100% natural rubber, (mat is adhered to the feet) |
| LEGS | Step-Overs; 48mm dia. 3mm stud steel tube with M24 stud adjuster and 3mm thick U clevis to top. |
| LEGS | Hop-Overs; 40x40x2mm SHS (Square hollow section) |
| HAND RAILS | 33.7mm diameter. Kee Klamp (or similar) c/w interchangeable fittings |
| TREADS / FLOORING | 25x3mm open grid flooring. (41/100 bearing bars) and designed to 7.5Kn/M ² Loading BS4592 part 1 |
| FINISH | Hot dip galvanised steelwork BS EN 10219-1:2006 Galvanising BS EN ISO 1461:2009. Salt Mist Testing BS EN 60068-2-52:2018 |



Pump House supply access solutions that utilise stairs, companion way ladders or cat ladders, or a combination of all of these. Ramped access solutions are also available upon request. Manufactured to current British Standards, Pump House supply the solutions flat packed with all necessary fixings for quick assembly on site by others. We offer an efficient manufacturing and galvanising process and can supply goods to site usually within 10-15 working days.

Fixings



Slotted Channel & Accessories

Slotted Channel

| Code 3 Metres | Code 6 metres | Description |
|------------------|------------------|---------------------------------------|
| X-CH4121-1.5-3M | X-CH4121-1.5-6M | Slotted Channel – 41mm x 21mm x 1.5mm |
| X-CH4121-2.5-3M | X-CH4121-2.5-6M | Slotted Channel – 41mm x 21mm x 2.5mm |
| X-CH4141-1.5-3M | X-CH4141-1.5-6M | Slotted Channel – 41mm x 41mm x 1.5mm |
| X-CH4141-2.5-3M | X-CH4141-2.5-6M | Slotted Channel – 41mm x 41mm x 2.5mm |
| X-CH4182-2.5-3M | X-CH4182-2.5-6M | Slotted Channel – 41mm x 82mm x 2.5mm |



X-CH4121-1.5

Beam G Clamp

| Code M6 | Code M8 | Code M10 | Code M12 | Description |
|------------|------------|-------------|-------------|--------------|
| X-BGC-M6 | X-BGC-M8 | X-BGC-M10 | X-BGC-M12 | Beam G Clamp |



X-BGC-M8

Channel Clamp

| Code Type 1 | Code Type 2 | Code Type 3 | Code Type 4 | Code Type 5 | Code Type 6 | Code Type 8 | Description |
|----------------|----------------|----------------|----------------|----------------|----------------|----------------|---------------|
| X-CBC-1 | X-CBC-2 | X-CBC-3 | X-CBC-4 | X-CBC-5 | X-CBC-6 | X-CBC-8 | Channel Clamp |



Type 1



Type 2



Type 3



Type 4



Type 5



Type 6



Type 8

Others

| Code | Description |
|---------------|--|
| X-BP810 | Back Plate – M8 / M10 |
| X-CB90-1H1H | 90 Degree Bracket – 1 Hole / 1 Hole |
| X-CB90-1H2H | 90 Degree Bracket – 1 Hole / 2 Hole |
| X-CB90-2H2H | 90 Degree Bracket – 2 Hole / 2 Hole |
| X-CH-4-IS | Channel 4 Way Intersection |
| X-CH-A | Channel Offset – 45 Degree |
| X-CHBC-3M | Channel Back Capping – 3 metres |
| X-CHBP1W-4141 | Channel Base Plate – One Way – 41mm x 41mm |
| X-CHBP2W-4141 | Channel Base Plate – Two Way – 41mm x 41mm |
| X-CH-1A-45 | Channel Internal Angle – 45 Degree |
| X-CH-1A-45135 | Channel Internal Angle – 45 Degree 135 |



X-CH-1A-45



X-CHBP2W-4141

Channel Wing Fitting

| Code Type 1 | Code Type 2 | Code Type 3 | Code Type 4 | Description |
|----------------|----------------|----------------|----------------|----------------------|
| X-CHWF-1 | X-CHWF-2 | X-CHWF-3 | X-CHWF-4 | Channel Wing Fitting |



Type 1



Type 2



Type 3



Type 4

Channel U Brackets

| Code | Description |
|------------|---------------------------------|
| X-CBU-4121 | Channel U Bracket – 41mm x 21mm |
| X-CBU-4141 | Channel U Bracket – 41mm x 41mm |
| X-CBU-4162 | Channel U Bracket – 41mm x 62mm |



X-CBU-4121

Channel Z Brackets

| Code | Description |
|-------------|---------------------------------|
| X-CHZB-4121 | Channel Z Bracket – 41mm x 21mm |
| X-CHZB-4141 | Channel Z Bracket – 41mm x 41mm |



X-CHZ-2121

Window Brackets

| Code | Description |
|------------|------------------------------|
| X-CWB-4121 | Window Bracket – 41mm x 21mm |
| X-CWB-4141 | Window Bracket – 41mm x 41mm |
| X-CWB-4182 | Window Bracket – 41mm x 82mm |



X-CWB-4121

Flat Plates

| Code | Code | Code | Code | Description |
|--------|--------|--------|--------|-------------|
| 2 Hole | 3 Hole | 4 Hole | 5 Hole | |
| X-FP2H | X-FP3H | X-FP4H | X-FP5H | Flat Plate |



X-FP4H

Other Plates

| Code | Description |
|------------|---------------------------------|
| X-FP3H-90 | Flat Plate – 3 Hole – 90 Degree |
| X-TBR4H | T Bracket – 4 Hole |
| X-TBR4H-90 | T Bracket – 4 Hole – 90 Degree |



X-TBR4H

Purling Clips

| Code | Description | Quantity |
|----------|------------------------------|-------------|
| X-PC | Purling Clip Z10 Beam Clamp | Pack of 100 |
| X-PC-M10 | Purling Clip – Pull On – M10 | Pack of 100 |
| X-PC-M8 | Purling Clip – Pull On – M8 | Pack of 100 |



X-PC



X-PC-M8

Channel 4 Hole Internal/External Connectors

| Code | Description |
|--------------|---|
| X-CEC4H-4121 | Channel 4 Hole – External Connector – 41mm x 21mm |
| X-CEC4H-4141 | Channel 4 Hole – External Connector – 41mm x 41mm |
| X-CIC4H-4121 | Channel 4 Hole – Internal Connector – 41mm x 21mm |
| X-CIC4H-4141 | Channel 4 Hole – Internal Connector – 41mm x 41mm |



X-CEC4H-4121



X-CIC4H-4121



Easy-Fit



Pivots



Pins



Install -



Partners



PH Screws



PH Motors



Pumps



Service +



Repairs

Channel Accessories / Cable Tray

Plastic End Caps

| Code Black | Code White | Description | Quantity |
|---------------|---------------|--------------------------------|------------|
| X-CHCB-4121 | X-CHCW-4121 | Plastic End Caps – 41mm x 21mm | Box of 100 |
| X-CHCB-4141 | X-CHCW-4141 | Plastic End Caps – 41mm x 41mm | Box of 100 |
| X-CHCB-4121B6 | X-CHCW-4121B6 | Plastic End Caps – 41mm x 21mm | Bag of 6 |
| X-CHCB-4141B6 | X-CHCW-4141B6 | Plastic End Caps – 41mm x 41mm | Bag of 6 |



X-CHCW-4121
X-CHCB-4121

Threaded Rod

| Code M6 | Code M8 | Code M10 | Code M12 | Description |
|------------|------------|-------------|-------------|-------------------------------|
| X-TR-M6-3M | X-TR-M8-3M | X-TR-M10-3M | X-TR-M12-3M | Threaded Rod – 3 metre length |



X-TR-M8-3M

Studding Caps

| Code M6 | Code M8 | Code M10 | Code M12 | Description | Quantity |
|--------------|--------------|---------------|---------------|---------------|------------|
| X-SCA-M6 | X-SCA-M8 | X-SCA-M10 | X-SCA-M12 | Studding Caps | Box of 100 |
| X-SCA-M6-B30 | X-SCA-M8-B30 | X-SCA-M10-B30 | X-SCA-M12-B30 | Studding Caps | Bag of 30 |



X-SCA-M8

Cable Tray

| Code | Description |
|------------------|---|
| X-CTMD-PG-50-3M | Cable Tray – Medium Duty Pre Galv. – 50mm x 3 metres |
| X-CTMD-PG-75-3M | Cable Tray – Medium Duty Pre Galv. – 75mm x 3 metres |
| X-CTMD-PG-100-3M | Cable Tray – Medium Duty Pre Galv. – 100mm x 3 metres |
| X-CTMD-PG-150-3M | Cable Tray – Medium Duty Pre Galv. – 150mm x 3 metres |
| X-CTMD-PG-225-3M | Cable Tray – Medium Duty Pre Galv. – 225mm x 3 metres |
| X-CTMD-PG-300-3M | Cable Tray – Medium Duty Pre Galv. – 300mm x 3 metres |
| X-CTMD-PG-450-3M | Cable Tray – Medium Duty Pre Galv. – 450mm x 3 metres |
| X-CTMD-PG-600-3M | Cable Tray – Medium Duty Pre Galv. – 600mm x 3 metres |



Cable Tray Flat Bends

| Code 90 Degree | Code 45 Degree | Description |
|-------------------|-------------------|------------------------------|
| X-CTMD-B-50 | X-CTMD-FB-50 | Cable Tray Flat Bend – 50mm |
| X-CTMD-B-75 | X-CTMD-FB-75 | Cable Tray Flat Bend – 75mm |
| X-CTMD-B-100 | X-CTMD-FB-100 | Cable Tray Flat Bend – 100mm |
| X-CTMD-B-150 | X-CTMD-FB-150 | Cable Tray Flat Bend – 150mm |
| X-CTMD-B-225 | X-CTMD-FB-225 | Cable Tray Flat Bend – 225mm |
| X-CTMD-B-300 | X-CTMD-FB-300 | Cable Tray Flat Bend – 300mm |
| X-CTMD-B-450 | X-CTMD-FB-450 | Cable Tray Flat Bend – 450mm |



X-CTMD-FB-150

Cable Tray Tees

| Code | Description |
|---------------|------------------------|
| X-CTMD-TP-75 | Cable Tray Tee – 75mm |
| X-CTMD-TP-100 | Cable Tray Tee – 100mm |
| X-CTMD-TP-150 | Cable Tray Tee – 150mm |
| X-CTMD-TP-225 | Cable Tray Tee – 225mm |
| X-CTMD-TP-300 | Cable Tray Tee – 300mm |
| X-CTMD-TP-450 | Cable Tray Tee – 450mm |



X-CTMD-TP-150

Other cable tray accessories are available upon request and come in light, heavy and hot dipped galvanised versions

Cable Tray Intersection

| Code | Description |
|---------------|---------------------------------|
| X-CTMD-IS-75 | Cable Tray Intersection – 75mm |
| X-CTMD-IS-100 | Cable Tray Intersection – 100mm |
| X-CTMD-IS-150 | Cable Tray Intersection – 150mm |
| X-CTMD-IS-225 | Cable Tray Intersection – 225mm |
| X-CTMD-IS-300 | Cable Tray Intersection – 300mm |
| X-CTMD-IS-450 | Cable Tray Intersection – 450mm |

medium and heavy duty versions available



X-CTMD-IS-300

Cable Tray Reducer

| Code | Description |
|-----------------|------------------------------------|
| X-CTMD-R-150100 | Cable Tray Reducer – 150mm x 100mm |
| X-CTMD-R-225150 | Cable Tray Reducer – 225mm x 150mm |
| X-CTMD-R-300150 | Cable Tray Reducer – 300mm x 150mm |
| X-CTMD-R-300225 | Cable Tray Reducer – 300mm x 225mm |
| X-CTMD-R-450300 | Cable Tray Reducer – 450mm x 300mm |
| X-CTMD-R-600450 | Cable Tray Reducer – 600mm x 450mm |

medium and heavy duty versions available



X-CTMD-R-300225

Cable Tray Hanger

| Code | Description |
|--------------|---------------------------------------|
| X-CTH-PG-50 | Cable Tray Hanger – Pre-Galv. – 50mm |
| X-CTH-PG-75 | Cable Tray Hanger – Pre-Galv. – 75mm |
| X-CTH-PG-100 | Cable Tray Hanger – Pre-Galv. – 100mm |
| X-CTH-PG-150 | Cable Tray Hanger – Pre-Galv. – 150mm |
| X-CTH-PG-225 | Cable Tray Hanger – Pre-Galv. – 225mm |
| X-CTH-PG-300 | Cable Tray Hanger – Pre-Galv. – 300mm |



X-CTH-PG-100

Cable Tray Stand Off Bracket

| Code | Description |
|----------------|--|
| X-CTMD-SOB-75 | Cable Tray Stand Off Bracket – Medium Duty – 75mm |
| X-CTMD-SOB-100 | Cable Tray Stand Off Bracket – Medium Duty – 100mm |
| X-CTMD-SOB-150 | Cable Tray Stand Off Bracket – Medium Duty – 150mm |
| X-CTMD-SOB-225 | Cable Tray Stand Off Bracket – Medium Duty – 225mm |
| X-CTMD-SOB-300 | Cable Tray Stand Off Bracket – Medium Duty – 300mm |
| X-CTMD-SOB-450 | Cable Tray Stand Off Bracket – Medium Duty – 450mm |

hot dipped galvanised versions available



X-CTMD-SOB-150

Cable Tray Accessories

| Code | Description |
|------------|----------------------------------|
| X-CTCHD-PG | Cable Tray Coupler – Medium Duty |



X-CTCHD-PG



Easy-Fit



Fixings



Fins



Install L



Partners



PHT Family



PHT Medium



Protection



Service L



Support

Basket Tray & Accessories

Basket Tray

| Code | Description |
|----------|---------------------------------|
| X-BT-60 | Basket Tray – 60mm x 60mm x 3m |
| X-BT-100 | Basket Tray – 100mm x 60mm x 3m |
| X-BT-150 | Basket Tray – 150mm x 60mm x 3m |
| X-BT-200 | Basket Tray – 200mm x 60mm x 3m |
| X-BT-300 | Basket Tray – 300mm x 60mm x 3m |
| X-BT-400 | Basket Tray – 400mm x 60mm x 3m |
| X-BT-450 | Basket Tray – 450mm x 60mm x 3m |
| X-BT-500 | Basket Tray – 500mm x 60mm x 3m |
| X-BT-600 | Basket Tray – 600mm x 60mm x 3m |



X-BT-100

Basket Tray Quik Connect

| Code | Description |
|-----------|--|
| X-BTM-100 | Basket Tray Quik Connect – 100mm x 60mm x 3m |
| X-BTM-150 | Basket Tray Quik Connect – 150mm x 60mm x 3m |
| X-BTM-200 | Basket Tray Quik Connect – 200mm x 60mm x 3m |
| X-BTM-300 | Basket Tray Quik Connect – 300mm x 60mm x 3m |



X-BTM-100

Basket Tray Wall Support Bracket

| Code | Description |
|------------|--|
| X-BTWB-150 | Basket Tray Wall Support Bracket – 150mm |
| X-BTWB-200 | Basket Tray Wall Support Bracket – 200mm |
| X-BTWB-300 | Basket Tray Wall Support Bracket – 300mm |
| X-BTWB-400 | Basket Tray Wall Support Bracket – 400mm |



X-BTWB-150

Basket Tray Ceiling Bracket

| Code | Description |
|------------|-------------------------------------|
| X-BTCB-150 | Basket Tray Ceiling Bracket – 150mm |
| X-BTCB-200 | Basket Tray Ceiling Bracket – 200mm |
| X-BTCB-300 | Basket Tray Ceiling Bracket – 300mm |



X-BTCB-150

Basket Tray Accessories


| Code | Description |
|----------|--|
| X-BTC | Basket Tray Couplers – Pair |
| X-BT-CH | Basket Tray Central Support Hangers - Pair |
| X-BT-HDC | Basket Tray Hold Down Clamp |
| X-BT-J | Basket Tray Jointing Kit – 4 Part Kit |
| X-BT-SH | Basket Tray Suspension Hanger |
| X-BT-PC | Basket Clamping Piece – Pack of 50 |
| X-BT-FC | Basket Corner Connector – Pack of 50 |



X-BTC



X-BT-CH



X-BT-SH

Penny Washers

| Code M6 | Code M8 | Code M10 | Code M12 | Description | Quantity |
|---------------|---------------|----------------|----------------|-------------------|------------|
| X-WA6-25-B25 | X-WA8-25-B25 | X-WA10-25-B25 | X-WA12-25-B25 | Penny Washer 25mm | Bag of 25 |
| X-WA6-25-B100 | X-WA8-25-B100 | X-WA10-25-B100 | X-WA12-25-B100 | Penny Washer 25mm | Box of 100 |
| X-WA6-30-B100 | X-WA8-30-B100 | X-WA10-30-B100 | X-WA12-30-B100 | Penny Washer 30mm | Box of 100 |
| X-WA6-40-B100 | X-WA8-40-B100 | X-WA10-40-B100 | X-WA12-40-B100 | Penny Washer 40mm | Box of 100 |

X-WA8-30



Flat / Form A Washer

| Code M6 | Code M8 | Code M10 | Code M12 | Description | Quantity |
|--------------|--------------|---------------|---------------|--------------------|------------|
| X-WA-M6-B100 | X-WA-M8-B100 | X-WA-M10-B100 | X-WA-M12-B100 | Flat/Form A Washer | Box of 100 |

X-WA-M8



Shake Proof Washers

| Code M6 | Code M8 | Code M10 | Code M12 | Description | Quantity |
|---------------|---------------|----------------|----------------|--------------------|------------|
| X-SPW-M6-B100 | X-SPW-M8-B100 | X-SPW-M10-B100 | X-SPW-M12-B100 | Shake Proof Washer | Box of 100 |

X-SPW-M8



Square Plate Washers

| Code M6 | Code M8 | Code M10 | Code M12 | Description | Quantity |
|----------------|----------------|-----------------|-----------------|---------------------|------------|
| X-SQPW-M6-B6 | X-SQPW-M8-B6 | X-SQPW-M10-B6 | X-SQPW-M12-B6 | Square Plate Washer | Bag of 6 |
| X-SQPW-M6-B100 | X-SQPW-M8-B100 | X-SQPW-M10-B100 | X-SQPW-M12-B100 | Square Plate Washer | Box of 100 |

X-SQPW-M8



Don't lose your cool!



Stay in control with our Portable AC Units!

- Meets EN14511 standard and EU commission regulation 206/2012
- Proven well-tested designs
- LED display and remote control (both models)
- Flexible exhaust hose – 1.5m (both models)
- Energy efficient rating A
- Suitable for areas up to 25m²
- No pump required – self-evaporating condensate
- R410A Refrigerant



Easy-Fit



Fixings



Filter



Install



Partners



PH Family



PH Motors



Portable



Service



Squeaky

Nuts

X-CNLS-M8



X-CNLS-M8-B6



X-CN-M8



X-HN-M8



X-WN-M8



X-RBN-M6-16



Long Spring Channel Nut

| Code M6 | Code M8 | Code M10 | Code M12 | Description | Quantity |
|----------------|----------------|-----------------|-----------------|-------------------------|------------|
| X-CNLS-M6-B6 | X-CNLS-M8-B6 | X-CNLS-M10-B6 | X-CNLS-M12-B6 | Long Spring Channel Nut | Bag of 6 |
| X-CNLS-M6-B100 | X-CNLS-M8-B100 | X-CNLS-M10-B100 | X-CNLS-M12-B100 | Long Spring Channel Nut | Box of 100 |

Short Spring Channel Nut

| Code M6 | Code M8 | Code M10 | Code M12 | Description | Quantity |
|----------------|----------------|-----------------|-----------------|--------------------------|------------|
| X-CNSS-M6-B6 | X-CNSS-M8-B6 | X-CNSS-M10-B6 | X-CNSS-M12-B6 | Short Spring Channel Nut | Bag of 6 |
| X-CNSS-M6-B100 | X-CNSS-M8-B100 | X-CNSS-M10-B100 | X-CNSS-M12-B100 | Short Spring Channel Nut | Box of 100 |

Plain Channel Nut

| Code M6 | Code M8 | Code M10 | Code M12 | Description | Quantity |
|--------------|--------------|---------------|---------------|-------------------|------------|
| X-CN-M6-B8 | X-CN-M8-B8 | X-CN-M10-B8 | X-CN-M12-B8 | Plain Channel Nut | Bag of 8 |
| X-CN-M6-B100 | X-CN-M8-B100 | X-CN-M10-B100 | X-CN-M12-B100 | Plain Channel Nut | Box of 100 |

Hexagonal Nuts & Cover

| Code M6 | Code M8 | Code M10 | Code M12 | Description | Quantity |
|--------------|--------------|---------------|---------------|---------------------|------------|
| X-HN-M6-B25 | X-HN-M8-B25 | X-HN-M10-B25 | X-HN-M12-B25 | Hexagonal Nut | Bag of 25 |
| X-HN-M6-B100 | X-HN-M8-B100 | X-HN-M10-B100 | X-HN-M12-B100 | Hexagonal Nut | Box of 100 |
| | X-HNC-M8-B10 | X-HNC-M10-B10 | | Hexagonal Nut Cover | Bag of 10 |

Wedge Nut

| Code M6 | Code M8 | Code M10 | Code M12 | Description | Quantity |
|--------------|--------------|---------------|---------------|-------------|------------|
| X-WN-M6-B100 | X-WN-M8-B100 | X-WN-M10-B100 | X-WN-M12-B100 | Wedge Nut | Box of 100 |

Roofing Bolt & Nut

| Code M6 - 12mm | Code M6 - 16mm | Code M6 - 20mm | Description | Quantity |
|------------------|------------------|------------------|--------------------|------------|
| X-RBN-M6-12-B20 | X-RBN-M6-16-B20 | X-RBN-M6-20-B20 | Roofing Nut & Bolt | Bag of 20 |
| X-RBN-M6-12-B100 | X-RBN-M6-16-B100 | X-RBN-M6-20-B100 | Roofing Nut & Bolt | Box of 100 |

Hex Sets

| Code M6 | Code M8 | Code M10 | Code M12 | Description | Quantity |
|---------------|---------------|----------------|----------------|--------------|------------|
| | | | X-SS12-25-B10 | Hex Set 25mm | Bag of 10 |
| | | | X-SS12-25-B100 | Hex Set 25mm | Box of 100 |
| X-SS6-30-B10 | X-SS8-30-B10 | X-SS10-30-B10 | X-SS12-30-B10 | Hex Set 30mm | Bag of 10 |
| X-SS6-30-B100 | X-SS8-30-B100 | X-SS10-30-B100 | X-SS12-30-B100 | Hex Set 30mm | Box of 100 |
| | | X-SS10-35-B10 | | Hex Set 35mm | Bag of 10 |
| | | X-SS10-35-B100 | | Hex Set 35mm | Box of 100 |
| | X-SS8-40-B10 | | X-SS12-40-B10 | Hex Set 40mm | Bag of 10 |
| | X-SS8-40-B100 | X-SS10-40-B100 | X-SS12-40-B100 | Hex Set 40mm | Box of 100 |
| | X-SS8-50-B10 | X-SS10-50-B10 | | Hex Set 50mm | Bag of 10 |
| | X-SS8-50-B100 | X-SS10-50-B100 | | Hex Set 50mm | Box of 100 |

X-SS8-30



Coach Screws

| Code M8 | Code M10 | Description | Quantity |
|----------------|-----------------|------------------|------------|
| X-CS-M830-B5 | X-CS-M1030-B5 | Coach Screw 30mm | Bag of 5 |
| X-CS-M830-B100 | X-CS-M1030-B100 | Coach Screw 30mm | Box of 100 |
| X-CS-M850-B5 | X-CS-M1050-B5 | Coach Screw 50mm | Bag of 5 |
| X-CS-M850-B100 | X-CS-M1050-B100 | Coach Screw 50mm | Box of 100 |

X-CS-M1050



Twin Fast Screws

| Code 1" | Code 1-1/2" | Code 2" | Code 2-1/2" | Description | Quantity |
|------------|----------------|------------|----------------|-------------------------|------------|
| X-TF8-1 | X-TF81-1/2 | X-TF8-2 | | Twin Fast Screw Size 8 | Box of 200 |
| X-TF10-1 | X-TF10-1-1/2 | X-TF10-2 | X-TF10-2-1/2 | Twin Fast Screw Size 10 | Box of 200 |

X-TF8-1-1/2



TEK Screws

| Code | Description | Quantity |
|------------------|------------------------------|------------|
| X-TEK5.5-25-B100 | TEK Screw 5.5 x 25mm | Box of 100 |
| X-TEK5.5-38-B100 | TEK Screw 5.5 x 38mm | Box of 100 |
| X-TEK-MAGBIT | 5/16 Magnetic Socket Adaptor | |

X-TEK5.5-25



Plaster Board Screw

| Code | Description | Quantity |
|-------|--------------------------|------------|
| X-PBS | Plaster Board Screw 15mm | Box of 100 |

X-PBS



Stud Connectors

| Code M8 | Code M10 | Description | Quantity |
|----------------|-----------------|----------------|------------|
| X-SCON-M8-B4 | X-SCON-M10-B4 | Stud Connector | Bag of 4 |
| X-SCON-M8-B100 | X-SCON-M10-B100 | Stud Connector | Box of 100 |

X-SCON-M10



Wall Plugs

| Code | Description | Quantity |
|--------------|-------------------------|------------|
| X-WPR-5MM | Wall Plug 5mm - Red | Box of 100 |
| X-WPB-7MM | Wall Plug 7mm - Brown | Box of 100 |
| X-WPG-8/10MM | Wall Plug 8/10mm - Grey | Box of 25 |

X-WPR-5MM

X-WPB-7MM



Easy-Fit



Fixings



Fills



Install



Partners



P11 Family



P11 Motors



Protection



Services



Support

Bolts

Anchor Bolts

| Code | Description | Quantity |
|------------------|------------------------|------------|
| X-AB-8/10-100-B4 | Anchor Bolt 8mm 10-100 | Bag of 4 |
| X-AB-M10-B100 | Anchor Bolt 8mm 10-100 | Box of 100 |
| X-AB-M10-60-B4 | Anchor Bolt 8mm 10-60 | Bag of 4 |
| X-AB-M10-60-B100 | Anchor Bolt 8mm 10-60 | Box of 100 |

X-AB-8/10



Loose Bolt Shield Anchor

| Code | Description | Quantity |
|--------------|----------------------------------|-----------|
| X-LBSA-0810L | Loose Bolt Shield Anchor - 0810L | Box of 50 |
| X-LBSA-1010L | Loose Bolt Shield Anchor - 1010L | Box of 50 |
| X-LBSA-1025L | Loose Bolt Shield Anchor - 1025L | Box of 50 |

X-LBSA-0810L



Eye Bolt

| Code | Description | Quantity |
|--------------|-----------------------|-----------|
| X-EB-M8-B25 | Eye Bolt - M8 x 80mm | Box of 25 |
| X-EB-M10-B10 | Eye Bolt - M10 x 80mm | Box of 10 |

X-EB-M8



Socket Bolts

| Code | Description | Quantity |
|----------------|------------------------------------|------------|
| X-SB810-B4 | Socket Bolt M8-M10 | Bag of 4 |
| X-SB810-B100 | Socket Bolt M8-M10 | Box of 100 |
| X-SBL2810-B100 | Socket Bolt Loose M8-M10 (2 Piece) | Box of 100 |
| X-SBL810-B4 | Socket Bolt Loose M8-M10 (3 Piece) | Bag of 4 |
| X-SBL810-B100 | Socket Bolt Loose M8-M10 (3 Piece) | Box of 100 |

X-SB810



Drop In Anchor



X-DIA-M10



X-DIAL-M10 (Lipped)

| Code M8 | Code M10 | Code M12 | Description | Quantity |
|----------------|----------------|----------------|-----------------------------|-----------------------------------|
| X-DIA-M8-B10 | X-DIA-M10-B10 | X-DIA-M12-B10 | Drop In Anchor | Bag of 10 |
| X-DIA-M8-B100 | X-DIA-M10-B50 | X-DIA-M12-B50 | Drop In Anchor | M8 Box of 100 - M10/M12 Box of 50 |
| X-DIAL-M8-B100 | X-DIAL-M10-B50 | X-DIAL-M12-B50 | Drop In Anchor Lipped | M8 Box of 100 - M10/M12 Box of 50 |
| X-DIA-ST | | | Drop In Anchor Setting Tool | Singles |

Unlined M8-M10 Pipe Clamps



| Code | Description | Quantity |
|---------------|--------------------------------|------------|
| X-PCU-15-18 | Pipe Clamp Unlined - 15-18mm | Pack of 50 |
| X-PCU-20-25 | Pipe Clamp Unlined - 20-25mm | Pack of 50 |
| X-PCU-26-30 | Pipe Clamp Unlined - 26-30mm | Pack of 50 |
| X-PCU-32-36 | Pipe Clamp Unlined - 32-36mm | Pack of 50 |
| X-PCU-38-43 | Pipe Clamp Unlined - 38-43mm | Pack of 50 |
| X-PCU-44-49 | Pipe Clamp Unlined - 44-49mm | Pack of 50 |
| X-PCU-56-61 | Pipe Clamp Unlined - 56-61mm | Pack of 50 |
| X-PCU-75-80 | Pipe Clamp Unlined - 75-80mm | Pack of 50 |
| X-PCU-87-92 | Pipe Clamp Unlined - 87-92mm | Pack of 50 |
| X-PCU-108-116 | Pipe Clamp Unlined - 108-116mm | Pack of 25 |

Lined M8-M10 Pipe Clamps



| Code | Description | Quantity |
|---------------|------------------------------|------------|
| X-PCL-12-14 | Pipe Clamp Lined - 12-14mm | Pack of 50 |
| X-PCL-15-19 | Pipe Clamp Lined - 15-19mm | Pack of 50 |
| X-PCL-20-25 | Pipe Clamp Lined - 20-25mm | Pack of 50 |
| X-PCL-26-30 | Pipe Clamp Lined - 26-30mm | Pack of 50 |
| X-PCL-32-36 | Pipe Clamp Lined - 32-36mm | Pack of 50 |
| X-PCL-38-43 | Pipe Clamp Lined - 38-43mm | Pack of 50 |
| X-PCL-44-49 | Pipe Clamp Lined - 44-49mm | Pack of 50 |
| X-PCL-50-55 | Pipe Clamp Lined - 50-55mm | Pack of 50 |
| X-PCL-56-61 | Pipe Clamp Lined - 56-61mm | Pack of 50 |
| X-PCL-62-67 | Pipe Clamp Lined - 62-67mm | Pack of 50 |
| X-PCL-68-73 | Pipe Clamp Lined - 68-73mm | Pack of 50 |
| X-PCL-75-80 | Pipe Clamp Lined - 75-80mm | Pack of 50 |
| X-PCL-82-86 | Pipe Clamp Lined - 82-86mm | Pack of 50 |
| X-PCL-87-92 | Pipe Clamp Lined - 87-92mm | Pack of 50 |
| X-PCL-95-102 | Pipe Clamp Lined - 95-102mm | Pack of 50 |
| X-PCL-108-116 | Pipe Clamp Lined - 108-116mm | Pack of 25 |
| X-PCL-121-127 | Pipe Clamp Lined - 121-127mm | Pack of 25 |
| X-PCL-131-141 | Pipe Clamp Lined - 131-141mm | Pack of 25 |
| X-PCL-159-163 | Pipe Clamp Lined - 159-163mm | Pack of 25 |
| X-PCL-165-168 | Pipe Clamp Lined - 165-168mm | Pack of 25 |
| X-PCL-192-202 | Pipe Clamp Lined - 192-202mm | Pack of 25 |
| X-PCL-210-220 | Pipe Clamp Lined - 210-220mm | Pack of 25 |



Easy-Fit



Fixings



Flare



Install



Partners



P11 Family



P11 Medium



Protection



Service



Support

Switches / Isolators & Stuffing Glands

Fused Spur Switches

| Code | Description |
|--------------|--|
| X-FSBBMC | Fused Spur Metal Clad – with Back Box |
| X-FSNBBMC | Fused Spur Metal Clad – with Back Box & Neon |
| X-FS | Fused Spur Plastic – without neon |
| X-FSN | Fused Spur Plastic – with neon |
| X-BBSM-25 | Back Box Surface Mount – 25mm |
| X-BBSM-35 | Back Box Surface Mount – 35mm |
| X-BBSM26-25 | Back Box 2 Gang – 25mm |
| X-BBSM2G-35 | Back Box 2 Gang – 35mm |
| X-BSPS-10A | Plug Socket – 10 Amp |
| X-2GSW2W-10A | Switch 2 Gang – 10 Amp |
| X-3GSW2W-10A | Switch 3 Gang – 10 Amp |
| X-1GDPW-13A | Switch 1 Gang – 13 Amp |
| X-2GDPW-13A | Switch 2 Gang – 13 Amp |
| X-DPSW-20A | Switch Double Pole – 20 Amp |
| X-PT | Plug Top – 13 Amp |

Fused Spur Metal



Fused Spur Plastic



Rotary Enclosed Isolators

Our insulated 3 and 4 pole rotary enclosed isolators are CE marked and suitable for disconnecting the power supply to outdoor air conditioning units.

The isolators are weatherproof to IP65, easy to install, conform to IEC 60947-3. They have a lockable off position and interlockable cover which can be removed only in the off position. Earth and neutral terminals included and M20/25 knockouts up to 63A.

Rotary Enclosed Isolators



| Code | No. of poles | Amps AC21 | AC23A 240VA | AC23A 400VA | Cable Capacity Solid | Cable Capacity Stranded | Height | Width | Depth |
|-------------|--------------|-----------|-------------|-------------|----------------------|-------------------------|--------|-------|-------|
| IS-3P-20A | 3 | 20 Amp | 5.5 kW | 3.7 kW | 1-16mm ² | 0.75-10mm ² | 175mm | 114mm | 135mm |
| IS-3P-32A | 3 | 32 Amp | 11 kW | 7.5 kW | 1-16mm ² | 0.75-10mm ² | 175mm | 114mm | 135mm |
| IS-3P-40A | 3 | 40 Amp | 15 kW | 11 kW | 1-16mm ² | 0.75-10mm ² | 175mm | 114mm | 135mm |
| IS-3P-63A | 3 | 63 Amp | 22 kW | 18.5 kW | 1-16mm ² | 0.75-10mm ² | 175mm | 114mm | 135mm |
| IS-4P-20A-S | 4 | 20 Amp | 5.5 kW | 3.7 kW | 1-16mm ² | 0.75-10mm ² | 125mm | 100mm | 120mm |
| IS-4P-20A | 4 | 20 Amp | 5.5 kW | 3.7 kW | 1-16mm ² | 0.75-10mm ² | 175mm | 114mm | 125mm |
| IS-4P-32A-S | 4 | 32 Amp | 11 kW | 7.5 kW | 1-16mm ² | 0.75-10mm ² | 125mm | 100mm | 120mm |
| IS-4P-32A | 4 | 32 Amp | 11 kW | 7.5 kW | 1-16mm ² | 0.75-10mm ² | 175mm | 114mm | 135mm |
| IS-4P-40A | 4 | 40 Amp | 15 kW | 11 kW | 1-16mm ² | 0.75-10mm ² | 175mm | 114mm | 125mm |
| IS-4P-63A | 4 | 63 Amp | 22 kW | 18.5 kW | 1-16mm ² | 0.75-10mm ² | 175mm | 114mm | 135mm |

Stuffing Glands

| Code Black | Code White | Description | Quantity |
|---------------|---------------|-----------------------------|------------|
| X-CSG-20B-B10 | X-CSG-20W-B10 | Cable Stuffing Gland – 20mm | Pack of 10 |
| X-CSG-25B-B10 | X-CSG-25W-B10 | Cable Stuffing Gland – 25mm | Pack of 10 |



Stuffing Gland White



Stuffing Gland Black

Cable

| CY | | WF | | YY | SY |
|---|----------------|---|----------------|---|--|
|  | |  | |  |  |
| Code | Code | Code | Code | Description | Length |
| CY | WF | YY | SY | | |
| X-CY0.75-2C-100 | | | | Cable 2 Core 0.75mm | 100m |
| X-CY0.75C-2C-50 | X-WF0.75-2C-50 | | | Cable 2 Core 0.75mm | 50m |
| X-CY1-2C-100 | X-WF1-2C-100 | | | Cable 2 Core 1mm | 100m |
| X-CY1-2C-50 | X-WF1-2C-50 | | | Cable 2 Core 1mm | 50m |
| X-CY1.5-2C-100 | | X-YY1.5-2C-100 | | Cable 2 Core 1.5mm | 100m |
| X-CY1.5-2C-50 | | | | Cable 2 Core 1.5mm | 50m |
| | X-WF0.75-3C-50 | | | Cable 3 Core 0.75mm | 50m |
| | X-WF1-3C-50 | | | Cable 3 Core 1mm | 50m |
| | | | X-SY1.5-3C-100 | Cable 3 Core 1.5mm | 100m |
| | X-WF1.5-3C-50 | | | Cable 3 Core 1.5mm | 50m |
| | | X-YY2.5-3C-100 | X-SY2.5-3C-100 | Cable 3 Core 2.5mm | 100m |
| | X-WF2.5-3C-50 | | X-SY2.5-3C-50 | Cable 3 Core 2.5mm | 50m |
| | | X-YY0.75-4C-100 | | Cable 4 Core 0.75mm | 100m |
| | | X-YY0.75-4C-50 | | Cable 4 Core 0.75mm | 50m |
| | | | X-SY1-4C-100 | Cable 4 Core 1mm | 100m |
| | | X-YY1.5-4C-100 | X-SY1.5-4C-100 | Cable 4 Core 1.5mm | 100m |
| | | X-YY1.5-4C-50 | X-SY1.5-4C-50 | Cable 4 Core 1.5mm | 50m |
| | | X-YY2.5-4C-100 | X-SY2.5-4C-100 | Cable 4 Core 2.5mm | 100m |
| | | X-YY2.5-4C-50 | | Cable 4 Core 2.5mm | 50m |
| | | | X-SY1.5-5C-100 | Cable 5 Core 1.5mm | 100m |
| | | | X-SY1.5-5C-50 | Cable 5 Core 1.5mm | 50m |
| | | | X-SY2.5-5C-100 | Cable 5 Core 2.5mm | 100m |
| | | | X-SY2.5-5C-50 | Cable 5 Core 2.5mm | 50m |
| | | X-YY1.5-7C-100 | | Cable 7 Core 1.5mm | 100m |
| | | X-YY1.5-7C-50 | | Cable 7 Core 1.5mm | 50m |

Cable Ties / Cable Tie Mounts

| Code | Description | Quantity |
|-------------------|---|-------------|
| X-CT100-2.5B-B100 | Cable Tie 100mm x 2.52mm - Black | Pack of 100 |
| X-CT300-4.8B-B100 | Cable Tie 300mm x 4.8mm - Black | Pack of 100 |
| X-CT300-4.8W-B100 | Cable Tie 300mm x 4.8mm - White | Pack of 100 |
| X-CT300-7.6B-B100 | Cable Tie 300mm x 7.6mm - Black | Pack of 100 |
| X-CT480-13B-B100 | Cable Tie 480mm x 13mm - Black | Pack of 100 |
| X-CT730-13B-B100 | Cable Tie 730mm x 13mm - Black | Pack of 100 |
| ID-BT-250 | Cable Tie 250mm x 20mm - Ivory | Pack of 20 |
| ID-BT-350 | Cable Tie 350mm x 20mm - Ivory | Pack of 20 |
| X-CB28-BL-B100 | Cable Tie Base - 28mm Self Adhesive - Black | Pack of 100 |
| X-CB28-W-B100 | Cable Tie Base - 28mm Self Adhesive - White | Pack of 100 |

| Code | Description | Quantity |
|-------|---------------------------------|-------------|
| CTM-1 | Cable Tie Mount - Screw Fixing | Pack of 100 |
| CTM-2 | Cable Tie Mount - with Studding | Pack of 100 |

CABLE TIES
VARIOUS

ID-BT-250



CTM-1

CTM-2



Easy-Fit



Footings



Fins



Install L



Partners



PH Family



PH Master



Protection



Service L



Support

Index - Product

| | | | | | |
|-----------------------------|--------|------------------------|---------|--------------------------|-------------|
| 90 Degree Brackets | 102 | Channel Z Bracket | 103 | Flexi Patch™ | 61 |
| Abrasive Cloth | 61, 84 | Chemicals - 1 Litre | 44, 82 | Flexi Quad Frames | 96 |
| Access Fittings | 42 | Chemicals - 5 Litre | 44, 82 | Flexi Solar | 77 |
| Acid Eliminator | 58 | Chemicals - Aerosols | 45, 83 | Flexi Twin Frames | 95 |
| Acid Test Kits | 58 | Cliplight Torches | 49, 84 | Flexible Hose | 78 |
| Adaptors | 17, 69 | Cloths | 85 | Flexi-Patch | 86 |
| Alarm | 17, 69 | Coach Screw | 109 | Floor Bracket Kit | 74 |
| All Purpose Cutter | 61 | Collection Trays | 24 | Flow-Plus™ | 58 |
| Aluminium Foil Tape | 61 | Compression Sprayers | 45, 63 | Foam Insulation Tape | 61 |
| Anchor Bolts | 110 | Compressor Tote | 48 | Foam Sealant | 57 |
| AV Mounting Bolts | 71 | Condensate Accessories | 19 | Fused Spur Switches | 112 |
| Back Plate | 102 | Connectors | 18 | Grip-Cut Cloth | 61, 84 |
| Basement Submersible Pump | 67 | Cool-Weld™ | 56 | Guards | 22, 75 |
| Basket Tray | 106 | Copper Fittings | 35 - 40 | Heat Barrier Spray | 85 |
| Basket Tray Accessories | 106 | Copper Spun Driers | 47 | Hex Set Screws | 109 |
| Basket Tray Ceiling Bracket | 106 | Core Removal Tool | 60 | Hexagonal Nut | 108 |
| Basket Tray Wall Bracket | 106 | Core Storer | 60 | Hexagonal Nut Cover | 108 |
| Beam G Clamp | 102 | Cork Insulation Tape | 61 | High Temperature Pumps | 16, 65 |
| Boiler Buoy | 88 | Cushion Clamps | 31 | Hose | 18 |
| Brackets | 23, 73 | Dairy Cabinet Pumps | 06 | Housings | 10 |
| Brass Fittings | 41, 42 | Diversi-Flush™ | 46 | Inaba Denko Trunking | 25, 80 |
| Braze Barrier Mats | 61, 84 | Diversi-Gum | 57, 86 | Inspection Mirrors | 47, 85 |
| Bronco Clips | 34 | Drain Gun™ | 46, 83 | Insta-charge | 60 |
| Cable | 113 | Drain Hose | 69 | Isolators | 10, 81, 112 |
| Cable Stuffing Gland | 112 | Drop In Anchor | 110 | Klo-Shure Clamps | 07 |
| Cable Tie Mounts | 113 | Dry R™ | 53 | Line Piercing Valves | 59 |
| Cable Ties | 113 | Eye Bolt | 110 | Line Tap Valve | 60 |
| Cable Tray | 104 | Fan Motors | 08, 09 | Loose Bolt Shield Anchor | 110 |
| Cable Tray Accessories | 105 | Fin Tools | 48 | Lubricants & Dyes | 55 |
| Cable Tray Flat Bends | 104 | Flash™ | 53 | Magnetic Drive Pumps | 20 |
| Cable Tray Hanger | 105 | Flat / Form Washer | 107 | Mini Pumps | 14 |
| Cable Tray Intersection | 105 | Flat Plates | 103 | Mounting Blocks | 27 |
| Cable Tray Reducer | 105 | Flex Inject® | 54 | Mounting Pads | 27 |
| Cable Tray Tees | 104 | Flexi Fix Clamp | 71, 93 | Mounting Strips | 27 |
| Cantilever Arms | 24 | Flexi Fix Pack | 71, 93 | Neutralisers | 66 |
| Channel 4 Hole | 103 | Flexi Foot Kits | 72 | Nitrogen Purge Tool | 47 |
| Channel Base Plate | 102 | Flexi Foot Universal | 71, 93 | Odour Elimination | 45 |
| Channel Black Capping | 102 | Flexi Foot Variations | 94 | Other Plates | 103 |
| Channel Bracket | 102 | Flexi Foot with Strut | 72, 92 | Parts Washer Pumps | 21 |
| Channel Clamp | 102 | Flexi Frames | 76, 90 | Penny Washer | 107 |
| Channel Internal Angle | 102 | Flexi H Frames | 91 | Peristaltic Pumps | 15 |
| Channel Nut Long Spring | 108 | Flexi Hop Overs | 99 | Pipe Clamps Lined | 111 |
| Channel Nut Plain | 108 | Flexi Lite Kit | 26 | Pipe Clamps Unlined | 111 |
| Channel Nut Short Spring | 108 | Flexi Lite Kits | 70 | Plastic End Caps | 104 |
| Channel U Bracket | 102 | Flexi Mini Foot | 94 | Plastic Pipe | 87, 88 |
| Channel Wing Fitting | 102 | Flexi Modular Frames | 97 | Pool Cover Pump | 21, 67 |

Index - Product

| | | | |
|------------------------------|--------|-----------------------------|--------|
| Portable Hand Torch | 61 | Through Wall Insulation Kit | 79 |
| Portables | 30, 77 | Trays | 74 |
| Power Sprayer | 46 | Twin Fast Screws | 109 |
| Pro-Bubble | 56 | Ultralite® Pads | 26, 70 |
| Protection Fleece | 93 | Vibration Absorbers | 07 |
| Pro-Tile™ | 57 | Walkway Mat | 54 |
| Pro-Treat™ | 58 | Wall Plugs | 109 |
| Pull A Spout Oiler | 56 | Wedge Nut | 108 |
| Pure-Beam™ Ultraviolet Light | 50 | Window Brackets | 103 |
| Purling Clips | 103 | Wypall Cloths | 56 |
| PVC Coated Insulation | 78 | | |
| PVC Coated Tape | 78 | | |
| PVC Pipe | 88 | | |
| Quick Sling | 29 | | |
| Quick Tap Valve Core | 59 | | |
| Refrigerant Recovery Tool | 59 | | |
| Remote Controller | 30 | | |
| Retrochill™ | 51 | | |
| Roofing Bolt & Nut | 108 | | |
| RPC | 32, 33 | | |
| Sealants | 86 | | |
| Seal-N-Go™ | 54 | | |
| Shake Proof Washer | 107 | | |
| Silicone Sealant | 57 | | |
| Slit & Seal Insulation | 79 | | |
| Slotted Channel | 102 | | |
| Soakaway | 74 | | |
| Socket Bolts | 110 | | |
| Soil & Vent Adaptors | 69 | | |
| Spark Key | 61 | | |
| Square Plate Washer | 107 | | |
| Stand Off Bracket | 105 | | |
| Stud Connectors | 109 | | |
| Studding Caps | 104 | | |
| Super Change™ | 52 | | |
| Super Seal Accessories | 53 | | |
| Super Seal Advanced™ | 52 | | |
| Super Seal Automotive | 51 | | |
| Super Seal Total™ | 52 | | |
| Sure Shot™ | 54 | | |
| Switches | 81 | | |
| Tank Pumps | 13 | | |
| TEK Screws | 109 | | |
| The Purifier | 51 | | |
| Threaded Rod | 104 | | |
| Threaded Rod Hangers | 31 | | |

Index - Part Code

| | | | | | | | | |
|--------|-----------|--------|--------|-----------|--------|------------|-----------|--------|
| 940 |Page | 54 | 724075 |Page | 07 | 16500 |Page | 61, 84 |
| 980 |Page | 53 | 724087 |Page | 07 | 16510 |Page | 61, 84 |
| 981 |Page | 52 | 724100 |Page | 07 | 170AIRFAN |Page | 51 |
| 984 |Page | 54 | 724112 |Page | 07 | 170AIRP |Page | 51 |
| 985 |Page | 54 | 724137 |Page | 07 | 170AIRPCB |Page | 51 |
| 1002 |Page | 45, 83 | 724162 |Page | 07 | 1Y-PW |Page | 21 |
| 2601 |Page | 45, 83 | 724212 |Page | 07 | 24-458 |Page | 49, 84 |
| 2602 |Page | 45, 83 | 724262 |Page | 07 | 24-460 |Page | 49, 84 |
| 2603 |Page | 45, 83 | 724312 |Page | 07 | 5-05790 |Page | 56 |
| 20122 |Page | 53 | 724362 |Page | 07 | 5-05790 |Page | 85 |
| 20128 |Page | 41, 53 | 724412 |Page | 07 | 525-TORCH |Page | 61 |
| 20133 |Page | 55 | 726025 |Page | 07 | 548-001 |Page | 61 |
| 51105 |Page | 55 | 726037 |Page | 07 | 6-202-1 |Page | 57, 86 |
| 51110 |Page | 55 | 726050 |Page | 07 | 6-202-2 |Page | 57, 86 |
| 51111 |Page | 55 | 726062 |Page | 07 | 6-330 |Page | 61 |
| 51112 |Page | 55 | 726075 |Page | 07 | 640-AF-2 |Page | 61 |
| 111112 |Page | 49 | 726087 |Page | 07 | 6-5718 |Page | 61 |
| 111113 |Page | 49 | 726112 |Page | 07 | 6E-CIA-SFS |Page | 67 |
| 111114 |Page | 49, 84 | 726137 |Page | 07 | 701-030 |Page | 18 |
| 111115 |Page | 49, 84 | 726162 |Page | 07 | 701-032 |Page | 18, 69 |
| 111116 |Page | 49 | 726212 |Page | 07 | 701-038 |Page | 18, 69 |
| 111117 |Page | 49, 84 | 726262 |Page | 07 | 70501KIT |Page | 51 |
| 111201 |Page | 50 | 726312 |Page | 07 | 70510KIT |Page | 51 |
| 114301 |Page | 49 | 726362 |Page | 07 | 7-4000 |Page | 57, 86 |
| 114302 |Page | 49 | 726412 |Page | 07 | 7-4100 |Page | 57, 86 |
| 154724 |Page | 17 | 728025 |Page | 07 | 805CLN |Page | 55 |
| 410212 |Page | 51 | 728037 |Page | 07 | 84DCPLUS |Page | 50 |
| 511046 |Page | 55 | 728050 |Page | 07 | 8-6H |Page | 69 |
| 511102 |Page | 55 | 728062 |Page | 07 | 87DCPLUS |Page | 50 |
| 511150 |Page | 55 | 728075 |Page | 07 | 900006B |Page | 55 |
| 599325 |Page | 15 | 728087 |Page | 07 | 900012B |Page | 55 |
| 723025 |Page | 07 | 728112 |Page | 07 | 908006B |Page | 55 |
| 723037 |Page | 07 | 728137 |Page | 07 | 908012B |Page | 55 |
| 723050 |Page | 07 | 728162 |Page | 07 | 927033 |Page | 69 |
| 723062 |Page | 07 | 728212 |Page | 07 | 9410SSR |Page | 54 |
| 723075 |Page | 07 | 728262 |Page | 07 | 944KIT |Page | 52 |
| 723087 |Page | 07 | 728312 |Page | 07 | 946KIT |Page | 51 |
| 723100 |Page | 07 | 728362 |Page | 07 | 947KIT |Page | 52 |
| 723112 |Page | 07 | 728412 |Page | 07 | 948KIT |Page | 52 |
| 723137 |Page | 07 | 900006 |Page | 55 | 971KIT |Page | 52 |
| 723162 |Page | 07 | 909006 |Page | 55 | 972KIT |Page | 52 |
| 723212 |Page | 07 | 911101 |Page | 55 | 973KIT |Page | 53 |
| 724025 |Page | 07 | 990006 |Page | 55 | 976KIT |Page | 51 |
| 724037 |Page | 07 | 01714 |Page | 57, 86 | 98084KIT |Page | 53 |
| 724050 |Page | 07 | 01724 |Page | 57, 86 | 98087KIT |Page | 53 |
| 724062 |Page | 07 | 154724 |Page | 69 | 983KIT |Page | 54 |

Index - Part Code

| | | | | | | | | |
|---------------|-----------|--------|--------------|-----------|----|--------------|-----------|----|
| 990006B |Page | 55 | C101-0215-PH |Page | 38 | C165-0150-PH |Page | 36 |
| 990012B |Page | 55 | C101-0295-PH |Page | 38 | C165-0159-PH |Page | 37 |
| ACID-ELIM |Page | 58 | C101-0390-PH |Page | 38 | C165-0160-PH |Page | 37 |
| ACT-6 |Page | 48 | C105-0025-PH |Page | 38 | C165-0161-PH |Page | 37 |
| ADAP-1 |Page | 17, 69 | C105-0050-PH |Page | 38 | C165-0215-PH |Page | 36 |
| ADAP-CAC-L |Page | 17 | C105-0057-PH |Page | 38 | C165-0222-PH |Page | 37 |
| ADAP-CAC-M |Page | 17 | C105-0058-PH |Page | 38 | C165-0223-PH |Page | 37 |
| ADAP-CAC-S |Page | 17 | C105-0058-PH |Page | 38 | C165-0224-PH |Page | 37 |
| ADAP-CAC-X |Page | 17 | C105-0059-PH |Page | 38 | C165-0295-PH |Page | 36 |
| AER-O-500 |Page | 45, 83 | C105-0100-PH |Page | 38 | C165-0304-PH |Page | 37 |
| AER-B-500 |Page | 45, 83 | C105-0107-PH |Page | 38 | C165-0305-PH |Page | 37 |
| AER-C-600 |Page | 45, 83 | C105-0150-PH |Page | 38 | C165-0390-PH |Page | 36 |
| AER-D-600 |Page | 45, 83 | C105-0159-PH |Page | 38 | C165-0398-PH |Page | 37 |
| AER-F-600 |Page | 45, 83 | C105-0215-PH |Page | 38 | C165-0399-PH |Page | 37 |
| AER-I-600 |Page | 45, 83 | C105-0295-PH |Page | 38 | C165-0400-PH |Page | 37 |
| ANTI-SYPH-KIT |Page | 69 | C105-0390-PH |Page | 38 | C165-0401-PH |Page | 37 |
| APCP-1700 |Page | 21, 67 | C154-0002-PH |Page | 36 | C165-0520-PH |Page | 36 |
| ASHP-SOAK |Page | 74 | C154-0025-PH |Page | 36 | C165-0531-PH |Page | 37 |
| ATK-1 |Page | 58 | C154-0050-PH |Page | 36 | C165-0532-PH |Page | 37 |
| ATK-4 |Page | 58 | C154-0090-PH |Page | 36 | C165-0533-PH |Page | 37 |
| ATL-1P |Page | 58 | C154-0100-PH |Page | 36 | C165-0850-PH |Page | 36 |
| AUDIBLE ALARM |Page | 17, 69 | C154-0150-PH |Page | 36 | C165-0862-PH |Page | 37 |
| AV-ADAPTOR-6 |Page | 17 | C154-0215-PH |Page | 36 | C165-0863-PH |Page | 37 |
| AVMB-1 |Page | 71 | C154-0296-PH |Page | 36 | C165-0864-PH |Page | 37 |
| AVM-PAD-1 |Page | 27 | C154-0390-PH |Page | 36 | C165-0750-PH |Page | 36 |
| AVM-PAD-2 |Page | 27 | C154-0620-PH |Page | 36 | C165-0790-PH |Page | 37 |
| AVM-PAD-3 |Page | 27 | C154-0650-PH |Page | 36 | C165-0850-PH |Page | 36 |
| AVMS-1 |Page | 27 | C154-0750-PH |Page | 36 | C165-0852-PH |Page | 37 |
| AVMS-2 |Page | 27 | C154-0850-PH |Page | 36 | C165-1498-PH |Page | 37 |
| AVMS-3 |Page | 27 | C165-0001-PH |Page | 36 | C180-0002-PH |Page | 38 |
| AVMS-4 |Page | 27 | C165-0002-PH |Page | 36 | C180-0025-PH |Page | 38 |
| AVMS-CR-3 |Page | 27 | C165-0007-PH |Page | 37 | C180-0050-PH |Page | 38 |
| AVMS-CR-4 |Page | 27 | C165-0025-PH |Page | 36 | C180-0080-PH |Page | 38 |
| B-5H |Page | 18 | C165-0030-PH |Page | 37 | C180-0100-PH |Page | 38 |
| BB-1 |Page | 68 | C165-0032-PH |Page | 37 | C180-0150-PH |Page | 38 |
| BCONDNEAU-30L |Page | 66 | C165-0033-PH |Page | 37 | C180-0215-PH |Page | 38 |
| BCONDNEUT-20L |Page | 66 | C165-0050-PH |Page | 36 | C180-0295-PH |Page | 38 |
| C101-0005-PH |Page | 38 | C165-0058-PH |Page | 37 | C180-0390-PH |Page | 38 |
| C101-0007-PH |Page | 38 | C165-0059-PH |Page | 37 | C235-0001-PH |Page | 35 |
| C101-0025-PH |Page | 38 | C165-0090-PH |Page | 36 | C235-0002-PH |Page | 35 |
| C101-0050-PH |Page | 38 | C165-0093-PH |Page | 37 | C235-0025-PH |Page | 35 |
| C101-0057-PH |Page | 38 | C165-0094-PH |Page | 37 | C235-0050-PH |Page | 35 |
| C101-0058-PH |Page | 38 | C165-0100-PH |Page | 36 | C235-0090-PH |Page | 35 |
| C101-0100-PH |Page | 38 | C165-0107-PH |Page | 37 | C235-0100-PH |Page | 35 |
| C101-0150-PH |Page | 38 | C165-0108-PH |Page | 37 | C235-0150-PH |Page | 35 |
| C101-0159-PH |Page | 38 | C165-0149-PH |Page | 37 | C235-0215-PH |Page | 35 |

Index - Part Code

| | | | | | |
|--------------|---------|--------------|---------|--------------|---------|
| C235-0295-PH | Page 35 | C290-0025-PH | Page 36 | C410-0306-PH | Page 37 |
| C235-0390-PH | Page 35 | C290-0050-PH | Page 36 | C410-0398-PH | Page 37 |
| C235-0520-PH | Page 35 | C290-0090-PH | Page 36 | C410-0399-PH | Page 37 |
| C235-0650-PH | Page 35 | C290-0100-PH | Page 36 | C410-0400-PH | Page 37 |
| C235-0750-PH | Page 35 | C290-0150-PH | Page 36 | C410-0401-PH | Page 37 |
| C235-0850-PH | Page 35 | C290-0215-PH | Page 36 | C410-0402-PH | Page 37 |
| C242-0001-PH | Page 35 | C290-0205-PH | Page 36 | C410-0531-PH | Page 37 |
| C242-0002-PH | Page 35 | C290-0390-PH | Page 36 | C410-0532-PH | Page 37 |
| C242-0025-PH | Page 35 | C290-0520-PH | Page 36 | C410-0533-PH | Page 37 |
| C242-0050-PH | Page 35 | C290-0650-PH | Page 36 | C410-0662-PH | Page 37 |
| C242-0090-PH | Page 35 | C290-0750-PH | Page 36 | C410-0663-PH | Page 37 |
| C242-0100-PH | Page 35 | C290-0850-PH | Page 36 | C410-0664-PH | Page 37 |
| C242-0150-PH | Page 35 | C295-0002-PH | Page 36 | C410-0754-PH | Page 37 |
| C242-0215-PH | Page 35 | C295-0025-PH | Page 36 | C410-0850-PH | Page 37 |
| C242-0295-PH | Page 35 | C295-0050-PH | Page 36 | C410-0852-PH | Page 37 |
| C242-0390-PH | Page 35 | C295-0090-PH | Page 36 | C410-0854-PH | Page 37 |
| C242-0520-PH | Page 35 | C295-0100-PH | Page 36 | C410-1498-PH | Page 37 |
| C242-0650-PH | Page 35 | C295-0150-PH | Page 36 | C460-0001-PH | Page 40 |
| C242-0750-PH | Page 35 | C295-0215-PH | Page 36 | C460-0002-PH | Page 40 |
| C242-0850-PH | Page 35 | C295-0295-PH | Page 36 | C460-0005-PH | Page 39 |
| C254-0002-PH | Page 35 | C295-0390-PH | Page 36 | C460-0006-PH | Page 39 |
| C254-0025-PH | Page 35 | C295-0520-PH | Page 36 | C460-0025-PH | Page 40 |
| C254-0050-PH | Page 35 | C295-0650-PH | Page 36 | C460-0031-PH | Page 39 |
| C254-0090-PH | Page 35 | C295-0750-PH | Page 36 | C460-0032-PH | Page 39 |
| C254-0100-PH | Page 35 | C295-0850-PH | Page 36 | C460-0033-PH | Page 39 |
| C254-0215-PH | Page 35 | C410-0007-PH | Page 37 | C460-0040-PH | Page 39 |
| C254-0295-PH | Page 35 | C410-0032-PH | Page 37 | C460-0041-PH | Page 39 |
| C254-0390-PH | Page 35 | C410-0033-PH | Page 37 | C460-0050-PH | Page 40 |
| C254-0520-PH | Page 35 | C410-0058-PH | Page 37 | C460-0056-PH | Page 39 |
| C254-0650-PH | Page 35 | C410-0059-PH | Page 37 | C460-0057-PH | Page 39 |
| C254-0750-PH | Page 35 | C410-0083-PH | Page 37 | C460-0058-PH | Page 39 |
| C254-0850-PH | Page 35 | C410-0094-PH | Page 37 | C460-0059-PH | Page 39 |
| C272-0002-PH | Page 35 | C410-0095-PH | Page 37 | C460-0066-PH | Page 39 |
| C272-0025-PH | Page 35 | C410-0107-PH | Page 37 | C460-0067-PH | Page 39 |
| C272-0050-PH | Page 35 | C410-0108-PH | Page 37 | C460-0068-PH | Page 39 |
| C272-0090-PH | Page 35 | C410-0109-PH | Page 37 | C460-0076-PH | Page 39 |
| C272-0100-PH | Page 35 | C410-0149-PH | Page 37 | C460-0087-PH | Page 39 |
| C272-0150-PH | Page 35 | C410-0159-PH | Page 37 | C460-0090-PH | Page 40 |
| C272-0215-PH | Page 35 | C410-0160-PH | Page 37 | C460-0092-PH | Page 39 |
| C272-0295-PH | Page 35 | C410-0161-PH | Page 37 | C460-0093-PH | Page 39 |
| C272-0390-PH | Page 35 | C410-0222-PH | Page 37 | C460-0094-PH | Page 39 |
| C272-0520-PH | Page 35 | C410-0223-PH | Page 37 | C460-0095-PH | Page 39 |
| C272-0650-PH | Page 35 | C410-0224-PH | Page 37 | C460-0098-PH | Page 39 |
| C272-0750-PH | Page 35 | C410-0303-PH | Page 37 | C460-0100-PH | Page 40 |
| C272-0850-PH | Page 35 | C410-0304-PH | Page 37 | C460-0106-PH | Page 39 |
| C290-0002-PH | Page 36 | C410-0306-PH | Page 37 | C460-0107-PH | Page 39 |

Index - Part Code

| | | | | | | | | |
|--------------|-----------|----|--------------|-----------|--------|---------------------|-----------|--------|
| C460-0108-PH |Page | 39 | C460-0416-PH |Page | 39 | C8R2-EL |Page | 23 |
| C460-0109-PH |Page | 39 | C460-0417-PH |Page | 39 | C8R2-L |Page | 23, 73 |
| C460-0111-PH |Page | 39 | C460-0429-PH |Page | 39 | C8R2-L-SS |Page | 23, 73 |
| C460-0117-PH |Page | 39 | C460-0431-PH |Page | 39 | C8R2-M |Page | 23, 73 |
| C460-0118-PH |Page | 39 | C460-0432-PH |Page | 39 | C8R2-M-SS |Page | 23, 73 |
| C460-0119-PH |Page | 39 | C460-0520-PH |Page | 40 | C8R2-S |Page | 23, 73 |
| C460-0127-PH |Page | 39 | C460-0531-PH |Page | 39 | C8R2-XL |Page | 23, 73 |
| C460-0150-PH |Page | 40 | C460-0532-PH |Page | 39 | C8R2-XL-3A |Page | 73 |
| C460-0157-PH |Page | 39 | C460-0533-PH |Page | 39 | C8R2-XL-SS |Page | 23, 73 |
| C460-0156-PH |Page | 39 | C460-0534-PH |Page | 39 | C8R3-L |Page | 23 |
| C460-0159-PH |Page | 39 | C460-0535-PH |Page | 39 | C8R3-M |Page | 23 |
| C460-0160-PH |Page | 39 | C460-0549-PH |Page | 39 | CC-004 |Page | 31 |
| C460-0169-PH |Page | 39 | C460-0650-PH |Page | 40 | CC-006 |Page | 31 |
| C460-0170-PH |Page | 39 | C460-0683-PH |Page | 39 | CC-008 |Page | 31 |
| C460-0171-PH |Page | 39 | C460-0684-PH |Page | 39 | CC-010 |Page | 31 |
| C460-0190-PH |Page | 39 | C460-0750-PH |Page | 40 | CC-012 |Page | 31 |
| C460-0181-PH |Page | 39 | C460-0850-PH |Page | 40 | CC-014 |Page | 31 |
| C460-0215-PH |Page | 40 | C460-1488-PH |Page | 39 | CC-018 |Page | 31 |
| C460-0221-PH |Page | 39 | C533-0050-PH |Page | 40 | CC-022 |Page | 31 |
| C460-0222-PH |Page | 39 | C533-0090-PH |Page | 40 | CC-025 |Page | 31 |
| C460-0222-PH |Page | 39 | C533-0100-PH |Page | 40 | CC-034 |Page | 31 |
| C460-0223-PH |Page | 39 | C533-0150-PH |Page | 40 | CC-042 |Page | 31 |
| C460-0224-PH |Page | 39 | C533-0215-PH |Page | 40 | CC-050 |Page | 31 |
| C460-0235-PH |Page | 39 | C533-0295-PH |Page | 40 | CC-058 |Page | 31 |
| C460-0237-PH |Page | 39 | C533-0390-PH |Page | 40 | CC-066 |Page | 31 |
| C460-0245-PH |Page | 39 | C947-0025-PH |Page | 38 | CC-1 |Page | 19 |
| C460-0246-PH |Page | 39 | C947-0050-PH |Page | 38 | CCT-790 |Page | 24 |
| C460-0247-PH |Page | 39 | C947-0090-PH |Page | 38 | CCT-900 |Page | 24 |
| C460-0295-PH |Page | 40 | C947-0100-PH |Page | 38 | CCTM-1100 |Page | 24, 74 |
| C460-0302-PH |Page | 39 | C947-0150-PH |Page | 38 | CCTM-1400 |Page | 24, 74 |
| C460-0303-PH |Page | 39 | C947-0215-PH |Page | 38 | CCTM-800 |Page | 24, 74 |
| C460-0305-PH |Page | 39 | C947-0295-PH |Page | 38 | CCTM-FLOOR-BRKT-KIT |Page | 74 |
| C460-0306-PH |Page | 39 | C947-0390-PH |Page | 38 | CG-500-L |Page | 22, 75 |
| C460-0315-PH |Page | 39 | CA-450-KIT |Page | 24 | CG-500-M |Page | 22, 75 |
| C460-0316-PH |Page | 39 | CA-450-S |Page | 24 | CG-500-S |Page | 22, 75 |
| C460-0328-PH |Page | 39 | CA-600-KIT |Page | 24 | CG-750+WOOD |Page | 22, 75 |
| C460-0330-PH |Page | 39 | CA-600-S |Page | 24 | CG-750+INV |Page | 22, 75 |
| C460-0331-PH |Page | 39 | CA-600-W |Page | 24 | CG-750-L |Page | 22, 75 |
| C460-0339-PH |Page | 39 | CA-750-S |Page | 24 | CG-750L+INV+WOOD |Page | 22, 75 |
| C460-0390-PH |Page | 40 | CA-750-W |Page | 24 | CG-750L+WOOD |Page | 22, 75 |
| C460-0397-PH |Page | 39 | CB-2 |Page | 19 | CG-750L-WOOD |Page | 22, 75 |
| C460-0398-PH |Page | 39 | CBR1-L |Page | 23, 73 | CG-750-M |Page | 22, 75 |
| C460-0399-PH |Page | 39 | CBR1-M |Page | 23, 73 | CG-750M+WOOD |Page | 22, 75 |
| C460-0400-PH |Page | 39 | CBR1-S |Page | 23, 73 | CG-750-S |Page | 22, 75 |
| C460-0401-PH |Page | 39 | CBR1-XL |Page | 23, 73 | CG-750S-WOOD |Page | 22, 75 |
| C460-0414-PH |Page | 39 | CBR1-XXL |Page | 23, 73 | CG-900L+INV |Page | 22, 75 |

Index - Part Code

| | | | | | | | | |
|--------------|-----------|--------|---------|-----------|----|------------|-----------|------------|
| CG-900L-SQ |Page | 22, 75 | DN1-14 |Page | 41 | DU3-8C |Page | 42 |
| CG-900-XXL |Page | 22, 75 | DN1-3 |Page | 41 | DU3-8D |Page | 42 |
| CG-L |Page | 22 | DN1-4 |Page | 41 | DUS4-4 |Page | 42 |
| CG-M |Page | 22 | DN1-5 |Page | 41 | DUS4-6 |Page | 42 |
| CG-S |Page | 22 | DN1-6 |Page | 41 | DUS4-8 |Page | 42 |
| CG-VRF-BP |Page | 22, 75 | DN1-8 |Page | 41 | DX-3 |Page | 47 |
| CG-VRF-EP-12 |Page | 22, 75 | DN5-4 |Page | 41 | DX-4 |Page | 47 |
| CG-VRF-EP-6 |Page | 22, 75 | DN5-6 |Page | 41 | DXA-5 |Page | 47 |
| CG-XL |Page | 22 | DNS4-10 |Page | 41 | EC-1 |Page | 14 |
| CH-L |Page | 10 | DNS4-12 |Page | 41 | EC-1-KIT |Page | 14 |
| CH-S |Page | 10 | DNS4-14 |Page | 41 | EC-400 |Page | 14 |
| CLL-1 |Page | 57 | DNS4-4 |Page | 41 | ECOP-ADAP |Page | 17 |
| CMB-100 |Page | 27 | DNS4-6 |Page | 41 | ET-150 |Page | 08 |
| CMB-1000-W |Page | 27 | DNS4-8 |Page | 41 | EXTCABLE |Page | 15 |
| CMB-350 |Page | 27 | DP-1 |Page | 47 | FBB-154-25 |Page | 09 |
| CMB-450 |Page | 27 | DP2-10 |Page | 41 | FBB-154-31 |Page | 09 |
| CMB-450-W |Page | 27 | DP2-4 |Page | 41 | FBB-172-25 |Page | 09 |
| CO-1 |Page | 56 | DP2-6 |Page | 41 | FBB-172-31 |Page | 09 |
| COOLWELD-32 |Page | 56, 86 | DP2-8 |Page | 41 | FBB-200-25 |Page | 09 |
| CS1200 |Page | 19 | DT2-10 |Page | 41 | FBB-200-31 |Page | 09 |
| CTC-050 |Page | 33 | DT2-4 |Page | 41 | FBB-230-25 |Page | 09 |
| CTC-065 |Page | 33 | DT2-6 |Page | 41 | FBB-230-31 |Page | 09 |
| CTC-080 |Page | 33 | DT2-8 |Page | 41 | FBB-254-25 |Page | 09 |
| CTM-1 |Page | 113 | DU1-10D |Page | 42 | FBB-254-31 |Page | 09 |
| CTM-2 |Page | 113 | DU1-10E |Page | 42 | FBB-300-25 |Page | 09 |
| CV-14-3 |Page | 17 | DU1-12D |Page | 42 | FBB-300-31 |Page | 09 |
| CV-38-3 |Page | 17, 69 | DU1-12E |Page | 42 | FBR-109-1 |Page | 09 |
| DCP-30A |Page | 06 | DU1-4A |Page | 42 | FBR-109-2 |Page | 09 |
| DCP-30E |Page | 06 | DU1-4B |Page | 42 | FBR-109-3 |Page | 09 |
| DCP-30V |Page | 06 | DU1-6B |Page | 42 | FBR-39 |Page | 09 |
| DCV-1G |Page | 60 | DU1-8C |Page | 42 | FBR-55 |Page | 09 |
| DE-05-FD |Page | 14 | DU1-8D |Page | 42 | FBR-72 |Page | 09 |
| DE1-10D |Page | 41 | DU1-8E |Page | 42 | FBR-84 |Page | 09 |
| DE1-12D |Page | 41 | DU1-8B |Page | 42 | FBS-154-25 |Page | 09 |
| DE1-12E |Page | 41 | DU1-8C |Page | 42 | FBS-154-31 |Page | 09 |
| DE1-4B |Page | 41 | DU1-8D |Page | 42 | FBS-172-25 |Page | 09 |
| DE1-6B |Page | 41 | DU1-8E |Page | 42 | FBS-172-31 |Page | 09 |
| DE1-8C |Page | 41 | DU2-10 |Page | 41 | FBS-200-25 |Page | 09 |
| DE1-6D |Page | 41 | DU2-12 |Page | 41 | FBS-200-31 |Page | 09 |
| DE1-8D |Page | 41 | DU2-4 |Page | 41 | FBS-230-25 |Page | 09 |
| DE1-8E |Page | 41 | DU2-6 |Page | 41 | FBS-230-31 |Page | 09 |
| DLT-3G |Page | 60 | DU2-8 |Page | 41 | FBS-254-25 |Page | 09 |
| DLT-4G |Page | 60 | DU3-10D |Page | 42 | FBS-254-31 |Page | 09 |
| DLT-5G |Page | 60 | DU3-10E |Page | 42 | FBS-300-25 |Page | 09 |
| DN1-10 |Page | 41 | DU3-6C |Page | 42 | FBS-300-31 |Page | 09 |
| DN1-12 |Page | 41 | DU3-6D |Page | 42 | FF-1000-S |Page | 72, 77, 92 |

Index - Part Code

| | | | | | |
|----------------------|----------------------|------------------|------------------|-----------------|------------------|
| FF-1000-S-KIT |Page 72 | FM-10W |Page 08 | HZSB225 |Page 34 |
| FF-250-S |Page 72, 77, 92 | FM-16W |Page 08 | HZSB325 |Page 34 |
| FF-250-S-P-L |Page 92 | FM-18W |Page 08 | HZSB425 |Page 34 |
| FF-250-UNI |Page 71, 93 | FM-25W |Page 08 | HZSB525 |Page 34 |
| FF-400-S |Page 72, 77, 92 | FM-34W |Page 08 | HZSB625 |Page 34 |
| FF-400-S-KIT |Page 72 | FM-5W |Page 08 | HZSB825 |Page 34 |
| FF-400-S-P-L |Page 92 | FM-7W |Page 08 | HZSW225 |Page 34 |
| FF-600-S |Page 72, 77, 92 | FM-A-12025-L |Page 08 | HZSW325 |Page 34 |
| FF-600-S-KIT |Page 72 | FM-A-12038-L |Page 08 | HZSW425 |Page 34 |
| FF-FIX-2 |Page 71, 93 | FM-A-12038-T |Page 08 | HZSW525 |Page 34 |
| FF-FIX-CLAMP |Page 71, 93 | FM-A-8038-L |Page 08 | HZSW625 |Page 34 |
| FF-FIX-PACK |Page 71, 93 | F-MF-160 |Page 94 | HZSW825 |Page 34 |
| FF-UC3 |Page 26, 70 | FMTS-15W-120 |Page 08 | IC00-15 |Page 33 |
| FF-UC3-3 |Page 26, 70 | FMTS-20W-120 |Page 08 | IC00-20 |Page 33 |
| FF-UC3-ASN |Page 26 | FMTS-30W-240 |Page 08 | IC00-22 |Page 33 |
| FF-UC3-XL |Page 26, 70 | FMTS-30W-300 |Page 08 | IC00-25 |Page 33 |
| FF-UC-PLATE-KIT |Page 26, 70 | FP-36 |Page 81, 86 | IC00-28 |Page 33 |
| FF-UCS-ASN |Page 70 | F-QUAD-500 |Page 96 | IC00-32 |Page 33 |
| FG-154 |Page 09 | F-QUAD-500-A |Page 96 | IC00-35 |Page 33 |
| FG-172 |Page 09 | FRS-154 |Page 09 | IC00-40 |Page 33 |
| FG-200 |Page 09 | FRS-172 |Page 09 | IC00-42 |Page 33 |
| FG-230 |Page 09 | FRS-200 |Page 09 | IC00-50 |Page 33 |
| FG-254 |Page 09 | FRS-230 |Page 09 | IC00-54 |Page 33 |
| FG-300 |Page 09 | FRS-254 |Page 09 | ID-BT-250 |Page 113 |
| FH-1000-28-F |Page 76 | FRS-300 |Page 09 | ID-BT-350 |Page 113 |
| FH-300-28-11/4-F-ELB |Page 76 | F-SO-2 |Page 99 | ID-NSD-100-I |Page 25, 80 |
| FH-300-28-F-ELB |Page 76 | F-SO-3 |Page 99 | ID-NSD-100-W |Page 25 |
| FH-500-F |Page 76 | F-SO-4 |Page 99 | ID-NSD-75-I |Page 25 |
| FH-750-28-11/4-F |Page 76 | F-TQ-ADJ-D |Page 95, 96 | ID-NSD-75-K |Page 25 |
| FH-750-28-F |Page 76 | F-TQ-ADJ-S |Page 95, 96 | ID-NSD-75-W |Page 25 |
| FH-750-28-F-ELB |Page 76 | F-TWIN-500 |Page 95 | ID-SC-100-I |Page 25, 80 |
| FH-750-28-M |Page 76 | F-TWIN-500-A |Page 95 | ID-SC-100-K |Page 25, 80 |
| F-HF-320 |Page 91 | G2G-BUBBLE-GB |Page 44 | ID-SC-100-W |Page 25 |
| F-HF-500 |Page 91 | G2G-CARE-GB |Page 44 | ID-SC-75-I |Page 25 |
| FH-I-1000-15 |Page 76 | G2G-FOAM+GB |Page 44 | ID-SC-75-K |Page 25 |
| FH-I-1000-22 |Page 76 | G2G-GREEN+GB |Page 44, 82 | ID-SC-75-W |Page 25 |
| FH-I-1000-22-SLIT |Page 79 | G2G-SMELL-BUSTER |Page 45 | ID-SCF-100-I |Page 25 |
| FH-I-1000-28 |Page 76 | G2G-UNIV-GB |Page 44, 82 | ID-SCF-100-K |Page 25 |
| FH-I-1000-28-SLIT |Page 79 | GFC-1 |Page 31 | ID-SCF-100-W |Page 25 |
| FH-I-1000-35 |Page 76 | GFC-2 |Page 31 | ID-SCF-75-I |Page 25 |
| FH-I-1000-35-SLIT |Page 79 | GFC-3 |Page 31 | ID-SCF-75-K |Page 25 |
| F-HO-1000 |Page 99 | GFC-4 |Page 31 | ID-SCF-75-W |Page 25 |
| F-HO-600 |Page 99 | GG-1 |Page 46, 83 | ID-SCR-100-75-K |Page 25 |
| F-HO-HR |Page 99 | GG-1A |Page 46, 83 | ID-SD-100-K |Page 80 |
| FLOW-PLUS-25 |Page 58 | GG-1H |Page 46, 83 | ID-SDR-100-75-I |Page 25 |
| FLOW-PLUS-6 |Page 58 | GGC-6 |Page 46, 83 | ID-SDR-100-75-W |Page 25 |

Index - Part Code

| | | | | | | | | |
|-----------------|-----------|--------|----------------|-----------|-------------|-----------------|-----------|--------|
| ID-SE-100-800-I |Page | 25 | ID-SWC-75-W |Page | 25 | PE2-YSA |Page | 21 |
| ID-SE-75-I |Page | 25 | INS-TAPE-10-PK |Page | 78 | PF-16-EU |Page | 46 |
| ID-SE-75-K |Page | 25 | IS-3P-32A |Page | 10, 81, 112 | PF-ADAPTOR |Page | 46 |
| ID-SE-75-W |Page | 25 | IS-3P-40A |Page | 10, 81, 112 | PF-KIT-EU |Page | 46 |
| ID-SEN-100-I |Page | 25 | IS-3P-20A |Page | 10, 81, 112 | PH-0.8-LC |Page | 64 |
| ID-SEN-100-K |Page | 25 | IS-3P-32A |Page | 10, 81, 112 | PH-0.8L-HL |Page | 64 |
| ID-SEN-100-W |Page | 25 | IS-3P-40A |Page | 10, 81, 112 | PH-1L |Page | 13 |
| ID-SF-100-800-K |Page | 25 | IS-3P-63A |Page | 10, 81, 112 | PH-1LSS |Page | 13 |
| ID-SF-100-800-W |Page | 25 | IS-4P-63A |Page | 10, 81, 112 | PH-1-SILENCE |Page | 13 |
| ID-SF-75-500-I |Page | 25 | IS-4P-20A |Page | 10, 81, 112 | PH-20-STA |Page | 64 |
| ID-SJ-100-I |Page | 25, 80 | IS-4P-20A-S |Page | 10, 81, 112 | PH-2L |Page | 13 |
| ID-SJ-100-K |Page | 25, 80 | IS-4P-32A |Page | 10, 81, 112 | PH-2LSS |Page | 13 |
| ID-SJ-100-W |Page | 25 | IS-4P-32A-S |Page | 10, 81, 112 | PH-2-SILENCE |Page | 13 |
| ID-SJ-75-I |Page | 25 | IS-4P-40A |Page | 10, 81, 112 | PH-3.8L-HW |Page | 16, 65 |
| ID-SJ-75-K |Page | 25 | IS-4P-63A |Page | 10, 81, 112 | PH-3.8L-HW |Page | 65 |
| ID-SJ-75-W |Page | 25 | ISO-18 |Page | 28 | PH-5L-HW |Page | 16 |
| ID-SK-100-I |Page | 25, 80 | ISO-2 |Page | 28 | PH-5L-HW |Page | 65 |
| ID-SK-100-K |Page | 80 | ISO-4 |Page | 28 | PH-6F-B |Page | 76 |
| ID-SK-75-I |Page | 25 | KT-1000 |Page | 30 | PH-6F-B |Page | 90 |
| ID-SKF-100-I |Page | 25 | M-1 |Page | 47, 85 | PH-EF-B |Page | 76 |
| ID-SKF-100-K |Page | 25 | M-1R |Page | 47, 85 | PH-EF-B |Page | 90 |
| ID-SKF-100-W |Page | 25 | M-2 |Page | 47, 85 | PHF-005A |Page | 97 |
| ID-SKF-75-I |Page | 25 | M-2R |Page | 47, 85 | PHF-005B |Page | 97 |
| ID-SP-100-I |Page | 25 | M-3 |Page | 47, 85 | PHF-005C |Page | 97 |
| ID-SP-100-K |Page | 25 | M-3R |Page | 47, 85 | PHF-005D |Page | 97 |
| ID-SP-100-W |Page | 25 | M-4 |Page | 47, 85 | PHF-016 |Page | 97 |
| ID-SP-75-I |Page | 25 | M-5 |Page | 47, 85 | PHF-016A |Page | 97 |
| ID-SP-75-K |Page | 25 | MBK-6 |Page | 19 | PHF-016B |Page | 97 |
| ID-SP-75-W |Page | 25 | MP-12C |Page | 28 | PHF-016C |Page | 97 |
| ID-ST-100-I |Page | 25 | MP-12E |Page | 28 | PHF-016D |Page | 97 |
| ID-ST-100-K |Page | 25 | MP-18C |Page | 28 | PH-FO-200 |Page | 94 |
| ID-ST-100-W |Page | 25 | MP-18E |Page | 28 | PH-FO-350 |Page | 94 |
| ID-ST-75-I |Page | 25 | MP-2C |Page | 28 | PH-FO-350-2 |Page | 94 |
| ID-ST-75-K |Page | 25 | MP-2E |Page | 28 | PH-FO-350-2.5-S |Page | 94 |
| ID-ST-75-W |Page | 25 | MP-3C |Page | 28 | PH-FO-350-5.0-S |Page | 94 |
| ID-SW-100-I |Page | 25, 80 | MP-3E |Page | 28 | PH-FO-500 |Page | 94 |
| ID-SW-100-K |Page | 25, 80 | MP-4C |Page | 28 | PH-FO-500-2 |Page | 94 |
| ID-SW-100-W |Page | 25 | MP-4E |Page | 28 | PH-FO-500-2.5 |Page | 94 |
| ID-SW-75-I |Page | 25 | MP-6C |Page | 28 | PH-FO-500-5.0 |Page | 94 |
| ID-SW-75-K |Page | 25 | MP-6E |Page | 28 | PH-PUMP-NRV |Page | 17 |
| ID-SW-75-W |Page | 25 | MPF-12 |Page | 93 | PH-PUMP-NRV |Page | 69 |
| ID-SWC-100-I |Page | 25 | MSA-44 |Page | 42 | PP-21.5-NRV |Page | 87 |
| ID-SWC-100-K |Page | 25 | PAC-C-12 |Page | 30, 77 | PP-45EL-21.5-B |Page | 87 |
| ID-SWC-100-W |Page | 25 | PAC-C-12S |Page | 30, 77 | PP-45EL-21.5-W |Page | 87 |
| ID-SWC-75-I |Page | 25 | PAC-H-12 |Page | 30, 77 | PP-80EL-21.5-B |Page | 87 |
| ID-SWC-75-K |Page | 25 | PAC-H-12S |Page | 30, 77 | PP-80EL-21.5-W |Page | 87 |

Index - Part Code

| | | | | | |
|--------------------|--------------|----------------|------------------|--------------------|------------------|
| PP-CL-15W |Page 87 | QTM-1 |Page 59 | SMELL-BUSTER-SMALL |Page 45 |
| PP-CL-21.5-W-32-40 |Page 87 | QTM-2 |Page 59 | SOAK1 |Page 68 |
| PP-CL-22-W |Page 87 | RC-1 |Page 60 | SPARK-KEY |Page 61 |
| PP-CL-28-W |Page 87 | RPC-0012 |Page 32 | SVA-3 |Page 17, 69 |
| PP-CL-32-B |Page 87 | RPC-0014 |Page 32 | SVA-6-3 |Page 17, 69 |
| PP-CL-32-G |Page 87 | RPC-0034 |Page 32 | SV-ADAPTOR |Page 17, 69 |
| PP-CL-32-W |Page 87 | RPC-0038 |Page 32 | T-1 |Page 48 |
| PP-CL-40-B |Page 87 | RPC-0058 |Page 32 | T-10 |Page 48 |
| PP-CL-40-G |Page 87 | RPC-0078 |Page 32 | T-100 |Page 48 |
| PP-CL-40-W |Page 87 | RPC-0118 |Page 32 | T-101 |Page 48 |
| PP-CON-21.5-W |Page 87 | RPC-0138 |Page 32 | T-11 |Page 48 |
| PP-CON-21.5-B |Page 87 | RPC-0158 |Page 32 | T-12 |Page 48 |
| PP-PIPE-21.5-B |Page 87 | RVT-1/2 |Page 69 | T-13 |Page 48 |
| PP-PIPE-21.5-W |Page 87 | RVT-1/2-B |Page 18 | T-14 |Page 48 |
| PP-SOBOSS-110-B-32 |Page 88 | RVT-1/4 |Page 18, 69 | T-15 |Page 48 |
| PP-SOBOSS-110-B-40 |Page 88 | RVT-1/4-B |Page 18 | T-16 |Page 48 |
| PP-SOBOSS-110-G-32 |Page 88 | RVT-3/4-6 |Page 18 | T-20 |Page 48 |
| PP-SOBOSS-110-G-40 |Page 88 | RVT-3/8 |Page 18, 69 | T-200 |Page 48 |
| PP-T-21.5-B |Page 87 | RVT-3/8-B |Page 18 | T-21 |Page 48 |
| PP-T-21.5-W |Page 87 | RVT-5/8 |Page 18 | T-300 |Page 48 |
| PP-UNI-CL-W-32-40 |Page 87 | SC08-15 |Page 32 | T-400 |Page 48 |
| PP-UNI-NRV |Page 87 | SC08-20 |Page 32 | T-408 |Page 48 |
| PRO-BUBBLE-32 |Page 44 | SC08-22 |Page 32 | T-409 |Page 48 |
| PRO-CARE-GB |Page 44 | SC08-25 |Page 32 | T-411 |Page 48 |
| PRO-CLEAN-GB |Page 44 | SC08-28 |Page 32 | T-412 |Page 48 |
| PRO-COOL-GB |Page 44 | SC08-32 |Page 32 | T-417 |Page 48 |
| PRO-FOAM+GB |Page 44 | SC08-35 |Page 32 | T-418 |Page 48 |
| PRO-GREEN |Page 82 | SC08-40 |Page 32 | T-8 |Page 48 |
| PRO-GREEN-GB |Page 44 | SC08-42 |Page 32 | T-9 |Page 48 |
| PRO-SCALE-GB |Page 44 | SC08-50 |Page 32 | TE-3-MD-HE |Page 20 |
| PRO-TREAT 151 |Page 58 | SC08-54 |Page 32 | TE-3-MD-SC |Page 20 |
| PRO-TREAT 152 |Page 58 | SC-10 |Page 61, 84 | TE-4-MD-HC |Page 20 |
| PRO-TREAT 161 |Page 58 | SC10-15 |Page 32 | TE-4-MD-SC |Page 20 |
| PRO-UNI |Page 82 | SC10-20 |Page 32 | TE-5.5-MD-HC |Page 20 |
| PRO-UNIV-GB |Page 44 | SC10-22 |Page 32 | TE-5.5-MD-SC |Page 20 |
| PS-1 |Page 46 | SC10-25 |Page 32 | TE-5-MD-HC |Page 20 |
| QSMS1201 |Page 29 | SC10-28 |Page 32 | TE-5-MD-SC |Page 20 |
| QSMS1801 |Page 29 | SC10-32 |Page 32 | TE-6-MD-HC |Page 20 |
| QSMS2401 |Page 29 | SC10-35 |Page 32 | TE-6-MD-SC |Page 20 |
| QT-1 |Page 59 | SC10-40 |Page 32 | TE-7-MD-HC |Page 20 |
| QT-100 |Page 59 | SC10-42 |Page 32 | TE-7-MD-SC |Page 20 |
| QT-100G |Page 59 | SC10-50 |Page 32 | TPR |Page 15 |
| QT-100N |Page 59 | SC10-54 |Page 32 | TPRC-10 |Page 15 |
| QT-2 |Page 59 | SCM-5 |Page 61, 84 | TPS |Page 15 |
| QTH-1 |Page 59 | SMELL-BUSTER |Page 45 | TPT |Page 15 |
| QTH-2 |Page 59 | SMELL-BUSTER-8 |Page 45 | TR-CP-140 |Page 60 |

Index - Part Code

| | | | | | |
|-------------|------------------|------------------|-------------------|----------------|-------------------|
| TR-CP-140-B |Page 80 | VCRT-1R |Page 60 | X-BGC-M8 |Page 102 |
| TR-D-140 |Page 80 | VCRT-1S |Page 60 | X-BP810 |Page 102 |
| TR-D-140-B |Page 80 | VIBA-1/2 |Page 07 | X-BSPS-10A |Page 81, 112 |
| TR-EC-140 |Page 80 | VIBA-1/4 |Page 07 | X-BT-100 |Page 106 |
| TR-EC-140-B |Page 80 | VIBA-1-1/8 |Page 07 | X-BT-150 |Page 106 |
| TR-FB-140 |Page 80 | VIBA-1-3/8 |Page 07 | X-BT-200 |Page 106 |
| TR-FB-140-B |Page 80 | VIBA-1-5/8 |Page 07 | X-BT-300 |Page 106 |
| TRH-1 |Page 31 | VIBA-2-1/8 |Page 07 | X-BT-400 |Page 106 |
| TRH-2 |Page 31 | VIBA-2-5/8 |Page 07 | X-BT-450 |Page 106 |
| TRH-3 |Page 31 | VIBA-3/4 |Page 07 | X-BT-500 |Page 106 |
| TRH-4 |Page 31 | VIBA-3/8 |Page 07 | X-BT-60 |Page 106 |
| TR-IC-140 |Page 80 | VIBA-3-1/8 |Page 07 | X-BT-600 |Page 106 |
| TR-IC-140-B |Page 80 | VIBA-3-5/8 |Page 07 | X-BTC |Page 106 |
| TR-WC-140 |Page 80 | VIBA-4-1/8 |Page 07 | X-BTCB-150 |Page 106 |
| TR-WC-140-B |Page 80 | VIBA-5/8 |Page 07 | X-BTCB-200 |Page 106 |
| TW-KIT |Page 79 | VIBA-7/8 |Page 07 | X-BTCB-300 |Page 106 |
| UC1636-2 |Page 26, 70 | VS-4 |Page 42 | X-BT-CH |Page 106 |
| UC2424-2 |Page 26, 70 | VST-4 |Page 42 | X-BT-FC |Page 106 |
| UC2436-3 |Page 26, 70 | VST-44 |Page 42 | X-BT-HDC |Page 106 |
| UC2442-3 |Page 26, 70 | VST-44X |Page 42 | X-BTJ |Page 106 |
| UC2448-3 |Page 26, 70 | VST-4X |Page 42 | X-BTM-100 |Page 106 |
| UV-1 |Page 50 | VT-14 |Page 18 | X-BTM-150 |Page 106 |
| UVEC-07G |Page 51 | VT-38 |Page 18 | X-BTM-200 |Page 106 |
| VA-3-346 |Page 42 | VTR-24 |Page 42 | X-BTM-300 |Page 106 |
| VA-34 |Page 42 | VTS-10 |Page 42 | X-BT-PC |Page 106 |
| VA-46 |Page 42 | VTS-46 |Page 42 | X-BT-SH |Page 106 |
| VA-68 |Page 42 | VTS-88 |Page 42 | X-BTWB-150 |Page 106 |
| VAU-24 |Page 42 | VTS-810 |Page 42 | X-BTWB-200 |Page 106 |
| VAU-45 |Page 42 | VUR-4 |Page 42 | X-BTWB-300 |Page 106 |
| VAX-3 |Page 42 | WAC-C-12-INV |Page 30 | X-BTWB-400 |Page 106 |
| VAX-4 |Page 42 | WW-MAT-500 |Page 94 | X-CB28-BL-B100 |Page 113 |
| VAX-4B |Page 42 | X-1GDPSW-13A |Page 81, 112 | X-CB28-W-B100 |Page 113 |
| VAX-4B-6 |Page 42 | X-2GDPSW-13A |Page 81, 112 | X-CB90-1H1H |Page 102 |
| VAX-5 |Page 42 | X-2GSW2W-10A |Page 81, 112 | X-CB90-1H2H |Page 102 |
| VAX-5-PH |Page 42 | X-3GSW2W-10A |Page 81, 112 | X-CB90-2H2H |Page 102 |
| VAX-6 |Page 42 | X-AB-8/10-100-B4 |Page 110 | X-CBC-1 |Page 102 |
| VC-4 |Page 42 | X-AB-M10-60-B100 |Page 110 | X-CBC-2 |Page 102 |
| VC-4R |Page 42 | X-AB-M10-60-B4 |Page 110 | X-CBC-3 |Page 102 |
| VCC-20S |Page 13 | X-AB-M10-B100 |Page 110 | X-CBC-4 |Page 102 |
| VCL-24S |Page 13 | X-BBSM-25 |Page 81, 112 | X-CBC-5 |Page 102 |
| VCL-45S |Page 13 | X-BBSM2G-25 |Page 81, 112 | X-CBC-6 |Page 102 |
| VCM-20S |Page 13 | X-BBSM2G-35 |Page 81, 112 | X-CBC-8 |Page 102 |
| VCMX-20S |Page 13 | X-BBSM-35 |Page 81, 112 | X-CBU-4141 |Page 102 |
| VCMX-20STA |Page 64 | X-BGC-M10 |Page 102 | X-CEC4H-4121 |Page 103 |
| VCR-1 |Page 60 | X-BGC-M12 |Page 102 | X-CEC4H-4141 |Page 103 |
| VCRT-1 |Page 60 | X-BGC-M6 |Page 102 | X-CH-1A-45 |Page 102 |

Index - Part Code

| | | | | | | | | |
|-----------------|-----------|-----|-------------------|-----------|-----|------------------|-----------|-----|
| X-CH-1A-45135 |Page | 102 | X-CN-M12-B8 |Page | 108 | X-CTMD-FB-150 |Page | 104 |
| X-CH4121-1.5-3M |Page | 102 | X-CN-M6-B100 |Page | 108 | X-CTMD-FB-225 |Page | 104 |
| X-CH4121-1.5-6M |Page | 102 | X-CN-M6-B8 |Page | 108 | X-CTMD-FB-300 |Page | 104 |
| X-CH4121-2.5-3M |Page | 102 | X-CN-M8-B100 |Page | 108 | X-CTMD-FB-450 |Page | 104 |
| X-CH4121-2.5-6M |Page | 102 | X-CN-M8-B8 |Page | 108 | X-CTMD-FB-50 |Page | 104 |
| X-CH4141-1.5-3M |Page | 102 | X-CNSS-M10-B100 |Page | 108 | X-CTMD-FB-75 |Page | 104 |
| X-CH4141-1.5-6M |Page | 102 | X-CNSS-M10-B6 |Page | 108 | X-CTMD-IS-100 |Page | 105 |
| X-CH4141-2.5-3M |Page | 102 | X-CNSS-M12-B100 |Page | 108 | X-CTMD-IS-150 |Page | 105 |
| X-CH4141-2.5-6M |Page | 102 | X-CNSS-M12-B6 |Page | 108 | X-CTMD-IS-225 |Page | 105 |
| X-CH4182-2.5-3M |Page | 102 | X-CNSS-M6-B100 |Page | 108 | X-CTMD-IS-300 |Page | 105 |
| X-CH4182-2.5-6M |Page | 102 | X-CNSS-M6-B6 |Page | 108 | X-CTMD-IS-450 |Page | 105 |
| X-CH4-IS |Page | 102 | X-CNSS-M8-B100 |Page | 108 | X-CTMD-IS-75 |Page | 105 |
| X-CH-A |Page | 102 | X-CNSS-M8-B6 |Page | 108 | X-CTMD-PG-100-3M |Page | 104 |
| X-CHBC-3M |Page | 102 | X-CSG-208-B10 |Page | 112 | X-CTMD-PG-150-3M |Page | 104 |
| X-CHBP1W-4141 |Page | 102 | X-CSG-20W-B10 |Page | 112 | X-CTMD-PG-225-3M |Page | 104 |
| X-CHBP2W-4141 |Page | 102 | X-CSG-25B-B10 |Page | 112 | X-CTMD-PG-300-3M |Page | 104 |
| X-CHCB-4121 |Page | 104 | X-CSG-25W-B10 |Page | 112 | X-CTMD-PG-450-3M |Page | 104 |
| X-CHCB-4121B6 |Page | 104 | X-CS-M1030-B100 |Page | 109 | X-CTMD-PG-50-3M |Page | 104 |
| X-CHCB-4141 |Page | 104 | X-CS-M1030-B5 |Page | 109 | X-CTMD-PG-600-3M |Page | 104 |
| X-CHCB-4141B6 |Page | 104 | X-CS-M1050-B100 |Page | 109 | X-CTMD-PG-75-3M |Page | 104 |
| X-CHCW-4121 |Page | 104 | X-CS-M1050-B5 |Page | 109 | X-CTMD-R-150100 |Page | 105 |
| X-CHCW-4121B6 |Page | 104 | X-CS-M830-B5 |Page | 109 | X-CTMD-R-225150 |Page | 105 |
| X-CHCW-4141 |Page | 104 | X-CS-M850-B100 |Page | 109 | X-CTMD-R-300150 |Page | 105 |
| X-CHCW-4141B6 |Page | 104 | X-CS-M850-B5 |Page | 109 | X-CTMD-R-450300 |Page | 105 |
| X-CHU-4121 |Page | 103 | X-CT100-2.5-B100 |Page | 113 | X-CTMD-R-600450 |Page | 105 |
| X-CHU-4141 |Page | 103 | X-CT300-4.8B-B100 |Page | 113 | X-CTMD-SOB-100 |Page | 105 |
| X-CHU-4162 |Page | 103 | X-CT300-4.8W-B100 |Page | 113 | X-CTMD-SOB-150 |Page | 105 |
| X-CHWF-1 |Page | 102 | X-CT300-7.6B-B100 |Page | 113 | X-CTMD-SOB-225 |Page | 105 |
| X-CHWF-2 |Page | 102 | X-CT480-13B-B100 |Page | 113 | X-CTMD-SOB-300 |Page | 105 |
| X-CHWF-3 |Page | 102 | X-CT730-13B-B100 |Page | 113 | X-CTMD-SOB-450 |Page | 105 |
| X-CHWF-4 |Page | 102 | X-CTCHD-PG |Page | 105 | X-CTMD-SOB-75 |Page | 105 |
| X-CHZB-4121 |Page | 103 | X-CTC-VC-HDG |Page | 105 | X-CTMD-TP-100 |Page | 104 |
| X-CHZB-4141 |Page | 103 | X-CTH-PG-100 |Page | 105 | X-CTMD-TP-150 |Page | 104 |
| X-CIC4H-4121 |Page | 103 | X-CTH-PG-150 |Page | 105 | X-CTMD-TP-225 |Page | 104 |
| X-CIC4H-4141 |Page | 103 | X-CTH-PG-225 |Page | 105 | X-CTMD-TP-300 |Page | 104 |
| X-CNLS-M10-B100 |Page | 108 | X-CTH-PG-300 |Page | 105 | X-CTMD-TP-450 |Page | 104 |
| X-CNLS-M10-B6 |Page | 108 | X-CTH-PG-50 |Page | 105 | X-CTMD-TP-75 |Page | 104 |
| X-CNLS-M12-B100 |Page | 108 | X-CTH-PG-75 |Page | 105 | X-CTMS-R-300225 |Page | 105 |
| X-CNLS-M12-B6 |Page | 108 | X-CTMD-B-100 |Page | 104 | X-CWB-4121 |Page | 103 |
| X-CNLS-M5-B100 |Page | 108 | X-CTMD-B-150 |Page | 104 | X-CWB-4141 |Page | 103 |
| X-CNLS-M6-B6 |Page | 108 | X-CTMD-B-225 |Page | 104 | X-CWB-4182 |Page | 103 |
| X-CNLS-M8-B100 |Page | 108 | X-CTMD-B-300 |Page | 104 | X-CY0.75-2C-100 |Page | 113 |
| X-CNLS-M8-B6 |Page | 108 | X-CTMD-B-450 |Page | 104 | X-CY0.75-2C-50 |Page | 113 |
| X-CN-M10-B100 |Page | 108 | X-CTMD-B-50 |Page | 104 | X-CY1.5-2C-100 |Page | 113 |
| X-CN-M10-B8 |Page | 108 | X-CTMD-B-75 |Page | 104 | X-CY1.5-2C-50 |Page | 113 |
| X-CN-M12-B100 |Page | 108 | X-CTMD-FB-100 |Page | 104 | X-CY1-2C-100 |Page | 113 |

Index - Part Code

| | | | | | | | | |
|----------------|-----------|---------|------------------|-----------|---------|---------------------|-----------|-----|
| X-CY1-2C-50 |Page | 113 | X-PCL-192-202 |Page | 111 | X-PVCU-3/4E-90 |Page | 88 |
| X-DIAL-M10-B50 |Page | 110 | X-PCL-20-25 |Page | 111 | X-PVCU-3/4-EC |Page | 88 |
| X-DIAL-M12-B50 |Page | 110 | X-PCL-210-220 |Page | 111 | X-PVCU-3/4-MAC |Page | 88 |
| X-DIAL-M8-B100 |Page | 110 | X-PCL-26-30 |Page | 111 | X-PVCU-3/4P-3M |Page | 88 |
| X-DIA-M10-B10 |Page | 110 | X-PCL-38-43 |Page | 111 | X-PVCU-3/4-PIN |Page | 88 |
| X-DIA-M10-B50 |Page | 110 | X-PCL-44-49 |Page | 111 | X-PVCU-3/4-R |Page | 88 |
| X-DIA-M12-B10 |Page | 110 | X-PCL-50-55 |Page | 111 | X-PVCU-3/4-RE |Page | 88 |
| X-DIA-M12-B50 |Page | 110 | X-PCL-56-61 |Page | 111 | X-PVCU-3/4-SOC |Page | 88 |
| X-DIA-M8-B10 |Page | 110 | X-PCL-62-67 |Page | 111 | X-PVCU-3/4-TP |Page | 88 |
| X-DIA-M8-B100 |Page | 110 | X-PCL-68-73 |Page | 111 | X-PVCU-SQBQSC-110MM |Page | 88 |
| X-DIA-ST |Page | 110 | X-PCL-75-80 |Page | 111 | X-RBN-M6-12-B100 |Page | 108 |
| X-DPSW-20A |Page | 61 | X-PCL-82-86 |Page | 111 | X-RBN-M6-12-B20 |Page | 108 |
| X-DPSW-20A |Page | 112 | X-PCL-87-92 |Page | 111 | X-RBN-M6-16-B100 |Page | 108 |
| X-EB-M10-B10 |Page | 110 | X-PCL-95-102 |Page | 111 | X-RBN-M6-16-B20 |Page | 108 |
| X-EB-M8-B25 |Page | 110 | X-PC-M10 |Page | 103 | X-RBN-M6-20-B100 |Page | 108 |
| X-FP2H |Page | 103 | X-PC-M8 |Page | 103 | X-RBN-M6-20-B20 |Page | 108 |
| X-FP3H |Page | 103 | X-PCU-108-116 |Page | 111 | X-SB810-B100 |Page | 110 |
| X-FP3H-90 |Page | 103 | X-PCU-15-18 |Page | 111 | X-SB810-B4 |Page | 110 |
| X-FP4H |Page | 103 | X-PCU-20-25 |Page | 111 | X-SBL2810-B100 |Page | 110 |
| X-FP5H |Page | 103 | X-PCU-26-30 |Page | 111 | X-SBL810-B100 |Page | 110 |
| X-FS |Page | 81, 112 | X-PCU-32-36 |Page | 111 | X-SBL810-B4 |Page | 110 |
| X-FS8BMC |Page | 81, 112 | X-PCU-38-42 |Page | 111 | X-SCA-M10 |Page | 104 |
| X-FSN |Page | 81, 112 | X-PCU-44-49 |Page | 111 | X-SCA-M10-B30 |Page | 104 |
| X-FSNBMC |Page | 81, 112 | X-PCU-56-61 |Page | 111 | X-SCA-M12 |Page | 104 |
| X-HNC-M10-B25 |Page | 108 | X-PCU-75-80 |Page | 111 | X-SCA-M12-B30 |Page | 104 |
| X-HNC-M8-B10 |Page | 108 | X-PCU-87-92 |Page | 111 | X-SCA-M6 |Page | 104 |
| X-HN-M10-B100 |Page | 108 | X-PT |Page | 61, 112 | X-SCA-M6-B30 |Page | 104 |
| X-HN-M10-B25 |Page | 108 | X-PVCU-1-1/4-3M |Page | 88 | X-SCA-M8 |Page | 104 |
| X-HN-M12-B100 |Page | 108 | X-PVCU-1-1/4-45T |Page | 88 | X-SCA-M8-B30 |Page | 104 |
| X-HN-M12-B25 |Page | 108 | X-PVCU-1-1/4-CAP |Page | 88 | X-SCON-M8-B100 |Page | 109 |
| X-HN-M6-B100 |Page | 108 | X-PVCU-1-1/4E-45 |Page | 88 | X-SCON-M8-B4 |Page | 109 |
| X-HN-M6-B25 |Page | 108 | X-PVCU-1-1/4E-90 |Page | 88 | X-SPW-M10-B100 |Page | 107 |
| X-HN-M8-B100 |Page | 108 | X-PVCU-1-1/4-MAC |Page | 88 | X-SPW-M12-B100 |Page | 107 |
| X-HN-M8-B25 |Page | 108 | X-PVCU-1-1/4-PIN |Page | 88 | X-SPW-M6-B100 |Page | 107 |
| X-LBSA-0810L |Page | 110 | X-PVCU-1-1/4-R |Page | 88 | X-SPW-M8-B100 |Page | 107 |
| X-LBSA-1010L |Page | 110 | X-PVCU-1-1/4-RE |Page | 88 | X-SQPW-M10-B100 |Page | 107 |
| X-LBSA-1025L |Page | 110 | X-PVCU-1-1/4-SOC |Page | 88 | X-SQPW-M10-B6 |Page | 107 |
| X-PBS |Page | 109 | X-PVCU-1-1/4-TP |Page | 88 | X-SQPW-M12-B100 |Page | 107 |
| X-PC |Page | 103 | X-PVCU-1E-90 |Page | 88 | X-SQPW-M12-B6 |Page | 107 |
| X-PCL-108-116 |Page | 111 | X-PVCU-1-MAC |Page | 88 | X-SQPW-M6-B100 |Page | 107 |
| X-PCL-121-127 |Page | 111 | X-PVCU-1P-3M |Page | 88 | X-SQPW-M6-B6 |Page | 107 |
| X-PCL-12-14 |Page | 111 | X-PVCU-1-SOC |Page | 88 | X-SQPW-M8-B6 |Page | 107 |
| X-PCL-131-141 |Page | 111 | X-PVCU-1TP |Page | 88 | X-SS10-30-B10 |Page | 109 |
| X-PCL-15-19 |Page | 111 | X-PVCU-3/4-45T |Page | 88 | X-SS10-30-B100 |Page | 109 |
| X-PCL-159-163 |Page | 111 | X-PVCU-3/4-CAP |Page | 88 | X-SS10-35-B10 |Page | 109 |
| X-PCL-165-168 |Page | 111 | X-PVCU-3/4-E45 |Page | 88 | X-SS10-35-B100 |Page | 109 |

Index - Part Code

| | | | | | |
|------------------|-----------|-----|-----------------|-----------|-----|
| X-SS10-50-B10 |Page | 109 | X-WA12-25-B100 |Page | 107 |
| X-SS10-50-B100 |Page | 109 | X-WA12-25-B25 |Page | 107 |
| X-SS12030-B100 |Page | 109 | X-WA12-30-B100 |Page | 107 |
| X-SS12-25-B10 |Page | 109 | X-WA12-40-B100 |Page | 107 |
| X-SS12-25-B100 |Page | 109 | X-WA6-25-B100 |Page | 107 |
| X-SS12-30-B10 |Page | 109 | X-WA6-25-B25 |Page | 107 |
| X-SS12-40-B10 |Page | 109 | X-WA6-30-B100 |Page | 107 |
| X-SS12-40-B100 |Page | 109 | X-WA6-40-B100 |Page | 107 |
| X-SS6-30-B10 |Page | 109 | X-WA6-25-B100 |Page | 107 |
| X-SS6-30-B100 |Page | 109 | X-WA6-25-B25 |Page | 107 |
| X-SS8-30-B10 |Page | 109 | X-WA6-30-B100 |Page | 107 |
| X-SS8-30-B100 |Page | 109 | X-WA6-40-B100 |Page | 107 |
| X-SS8-40-B10 |Page | 109 | X-WA-M10-B100 |Page | 107 |
| X-SS8-40-B100 |Page | 109 | X-WA-M12-B100 |Page | 107 |
| X-SS8-50-B10 |Page | 109 | X-WA-M6-B100 |Page | 107 |
| X-SS8-50-B100 |Page | 109 | X-WA-M8-B100 |Page | 107 |
| X-SY1.5-3C-100 |Page | 113 | X-WF0.75-2C-50 |Page | 113 |
| X-SY1.5-4C-100 |Page | 113 | X-WF0.75-3C-50 |Page | 113 |
| X-SY1.5-4C-50 |Page | 113 | X-WF1.5-3C-50 |Page | 113 |
| X-SY1.5-5C-100 |Page | 113 | X-WF1-2C-100 |Page | 113 |
| X-SY1.5-5C-50 |Page | 113 | X-WF1-2C-50 |Page | 113 |
| X-SY1-4C-100 |Page | 113 | X-WF1-3C-50 |Page | 113 |
| X-SY2.5-3C-100 |Page | 113 | X-WF2.5-3C-50 |Page | 113 |
| X-SY2.5-3C-50 |Page | 113 | X-WN-M10-B100 |Page | 108 |
| X-SY2.5-5C-100 |Page | 113 | X-WN-M12-B100 |Page | 108 |
| X-SY2.5-5C-50 |Page | 113 | X-WN-M6-B100 |Page | 108 |
| X-TBR4H |Page | 103 | X-WN-M8-B100 |Page | 108 |
| X-TBR4H-90 |Page | 103 | X-WPB-7MM |Page | 109 |
| X-TEK5.5-25-B100 |Page | 109 | X-WPG-8/10MM |Page | 109 |
| X-TEK5.5-38-B100 |Page | 109 | X-WPR-5MM |Page | 109 |
| X-TEK-MAGBIT |Page | 109 | X-YY0.74-4X-50 |Page | 113 |
| X-TF10-1 |Page | 109 | X-YY0.75-4C-100 |Page | 113 |
| X-TF10-1-1/2 |Page | 109 | X-YY1.5-2C-100 |Page | 113 |
| X-TF10-2 |Page | 109 | X-YY1.5-4C-100 |Page | 113 |
| X-TF10-2-1/2 |Page | 109 | X-YY1.5-4C-50 |Page | 113 |
| X-TF10-1 |Page | 109 | X-YY1.5-7C-100 |Page | 113 |
| X-TF10-1-1/2 |Page | 109 | X-YY1.5-7C-50 |Page | 113 |
| X-TF10-2 |Page | 109 | X-YY2.5-3C-100 |Page | 113 |
| X-TR-M10-3M |Page | 104 | X-YY2.5-4C-100 |Page | 113 |
| X-TR-M12-3M |Page | 104 | X-YY2.5-4C-50 |Page | 113 |
| X-TR-M6-3M |Page | 104 | | | |
| X-TR-M8-3M |Page | 104 | | | |
| X-WA10-25-B100 |Page | 107 | | | |
| X-WA10-25-B25 |Page | 107 | | | |
| X-WA10-30-B100 |Page | 107 | | | |
| X-WA10-40-B100 |Page | 107 | | | |

Notes

This image shows a single sheet of white paper with horizontal ruling lines. The lines are evenly spaced and run across the width of the page. There are no margins, text, or other markings on the paper.


Notes

[illegible]

Notes

[illegible]

ENGINEER ON CALL



/pumph.co.uk



/pumphouseltd



/pumphouseltd



/pump-house-ltd



/pumphousepumps