



TYPE 2 (BLACK) BRACKETS



These flat-packed, self assembly brackets provide a professional finish to the installation of wall mounted outdoor condensing units and air source heat pumps. The Type 2 brackets have a crossbar allowing the uprights to be spaced exactly as required, and include wall spacers to help level the unit on uneven walls. All components receive a powder coating, with a scratch resistant, textured finish in a colour (RAL 7032) to match most brands of condensing units and domestic air source heat pumps.

FEATURES

- Integral spirit level for easier, correct installation
- Uprights mount anywhere on the crossbar which enables the arm span to be adjusted easily
- Adjustable wall spacers to level the arms
- Safe working load up to 250kg
- Suitable to match most brands of condensing units and domestic air source heat pumps
- Extra long arms (up to 660mm available for larger condensing units)
- Textured finish in (RAL 7032)

THE PACKAGE

- Crossbar with spirit level
- 2/3 x support arms
- 2/3 x uprights
- Fixings
- Installation instructions

RELATED PRODUCTS


- All guards
- Collection trays

NB: Sea salts are very corrosive and affect both ferrous and non-ferrous metals. Coastal installations are particularly at risk as they are frequently exposed to sea salt solutions followed by dry periods, where this wet/dry cycle produces a very corrosive environment. We strongly recommend that in such locations only our stainless steel brackets are installed.

WEATHER PROTECTION PROCESS



PROCESS ONE
Corrosion resistant raw material, often referred to as Zintec



PROCESS TWO
Zinc phosphating process multi stage cleaning and dipping chemical zinc



PROCESS THREE
ED coating process: electrophoretic deposition (aka ED or EPD) coating



PROCESS FOUR
Epoxy polyester powder coating

Part code	Description	Safe working load*	Max load	Crossbar	Upright	Support arm	Weight
CBR2-XL-BL	Type 2 Bracket – XL	250kg	500kg	1040mm	550mm	660mm	16.2kg
CBR2-XL-3A-BL	Type 2 Bracket – XL (3 arms)	250kg	500kg	1040mm	550mm	660mm	16.2kg
CBR2-XXL-3A-BL	Type 2 Bracket – Double XL (3 arms)	200kg	400kg	1040mm	550mm	780mm	17.3kg
CBR2-XXL-3A-BL-D	Type 2 Bracket – Double XL (3 arms)	200kg	400kg	1120mm	550mm	780mm	17.3kg

*All brackets are tested to twice the safe working loads at an independent UK facility.

BRACKETS TYPE 2 BRACKETS

(black)

The DiversiTech International sales team are available to answer your questions or queries on this product. Our experts are waiting for your call +44 (0)115 900 5858 or if you prefer send an email to sales@diversitech.com or visit www.diversitech.global