## PORTABLES TECHNICAL DATA SHEET

DiversiTech

INSTAL



The Pump House portable air conditioners are suitable for offices, computer rooms and light commercial use. The cooling only model is ideal for cooling flats, conservatories or loft conversions during hot summer months. The heat pump model can also be used as an energy efficient form of heating along with cooling. The units come with a hose, tray, remote control and wall kit. Spare parts are available upon request.

### **FEATURES**

- Meets EN14511 standard and EU commission regulations 206/2012
- Proven well-tested designs
- LED display and remote control (both models)
- Flexible exhaust hose 1.5m (both models)
- Suitable for areas up to 26m<sup>2</sup>
- No pump required self evaporating condensate. Water hose needs to be connected when in heat pump mode for dehumidification
- Natural Refrigerant R290
- Ultra-low GWP
- Future proofed Quota free

#### THE PACKAGE

- Portable unit
- Remote controller
- Installation instructions

# RELATED PRODUCTS

• Through all air conditioning

Part code	Description	Cool capacity (Btu/kW)	Heat capacity (Btu/kW)	Watts	Amps	Air flow volume	EER	СОР	dB(A) sound power level
PAC-C-12	Portable (cooling)	12,000/3.3	N/A	1350W	5.9A	370m³/h	2.6	N/A	65
PAC-H-12	Portable (heat pump)	12,000/3.3	10,000/2.9	1350W	5.9A	370m³/h	2.6	2.6	65

Part code	Description	Height	Width	Depth	Weight	Hose length	Refrigerant	Cooling area
PAC-C-12	Portable (cooling)	765mm	467mm	397mm	34kg	1.5m	R290	16-26m <sup>2</sup>
PAC-C-12	Portable (cooling)	765mm	467mm	397mm	34kg	1.5m	R290	16-26m <sup>2</sup>

#### AC PORTABLES

Cooling / heating

The DiversiTech International sales team are available to answer your questions or queries on this product. Our experts are waiting for your call +44 (0)115 900 5858 or if you prefer send an email to sales@diversitech.com or visit www.diversitech.global



Glaisdale Drive East Nottingham NG8 4LY United Kingdom