RA 1000FS/RA 1000HS TECHNICAL DATA SHEET

DIVERSITECH

REFRIGERANT SAVER COUPLINGS



FEATURES

- Solid brass construction
- Two sizes of straight valve
- Ultra-compact right angle valve for tight spaces
- Fitting does not depress Schrader™ during installation easier to install, no refrigerant loss
- · Seals compatible with all refrigerants and oils
- Diamond knurl for easy grip
- Available in either 1/4" or 5/16" Flare sizes

Туре	RA 1000HS	RA 1000FS
Connections	5/16" MFL x 5/16" FFL	1/4" MFL x 1/4" FFL
Height	58 mm	58 mm
Working pressure	55 bar / 800 Psi	41 bar / 600 Psi
Spare seals	RA 1000 Gasket	RA 1000 Gasket

1/4" SAE = 7/16" UNF 5/16" SAE = 1/2" UNF

> COUPLERS RA 1000FS/RA 1000HS



The DiversiTech International sales team are available to answer your questions or queries on this product. Our experts are waiting for your call +44 (0)115 900 5858 or if you prefer send an email to sales@diversitech.com or visit www.diversitech.global



Refrigerant saver couplings with valve core depressors.

This family of service fittings provides a convenient, safe and reliable way of connecting to refrigeration or air conditioning systems without releasing refrigerant to the environment. Each valve attaches to the system without depressing the valve core. Once installed, opening the knob depresses the valve core on the system and simultaneously opens the valve inside.



Glaisdale Drive East Nottingham NG8 4LY United Kingdom