

## PRO-SCALE-GB LIME SCALE REMOVER



Pro-Scale removes lime scale, slime and algae build-up from heat exchangers, cooling towers, pipework, and condensers. Pro-Scale will increase system efficiency and reduce head pressure.

**LIME SCALE  
REMOVER**


**5L**

**MIX RATIO**  
3L of Pro-Scale  
to 100L water  
in system

**CONCENTRATED**

## FEATURES

- Increases system capacity and efficiency, and reduces head pressure
- Removes lime scale, slime and algae build-up from heat exchangers, cooling towers, pipework and condensers



## INSTRUCTIONS

Wear eye and skin protection when using the product to avoid irritation. When cleaning the system, ensure that the pump and compressor are working normally. Add three litres of Pro-Scale for each 100 litres of water in the system. Turn off bleed line, and allow Pro-Scale to circulate through the system for 24 to 48 hours. Drain the system, or increase the bleed rate 2-3 times above the normal setting to dilute Pro-Scale and flush the system. Pro-Scale solution will change colour from red to yellow as it dissolves scale. If the system water turns yellow, add more Pro-Scale until the system water turns red, and continue to circulate Pro-Scale through the system. Repeat the process until the Pro-Scale solution maintains red colour. Drain the system and flush with fresh water. Test Pro-Scale on a small area to be certain it is suitable for tower and basin cleaning. Galvanised surfaces may require special treatment.

## SAFETY

**CONTAINS:** Phosphoric acid: EC number 231-633-2



**DANGER!** Causes severe skin burns and eye damage. May be harmful if swallowed. May be corrosive to metals. Keep out of reach of children. Read label before use. Do not breathe the mist, vapours, or spray. Wear rubber, nitrile or neoprene protective gloves and clothing, and safety goggles or face shield to protect eyes and face. Store locked up and in a plastic container or one with a resistant inner liner. Dispose of contents and container in accordance with international and local regulations. Keep only in original container. Absorb spillage to prevent material damage.

**FIRST AID: IF SWALLOWED:** Rinse mouth. Do NOT induce vomiting. Immediately call your National Poison Centre information service or a doctor. **IF ON SKIN (or hair):** Remove immediately all contaminated clothing. Rinse SKIN with water/shower for a minimum of fifteen minutes. Wash contaminated clothing before reuse. Immediately call your National Poison Centre information service or a doctor. **IF INHALED:** Remove victim to fresh air and keep at rest in a position comfortable for breathing. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call your National Poison Centre information service or a doctor.

Do not use water.

See Safety Data Sheet for further details regarding safe use of this product.

NON-WARRANTY: This product is provided "as is". Seller specifically disclaims any and all warranties, whether expressed, implied, statutory or otherwise and specifically disclaims all implied warranties including without limitation, any implied warranties of merchantability or fitness for a particular purpose or those arising by reason of custom or usage in the trade or by course of dealing.

**SERVICE & MAINTENANCE**  
**PRO-SCALE**  
LIME SCALE REMOVER

The DiversiTech International sales team are available to answer your questions or queries on this product. Our experts are waiting for your call +44 (0)115 900 5858 or if you prefer send an email to [sales@diversitech.com](mailto:sales@diversitech.com) or visit [www.diversitech.global](http://www.diversitech.global)

**DIVERSITECH**  
INTERNATIONAL

Glaisdale Drive East  
Nottingham NG8 4LY  
United Kingdom