PH-O.8L-HL TECHNICAL DATA SHEET

DIVERSITECH

PH-0.8L-HL - 0.8 LITRE BOILER PUMP






When space and lift are a challange, our shallow tank pump enables installation in compact areas such as below kitchen units. The 6 metre discharge lift helps with the flexibility of the installation. Suitable for both floor and wall mounting and comes with a quick release check valve. Suitable for boilers up to 100kW.

FEATURES

- High discharge head of 6 metres
- Quiet operation
- 300ml drink cycle
- Quality design and engineered product
- 6 metres of 9.5mm (3/8") ID flexible drain hose
- Quick release quarter turn non return valve



TANK CAP. 0.8L

THE PACKAGE

- 1 Litre tank pump
- 6m of 9.5mm (3/8") hose
- Quick release 1/4 turn check
 valve
- 22mm adaptor
- Hose clip

RELATED PRODUCTS

- Braided hose
- S&V adaptors
- Non-return valve
- PVC coated insulation

DECIBEL RATING 43 dB(A)

Part code	Max. lift	Discharge siz	e PSI	w	Watts		IP		Amps	Volts	Hz
PH-0.8L-HL	6m	9.5mm (3/8")	8.5	75W			20		0.74A	240V	50Hz
High level alarm	Inlet height	Weight (Cable length	Drink	cycle	On le	vel	Off level	Reserve befo	ore overflow	Alarm level
Volt free	45mm	1.9kg 1	.8mm	300ml	10ml 2:		ım	13.5mm	175ml		29mm

PUMPS PH-0.8L-HL

MAX. FLOW 270 LPH

0.8 litre boiler pump

The DiversiTech International sales team are available to answer your questions or queries on this product. Our experts are waiting for your call +44 (0)115 900 5858 or if you prefer send an email to sales@diversitech.com or visit www.diversitech.global



Glaisdale Drive East Nottingham NG8 4LY United Kingdom