# BOSCH TOOLS

## **TECHNICAL DATA SHEET**



## CS-LD 1.0 LEAK DETECTOR







The BOSCH CS LD 1.0 leak detector detects Halogenated CFC, HCFC, HFC, HFO compounds, HC refrigerants such as butane and propane, Tracer Gas (95 %N2/5 %H2 mixture), ammonia.

It boasts a rubber keypad which provides positive actuation and tactile feedback, an ergonomic design with TPU overmold and ambidextrous operation.

Includes carrying case, spare filters and battery charger.

#### FEATURES

- Detects Halogenated CFC, HCFC, HFC, HFO compounds, HC refrigerants, Tracer Gas (95 %N2/5 %H2 mixture), ammonia, butane and propane.
- Meets or exceeds EN14624 performance standards.
- Ultimate Sensitivity of less than 1 g/yr.
- Electronic sensor lasts > 5 years.
- Large 61 mm backlit graphic LCD.
- Audible alarm with Mute and Visual Leak Size Indicator.
- Leak tracing mode to pinpoint hard to find leaks.
- 2-year warranty includes sensor.

## SPECIFICATIONS

Dimensions (L x W x H)	218 x 83 x 51 mm	
Probe Length	413 mm	
Weight	15mm Former Disc	
Sensor Life	22mm Former Disc	
Warm Up Time	28mm Former Disc	
Ultimate Sensitivity	7/8" Former Disc	
Power Supply	11/8" Former Disc	
Battery Life	15mm GUIDE	
Recharge time	22mm GUIDE	
Operating Temperature & Humidity	28mm GUIDE	
IP Rating	7/8" GUIDE	

### TEST RESULTS

	R-134A	R-1234yf	R-290
Static lower detection limit (g/a) <sup>1</sup>	1 g/a	1 g/a	0.5 g/a
Dynamic lower detection limit (g/a) <sup>1</sup>	1 g/a	1 g/a	0.5 g/a
Dynamic lower detection limit in a contaminated environment (g/a) <sup>1</sup>	12 g/a	10 g/a	4 g/a
Response time (s) <sup>1</sup>	0.5 sec	0.5 sec	0.5 sec
Zeroing time (s) <sup>2,3</sup>	-	-	-
Recovery time (s) <sup>2</sup>	14 sec	10 sec	6 sec

Grams per year / 2 seconds / 3 Not applicable. Subject to change

TOOLS

Glaisdale Drive East Nottingham NG8 4LY United Kingdom