WHISPA-Q-TRUNK TECHNICAL DATA SHEET



WHISPA-Q-TRUNK - ULTRA QUIET PUMP IN TRUNKING






WHISPA-Q-TRUNK

The WHISPA-Q-TRUNK is an industry first stand-alone pump in trunking for the future. Designed to provide ultra-quiet running utilising the new DC DIAPHRAGM PUMP TECHNOLOGY along with a stylish sleek ultra-cool design. This new pump offers easy installation and hassle free maintenance, whilst dramatically cutting running costs. A true silent, gentle giant that doesn't cost the earth.

FEATURES

- Low power consumption (approx 80% less than other models)
- High performance with a max. flow rate of 36L/hr
- Ultra quiet operation
- Low temperature motor does not exceed 27°C
- · Innovative design
- Added space for pipe and hose
- Alarm warning red LED





MAX. FLOW 33 LPH

THE PACKAGE Pump and trunking

- Ceiling rosette
- Anti-syphon valve
- Hose connector
- Silicone hose
- · Complete fixings accessories
- 400mm extra trunking

RELATED **PRODUCTS**

- Braided hose
- S&V adaptor
- · Squeezy fit



Section	Specification	Section	Specification
Capacity of AC	Up to 16kw / 54,000Btu/h	Available fluid	Condensate of 1~40°C
Power supply	220V 50/60Hz / 120V 50/60Hz	Dry running	Not advised
Power consumption	2.5W	Intermittant rating	3 minutes
Max discharge head	8m	Safety switch	Max 3 amp
Max flow rate	33L/h at zero meter	Pump size (mm)	106(W) x 52(H) x 550(L) + (400(L))
Outlet size	1/4" (6mm)	Weight	1.2kg

The DiversiTech International sales team are available to answer your questions or queries on this product. Our experts are waiting for your call +44 (0)115 900 5858 or if you prefer send an email to sales@diversitech.com or visit www.diversitech.global



Glaisdale Drive East Nottingham NG8 4LY United Kingdom